

Ps

ADOBE® PHOTOSHOP® CS5



ADOBE PHOTOSHOP CS5

VBSCRIPT SCRIPTING REFERENCE



© 2010 Adobe Systems Incorporated. All rights reserved.

Adobe® Creative Suite® 5 Photoshop® VBScript Scripting Reference for Windows®.

NOTICE: All information contained herein is the property of Adobe Systems Incorporated. No part of this publication (whether in hardcopy or electronic form) may be reproduced or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Adobe Systems Incorporated. The software described in this document is furnished under license and may only be used or copied in accordance with the terms of such license.

This publication and the information herein is furnished AS IS, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies, makes no warranty of any kind (express, implied, or statutory) with respect to this publication, and expressly disclaims any and all warranties of merchantability, fitness for particular purposes, and noninfringement of third party rights.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe®, the Adobe logo, Acrobat®, Illustrator®, and Photoshop® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Apple®, Mac OS®, and Macintosh® are trademarks of Apple Computer, Inc., registered in the United States and other countries. Microsoft®, and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries. JavaScript™ and all Java-related marks are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries. UNIX® is a registered trademark of The Open Group.

All other trademarks are the property of their respective owners.

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe Systems Incorporated. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Adobe Systems Incorporated, 345 Park Avenue, San Jose, California 95110, USA.

Contents

1	Introduction	5
	Changes Since Earlier Versions.....	5
2	VBScript Interface	6
	Working with the Properties Tables	6
	Working with the Methods Tables	6
	ActionDescriptor	8
	ActionList.....	11
	ActionReference	14
	Application	16
	ArtLayer.....	24
	ArtLayers.....	36
	BatchOptions	37
	BitmapConversionOptions	39
	BMPSaveOptions	40
	CameraRAWOpenOptions	41
	Channel	43
	Channels	44
	CMYKColor	50
	ColorSampler	51
	ColorSamplers	52
	ContactSheetOptions	53
	CountItem	55
	CountItems	56
	DCS1_SaveOptions	57
	DCS2_SaveOptions	58
	DICOMOpenOptions	59
	Document	60
	DocumentInfo	69
	Documents	72
	EPSOpenOptions	73
	EPSSaveOptions.....	74
	ExportOptionsIllustrator	75
	ExportOptionsSaveForWeb	76
	GalleryBannerOptions	78
	GalleryCustomColorOptions	79
	GalleryImagesOptions	80
	GalleryOptions.....	82
	GallerySecurityOptions	84
	GalleryThumbnailOptions	85
	GIFSaveOptions.....	86
	GrayColor.....	88
	HistoryState	89
	HistoryStates	90
	HSBColor.....	91
	IndexedConversionOptions	92

JPEGSaveOptions	94
LabColor	95
LayerComp.....	96
LayerComps.....	97
Layers.....	98
LayerSet	99
LayerSets	101
MeasurementLog	103
MeasurementScale	104
NoColor	105
Notifier.....	106
Notifiers.....	107
PathItem	109
PathItems	113
PathPoint.....	114
PathPointInfo.....	115
PathPoints.....	116
PDFOpenOptions	117
PDFSaveOptions	118
PhotoCDOpenOptions	121
PhotoshopSaveOptions.....	122
PICTFileSaveOptions	123
PicturePackageOptions.....	124
PixarSaveOptions	125
PNGSaveOptions	126
Preferences.....	127
PresentationOptions.....	132
RawFormatOpenOptions	133
RawSaveOptions.....	134
RGBColor.....	135
Selection	136
SGIRGBSaveOptions	141
SolidColor.....	142
SubPathInfo.....	143
SubPathItem.....	144
SubPathItems.....	145
TargaSaveOptions.....	146
TextFont.....	147
TextFonts.....	148
TextItem	149
TiffSaveOptions.....	155
XMPMetadata	157
3 Scripting Constants	158
Appendix A: Event ID Codes	175
Index	183

This reference describes the objects and commands in the Adobe® Photoshop® CS⁵ VBScript dictionary. A companion document, *Photoshop CS5 Scripting Guide*, describes basic scripting concepts and the Photoshop object model. This document provides reference details of the Photoshop object model, and additional information on VBScript-specific features.

This book contains the following sections:

- This introduction, which describes scripting support in Adobe Photoshop CS5, and lists changes to the VBScript interface since the previous release.
- [“VBScript Interface” on page 6](#), which describes the objects of the VBScript type library for Adobe Photoshop CS5.
- [“Scripting Constants” on page 158](#), which describes the enumerated values defined for use with Adobe Photoshop CS5 VBScript properties and methods.

Changes Since Earlier Versions

The following changes have been made to the VBScript object model and language support in Adobe Photoshop CS5:

We’ve made major changes around printing a document. After making such sweeping changes, your printing scripts may not work in CS5. The new printing interface makes maintaining backwards compatibility an issue and scripts will need to be updated for the new printing interface. See the [PrintOut](#) method.

- Modified enumerations:
 - `psSubtract (29)` has been added to the `PsBlendMode` enumeration.
 - `psDivide (30)` has been added to the `PsBlendMode` enumeration.
 - `psSubtract (27)` has been added to the `PsColorBlendMode` enumeration.
 - `psDivide (28)` has been added to the `PsColorBlendMode` enumeration.

2

VBScript Interface

The objects of the VBScript type library for Adobe Photoshop CS5 are presented alphabetically and in tabular format in this chapter.

Object properties and methods are described in separate tables for each object. See ['Working with the Properties Tables' on page 6](#) and ['Working with the Methods Tables' on page 6](#) for information on how to use these tables.

Sample code for several object model classes is given to help illustrate the syntax as well as usage of the object class.

Working with the Properties Tables

The Properties table for an object lists the following:

- The properties you can use with the object
- The value type for each property

When the value type is a constant or another object, the value is a hypertext link to the constant's or object's listing, as in the following Properties table sample.

- The property's input status: Read-only or Read-write.
- A description that explains what the property is

Descriptions are omitted for self-explanatory properties.

Property	Value Type	What it is
DisplayDialogs	PsDialogModes	Read-write. Controls whether or not Adobe Photoshop CS5 displays dialog boxes.

Working with the Methods Tables

The Methods table for an object lists the following:

- The method name
- Parameter(s)

When a parameter type or return value is a constant or another object, the value is a hypertext link to the constant's or object's listing. In the following Methods table sample, the parameter type `ActionDescriptor` is an object; the parameter type `DialogModes` is a constant; the return value `ActionDescriptor` is also an object.

Parameters can be required or optional. Optional parameters are indicated in the table by square brackets ([]). See ['Working with Method Parameters' on page 7](#) for information on using parameters.

- Return value type(s)
- A description, if applicable

Method	Parameter Type	Returns	What it does
ExecuteAction (EventID [, Descriptor] [, DisplayDialogs])	Number (Long) ActionDescriptor PsDialogModes	ActionDescriptor	Plays an ActionManager event.

Working with Method Parameters

Optional parameters are surrounded by square brackets ([]). In the following Methods table sample, the parameters `Descriptor` and `DisplayDialogs` are optional and the parameter `EventID` is not. See

Therefore, if you use the `ExecuteAction()` method for the object associated with the sample Methods table above, you *must* include an `EventID` value in the Parentheses following the method name. The `EventID` value must be a number, as indicated by the `Number (Long)` in the table's Parameter Type column.

If you use an optional parameter, you must separate the parameters with a comma, as indicated by the comma that precedes each optional parameter in the table.

Also, if you use an optional parameter, you must enter the values in the order they are listed in the table so that the JavaScript compiler knows which value you are entering. To skip an optional parameter, insert an extra comma to act as a placeholder.

The following sample provides values for an `EventID` and a `DisplayDialog`, but skips the `Descriptor` parameter (represented by the empty value between two commas). The statement executes action #4233 and allows only error type dialog boxes to be displayed.

```
appRef.ExecuteAction(4233, , Error)
```

ActionDescriptor

A record of key-value pairs for actions, such as those included on the Adobe Photoshop CS5 Actions menu.

Note: The `ActionDescriptor` class is part of the Action Manager functionality. See the *Photoshop CS5 Scripting Guide*.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Count	Number (Long)	Read-only. The number of keys contained in the descriptor.
typename	String	Read-only. The class name of the referenced <code>ActionDescriptor</code> object.

Methods

Method	Parameter Type	Returns	What it does
Clear ()			Clears the descriptor.
Erase (Key)	Number (Long)		Erases a key from the descriptor.
GetBoolean (Key)	Number (Long)	Boolean	Gets the value of a key of type boolean.
GetClass (Key)	Number (Long)	Number (Long)	Gets the value of a key of type class.
GetDouble (Key)	Number (Long)	Number (Double)	Gets the value of a key of type double.
GetEnumerationType (Key)	Number (Long)	Number (Long)	Gets the enumeration type of a key.
GetEnumerationValue (Key)	Number (Long)	Number (Long)	Gets the enumeration value of a key.
GetInteger (Key)	Number (Long)	Number (Long)	Gets the value of a key of type integer.
GetKey (Index)	Number (Long)	Number (Long)	Gets the ID of the <i>N</i> th key.
GetList (Key)	Number (Long)	ActionList	Gets the value of a key of type list.
GetObjectType (Key)	Number (Long)	Number (Long)	Gets the class ID of an object in a key of type object.

Method	Parameter Type	Returns	What it does (Continued)
GetObjectValue (Key)	Number (Long)	ActionDescriptor	Gets the value of a key of type object.
GetPath (Key)	Number (Long)	String	Gets the value of a key of type Alias. Returns a String that represents a file path.
GetReference (Key)	Number (Long)	ActionReference	Gets the value of a key of type ActionReference .
GetString (Key)	Number (Long)	String	Gets the value of a key of type String.
GetType (Key)	Number (Long)	PsDescValueType	Gets the type of a key.
GetUnitDoubleType (Key)	Number (Long)	Number (Long)	Gets the unit type of a key of type UnitDouble.
GetUnitDoubleValue (Key)	Number (Long)	Number (Double)	Gets the value of a key of type UnitDouble.
HasKey (Key)	Number (Long)	Boolean	Checks whether the descriptor contains the provided key.
IsEqual (otherDesc)	ActionDescriptor	Boolean	Determines whether the descriptor is the same as another descriptor.
PutBoolean (Key, Value)	Number (Long) Boolean		Sets the value for a key whose type is Boolean.
PutClass (Key, Value)	Number (Long) Number (Long)		Sets the value for a key whose type is class.
PutDouble (Key, Value)	Number (Long) Number (Double)		Sets the value for a key whose type is double.
PutEnumerated (Key, EnumType, Value)	Number (Long) Number (Long) Number (Long)		Sets the enumeration type and value for a key.
PutInteger (Key, Value)	Number (Long) Number (Long)		Sets the value for a key whose type is integer.
PutList (Key, Value)	Number (Long) ActionList		Sets the value for a key whose type is an ActionList object.

Method	Parameter Type	Returns	What it does (Continued)
PutObject (Key, ClassID, Value)	Number (Long) Number (Long) ActionDescriptor		Sets the value for a key whose type is an Action Descriptor.
PutPath (Key, Value)	Number (Long) String		Sets the value for a key whose type is path. The Value argument takes a String that represents a file path.
PutReference (Key, Value)	Number (Long) ActionReference		Sets the value for a key whose type is an object reference.
PutString (Key, Value)	Number (Long) String		Sets the value for a key whose type is String.
PutUnitDouble (Key, UnitID, Value)	Number (Long) Number (Long) Number (Double)		Sets the value for a key whose type is a unit value formatted as a double.

ActionList

This object provides an array-style mechanism for storing data. It can be used for low-level access into Photoshop.

This object is ideal when storing data of the same type. All items in the list must be the same type.

You can use the "put" methods, such as `putBoolean()`, to append new elements, and can clear the entire list using `clear()`, but cannot otherwise modify the list.

Note: The `actionList` object is part of the Action Manager functionality. For details on using the Action Manager, see the *Photoshop CS5 Scripting Guide*.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Count	Number (Long)	Read-only. The number of commands that comprise the action.
typename	String	Read-only. The class name of the referenced <code>actionList</code> object.

Methods

With the exception of the `Clear()` method, you use the methods of this object to either get the value of a specific type of data in the list or set (put) the value type.

Method	Parameter Type	Returns	What it does
Clear ()			Clears the list.
GetBoolean (Index)	Number (Long)	Boolean	Gets the value of a list item of type boolean.
GetClass (Index)	Number (Long)	Number (Long)	Gets the value of a list item of type class.
GetDouble (Index)	Number (Long)	Number (Double)	Gets the value of a list item of type double.
GetEnumerationType (Index)	Number (Long)	Number (Long)	Gets the enumeration type of a list item.
GetEnumerationValue (Index)	Number (Long)	Number (Long)	Gets the enumeration value of a list item.
GetInteger (Index)	Number (Long)	Number (Long)	Gets the value of a list item of type integer.
GetList (Index)	Number (Long)	ActionList	Gets the value of a list item of type list.

Method	Parameter Type	Returns	What it does (Continued)
GetObjectType (Index)	Number (Long)	Number (Long)	Gets the class ID of a list item of type object.
GetObjectValue (Index)	Number (Long)	ActionDescriptor	Gets the value of a list item of type object.
GetPath (Index)	Number (Long)	String	Gets the value of a list item of type Alias. Returns a <code>String</code> that represents a file path.
GetReference (Index)	Number (Long)	ActionReference	Gets the value of a list item of type ActionReference .
GetString (Index)	Number (Long)	String	Gets the value of a list item of type <code>String</code> .
GetType (Index)	Number (Long)	PsDescValueType	Gets the type of a list item.
GetUnitDoubleType (Index)	Number (Long)	Number (Long)	Gets the unit value type of a list item of type <code>Double</code> .
GetUnitDoubleValue (Index)	Number (Long)	Number (Double)	Gets the unit value of a list item of type <code>double</code> .
PutBoolean (Value)	Boolean		Sets the value to either true or false.
PutClass (Value)	Number (Long)		Sets the class or data type.
PutDouble (Value)	Number (Double)		Sets the value type as a double.
PutEnumerated (EnumType, Value)	Number (Long) Number (Long)		Sets the value type as an enumerated, or constant, value.
PutInteger (Value)	Number (Long)		Sets the value of a list item of type integer.
PutList (Value)	ActionList		Sets the value of a list item of type list or array.
PutObject (ClassID, Value)	Number (Long) ActionDescriptor		Sets the value of a list item of type object.
PutPath (Value)	String		Sets the value of a list item of type path. The <code>Value</code> parameter takes a <code>String</code> that represents a file path.

Method	Parameter Type	Returns	What it does (Continued)
PutReference (Value)	ActionReference		Sets the value of a list item whose type a reference to an object created in the script.
PutString (Value)	String		Sets the value of a list item of type String.
PutUnitDouble (UnitID, Value)	Number (Long) Number (Double)		Sets the value of a list item of type unit value represented as a double.

ActionReference

A reference object that contains the data describing the object you are referring to.

Note: The `actionReference` object is part of the Action Manager functionality. See the *Photoshop CS5 Scripting Guide*.

Properties

Property	Value type	What it does
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>typename</code>	String	Read-only. The class name of the referenced Action object.

Methods

Method	Parameter Type	Returns	What it does
<code>GetContainer</code> ()		ActionReference	Gets a reference contained in this reference. Container references provide additional pieces to the reference. This looks like another reference, but it is actually part of the same reference.
<code>GetDesiredClass</code> ()		Number (Long)	Gets a number representing the class of the object.
<code>GetEnumeratedType</code> ()		Number (Long)	Gets the enumeration type.
<code>GetEnumeratedValue</code> ()		Number (Long)	Gets the enumeration value.
<code>GetForm</code> ()		PsReferenceFormType	Gets the form of an ActionReference .
<code>GetIdentifier</code> ()		Number (Long)	Gets the identifier value for a reference whose form is identifier.
<code>GetIndex</code> ()		Number (Long)	Gets the index value for a reference in a list or array.
<code>GetName</code> ()		String	Gets the name of a reference.
<code>GetOffset</code> ()		Number (Long)	Gets the offset of the object's index value.

Method	Parameter Type	Returns	What it does (Continued)
GetProperty ()		Number (Long)	Gets the property ID value.
PutClass (DesiredClass)	Number (Long)		Puts a new class form and class type into the reference.
PutEnumerated (DesiredClass, EnumType, Value)	Number (Long) Number (Long) Number (Long)		Puts an enumeration type and ID into a reference along with the desired class for the reference.
PutIdentifier (DesiredClass, Value)	Number (Long) Number (Long)		Puts a new identifier and value into the reference..
PutIndex (DesiredClass, Value)	Number (Long) Number (Long)		Puts a new index and value into the reference.
PutName (DesiredClass, Value)	Number (Long) String		Puts a new name and value into the reference.
PutOffset (DesiredClass, Value)	Number (Long) Number (Long)		Puts a new offset and value into the reference.
PutProperty (DesiredClass, Value)	Number (Long) Number (Long)		Puts a new property and value into the reference.

Application

The Adobe Adobe Photoshop CS5 application object. The `Application` object contains all other Adobe Photoshop CS5 objects.

Properties

Property	Value Type	What it is
<code>ActiveDocument</code>	Document	Read-write. The foremost document. (Setting this property is equivalent to clicking an open document in the Adobe Photoshop CS5 application to bring it to the front of the screen.)
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>BackgroundColor</code>	SolidColor	Read-write. The color mode for the document's background color.
<code>Build</code>	string	Read-only. The build number of the application.
<code>ColorSettings</code>	String	Read-write. The name of selected color setting's set.
<code>DisplayDialogs</code>	PsDialogModes	Read-write. The dialog mode for the document, which indicates whether or not Adobe Photoshop CS5 displays dialogs when the script runs.
<code>Documents</code>	Documents	Read-only. The collection of open documents.
<code>Fonts</code>	TextFonts	Read-only. The fonts installed on this system.
<code>ForegroundColor</code>	SolidColor	Read-write. The default foreground color (used to paint, fill, and stroke selections).
<code>FreeMemory</code>	Number (Double)	Read-only. The amount of unused memory available to Adobe Photoshop CS5.
<code>Locale</code>	String	Read-only. The language location of the application.
<code>MacintoshFileTypes</code>	Array of String	Read-only. A list of file image types Adobe Photoshop CS5 can open.
<code>MeasurementLog</code>	MeasurementLog	Read-only. The log of measurements taken.
<code>Name</code>	String	Read-only. The application's name.
<code>Notifiers</code>	Notifiers	Read-only. The collection of notifiers currently configured (in the Scripts Events Manager menu in the Adobe Photoshop CS5 application).
<code>NotifiersEnabled</code>	Boolean	Read-write. Indicates whether all notifiers are enabled or disabled.
<code>Path</code>	String	Read-only. The full path (as a <code>String</code>) to the location of the Adobe Photoshop CS5 application.

Property	Value Type	What it is (Continued)
Preferences	Preferences	Read-only. The application preference settings (equivalent to selecting Edit > Preferences in the Adobe Photoshop CS5 application in Windows® or Photoshop > Preferences in Mac OS®).
PreferencesFolder	String	Read-only. The full path to the Preferences folder.
RecentFiles	Array of String	Read-only. Files (as an Array of String) in the Recent Files list.
ScriptingBuildDate	String	Read-only. The build date of the Scripting interface.
ScriptingVersion	String	Read-only. The version of the Scripting interface.
SystemInformation	string	Read-only. The system information for the applicaiton and the system.
typename	String	Read-only. The class name of the referenced Application object.
Version	String	Read-only. The version of Adobe Photoshop application you are running.
Visible	Boolean	Read-write. Indicates whether the Adobe Photoshop CS5 application is the front-most/active application.
WinColorSettings	String	Read-only. Color settings.
WindowsFileTypes	Array of String	Read-only. A list of file image extensions Adobe Photoshop CS5 can open.

Methods

Method	Parameter Type	Returns	What it does
Batch (InputFiles, Action, From [, Options])	Array of String String String BatchOptions	String	Runs the batch automation routine (similar to the Batch command, or File > Automate > Batch in the Adobe Photoshop CS5 application). Note: The <code>inputFiles</code> parameter specifies the source for the files (as an array of <code>String</code>) to be manipulated by the Batch command.
ChangeColorSettings ([Name] [, File])	String String	None	Sets Color Settings to a named set or to the contents of a settings file. The <code>File</code> parameter represents the path to the file as a <code>String</code> .
CharIDToTypeID (CharID)	String	Number (Long)	Converts from a four character code (character ID) to a runtime ID.
DoAction (Action, From)	String String	none	Plays an action from the Actions palette.
DoJavaScript (JavaScriptCode, [, Arguments] [, ExecutionMode])	String Array PsJavaScriptExecutionMode	String	Executes the specified JavaScript code.
DoJavaScriptFile (JavaScriptFile, [, Arguments] [, ExecutionMode])	String Array PsJavaScriptExecutionMode	String	Executes the specified JavaScript code, from the file specified by argument <code>JavaScriptFile</code> .
ExecuteAction (EventID [, Descriptor] [, DisplayDialogs])	Number (Long) ActionDescriptor PsDialogModes	ActionDescriptor	Plays an ActionManager event.

Method	Parameter Type	Returns	What it does
ExecuteActionGet (Reference)	ActionReference	ActionDescriptor	Obtains an ActionDescriptor.
FeatureEnabled (Name)	String	Boolean	Determines whether the feature specified by Name is enabled. The following features are supported as values for Name: "photoshop/extended" "photoshop/standard" "photoshop/trial"
Load (Document)	String		Loads a support document from the specified file path location.
MakeContactSheet (InputFiles [, Options])	Array of String ContactSheetOptions	String	Deprecated for Adobe Photoshop CS5. Creates a contact sheet from the specified files.
MakePDFPresentation (InputFiles OutputFiles [, Options])	Array of String String PresentationOptions	String	Deprecated for Adobe Photoshop CS5. Creates a PDF presentation file from the specified input files. Note: The return string contains the path to the PDF file.
MakePhotoGallery (InputFolder OutputFolder [, Options])	String String GalleryOptions	String	Deprecated for Adobe Photoshop CS5. Creates a Web photo gallery from the files in the specified input folder.
MakePhotomerge (InputFiles)	Array of String	String	Deprecated for Adobe Photoshop CS5. Merges multiple files into one; user interaction required.

Method	Parameter Type	Returns	What it does
MakePicturePackage (InputFiles [, Options])	Array of String PicturePackageOptions	String	Deprecated for Adobe Photoshop CS5. Creates a picture package from the specified input files.
Open (Document [, As] [, AsSmartObject])	String object (open options) Boolean Note: See open options for individual file types, such as CameraRAWOpenOptions or EPSOpenOptions , etc.	Document	Opens the specified document as the optionally specified file type. Optional parameter <code>AsSmartObject</code> (default: false) indicates whether to create a smart object around the opened document.
OpenDialog ()		Array of String	Uses the Photoshop open dialog box to select files. Returns an <code>Array of String</code> representing the files selected.
Purge (Target)	PsPurgeTarget		Purges one or more caches.
Quit ()			Quits the Photoshop application.
Refresh ()			Pauses the script while the application refreshes.
StringIDToTypeID (StringID)	String	Number (Long)	Converts from a String ID to a runtime ID.
TypeIDToCharID (TypeID)	Number (Long)	String	Converts from a runtime ID to a character ID.
TypeIDToStringID (TypeID)	Number (Long)	String	Converts from a runtime ID to a String ID.

First Sample Script

The following script displays a message box that contains the application version number, the path to the application, the amount of memory available, and the number of documents open.

When the user clicks OK, a second dialog asks whether they would like the foreground and background colors set.

A third dialog offers to open a sample file. If the user clicks OK, the script opens the file Fish.psd from the samples folder in the application directory.

Application.vbs

```
' Create a Welcome message
' Use the name and version properties of the application object to append the
' application's name and version to the Welcome message use vbCrLf to insert a
' carriage return

Dim appRef, message, documentsOpen, answer, sampleDocToOpen

Set appRef = CreateObject("Photoshop.Application")

message = "Welcome to " & appRef.Name
message = message & " version " & appRef.Version & vbCrLf & vbCrLf

' find out where Photoshop CS5 is installed and add the path to the message add
' the optional parameter fsName to the path property to display the file system
' name in the most common format
message = message & "I'm installed in " & appRef.Path & vbCrLf & vbCrLf

'see how much memory Photoshop CS5 has to play with
message = message & "You have this much memory available for Photoshop CS5: "
message = message & appRef.FreeMemory & vbCrLf & vbCrLf

' use the Count property of the Documents object to see how many are open
documentsOpen = appRef.Documents.Count
message = message & "You currently have " & documentsOpen & " documents open." & _
    vbCrLf & vbCrLf

'display the message to the user
MsgBox (message)

answer = MsgBox _
    ("Do you want me to set the foreground and background to my favorite colors?", _
    vbYesNo, "Change Colors?")
' set the colors
If answer = vbYes Then
    Randomize ' Initialize random-number generator.
    ' I don't have a favorite color. Why did I ask you may wonder?
    appRef.ForegroundColor.RGB.Red = Rnd() * 255
    appRef.ForegroundColor.RGB.Green = Rnd() * 255
    appRef.ForegroundColor.RGB.Blue = Rnd() * 255
    appRef.BackgroundColor.RGB.Red = Rnd() * 255
    appRef.BackgroundColor.RGB.Green = Rnd() * 255
    appRef.BackgroundColor.RGB.Blue = Rnd() * 255
End If

' Open a document
If documentsOpen = 0 Then
    ' use the application's path and the offset to the samples folder
    sampleDocToOpen = appRef.Path & "Samples\Fish.psd"
    ' compose a message with the name of the file
    message = "Would you like me to open a sample for you? ("
    message = message & sampleDocToOpen & ")"
    ' ask the user another question
```

```
answer = MsgBox (message, vbYesNo, "Open Something?")  
' open the document accordingly  
If answer = vbYes Then  
    appRef.Open sampleDocToOpen  
End If  
End If
```

Second Sample Script

The following script presents a progression of images as a PDF slide show.

PDFPresentation.vbs

```
' use all the files in the Samples folder
Dim appRef, inputFiles(), i, outputFile, options, objWshShell

Set appRef = CreateObject("Photoshop.Application")

' get all the files found in this folder
Set fsoRef = CreateObject("Scripting.FileSystemObject")
Set folderRef = fsoRef.GetFolder(appRef.Path & "Samples\")

ReDim inputFiles(folderRef.Files.Count-1)

i = 0
For Each f in folderRef.Files
    inputFiles(i) = f.Path
    i = i + 1
Next

' Get a shell object so we can point to the desktop
Set shellRef = WScript.CreateObject("Wscript.Shell")
outputFile = shellRef.SpecialFolders("Desktop") & "\VBSPresentation.pdf"

' there are defaults but I like to set the options myself
Set options = CreateObject("Photoshop.PresentationOptions")
options.Presentation = true
options.PDFFileOptions.Encoding = 2 'for PsPDFEncoding --> 2 (psPDFJPEG)
options.AutoAdvance = true
options.Interval = 5
options.Loop = false
options.Transition = 10 'for PsTransitionType --> 10 (psRandom)

' create the presentation
appRef.MakePDFPresentation inputFiles, outputFile, options

Set objWshShell = WScript.CreateObject("Wscript.Shell")
WScript.Echo "Presentation file saved in: " & _
    shellRef.SpecialFolders("Desktop") & "\VBSPresentation.pdf"
```

ArtLayer

An object within a document that contains the visual elements of the image (equivalent to a layer in the Adobe Photoshop CS5 application).

Properties

Property	Value Type	What it is
AllLocked	Boolean	Read-write. Indicates whether to completely lock the layer's contents and settings.
Application	Object (Application)	Read-only. The application that this art layer belongs to.
BlendMode	PsBlendMode	Read-write. The layer's blending mode.
Bounds	Array	Read-only. An array of coordinates that describes the bounding rectangle of the ArtLayer.
FillOpacity	Number (Double)	Read-write. The interior opacity of the layer (0.0 - 100.0).
Grouped	Boolean	Read-write. Indicates whether to group this layer with the layer beneath it.
IsBackgroundLayer	Boolean	Read-write. Indicates whether the layer is a background layer or normal layer. Note: A document can have only one background layer.
Kind	PsLayerKind	Read-write. Sets the layer's kind (such as 'text layer') for an empty layer. Note: Valid only when the layer is empty and when <code>IsBackgroundLayer</code> is false. See IsBackgroundLayer . Note: You can use the <code>kind</code> property to make a background layer a normal layer; however, to make a layer a background layer, you must set <code>IsBackgroundLayer</code> to true.
LinkedLayers	Array of ArtLayer and/or LayerSet	Read-only. The layers linked to this layer. Note: See Link .
Name	String	Read-write. The layer's name.
Opacity	Number (Double)	Read-write. The master opacity of the layer (0.0 - 100.0).
Parent	Object (Document)	Read-only. The object's container.

Property	Value Type	What it is (Continued)
PixelsLocked	Boolean	Read-write. Indicates whether the pixels in the layer's image can be edited using the paintbrush tool.
PositionLocked	Boolean	Read-write. Indicates whether the pixels in the layer's image can be moved within the layer.
TextItem	TextItem	Read-only. The text item that is associated with the layer. Note: Valid only when <code>Kind = 2</code> . See Kind .
TransparentPixelsLocked	Boolean	Read-write. Indicates whether editing is confined to the opaque portions of the layer.
typename	String	Read-only. The class name of the referenced <code>ArtLayer</code> object.
Visible	Boolean	Read-write. Indicates whether the layer is visible.
XMPMetadata	Object (XMPMetadata)	Read-only. XMP data for the layer.

Methods

Method	Parameter Type	Returns	What it does
AdjustBrightnessContrast (Brightness, Contrast)	Number (Long) Number (Long)		Adjusts the brightness (-100 - 100) and contrast (-100 - 100).
AdjustColorBalance ([Shadows] [, Midtones] [, Highlights] [, PreserveLuminosity])	Array of Number Array of Number Array of Number Boolean		Adjusts the color balance of the layer's component channels. For <code>Shadows</code> , <code>Midtones</code> , and <code>Highlights</code> , the array must include three values (-100 - 100), which represent cyan or red, magenta or green, and yellow or blue, when the document mode is CMYK or RGB. Note: See <code>mode</code> in the Properties table of the Document object.
AdjustCurves (CurveShape)	Array of points (Array (Array(x, y)))		Adjusts the tonal range of the selected channel using up to fourteen points.

Method	Parameter Type	Returns	What it does (Continued)
AdjustLevels (InputRangeStart, InputRangeEnd, InputRangeGamma, OutputRangeStart, OutputRangeEnd)	Number (Long) Number (Long) Number (Double) Number (Long) Number (Long)		Adjusts the levels of the selected channels (InputRangeStart: 0 - 253; InputRangeEnd: (InputRangeStart + 2) - 255; InputRangeGamma: 0.10 - 9.99; OutputRangeStart: 0 - 253; OutputRangeEnd: (OutputRangeStart + 2) - 255).
ApplyAddNoise (Amount, Distribution, Monochromatic)	Number (Double) PsNoiseDistribution Boolean		Applies the Add Noise filter (Amount: 0.1 - 400, as a percentage).
ApplyAverage ()			Applies the Average filter.
ApplyBlur ()			Applies the Blur filter.
ApplyBlurMore ()			Applies the Blur More filter.
ApplyClouds ()			Applies the Clouds filter.
ApplyCustomFilter (Characteristics, Scale, Offset)	Array of twenty-five Numbers (Long) Number (Long) Number (Long)		Applies a custom filter. Note: Required parameter values define the filter. Refer to Adobe Photoshop CS5 Help for specific instructions.
ApplyDeInterlace (EliminateFields, CreateFields)	PsEliminateFields PsCreateFields		Applies the De-Interlace filter.
ApplyDespeckle ()			Applies the Despeckle filter.
ApplyDifferenceClouds ()			Applies the Difference Clouds filter.
ApplyDiffuseGlow (Graininess, GlowAmount, ClearAmount)	Number (Long) Number (Long) Number (Long)		Applies the Diffuse Glow filter (Graininess: 0 - 10; GlowAmount: 0 - 20; ClearAmount: 0 - 20).
ApplyDisplace (HorizontalScale, VerticalScale, DisplacementType, UndefinedAreas, DisplacementMapFiles)	Number (Long) Number (Long) PsDisplacementMapType PsUndefinedAreas String		Applies the Displace filter using the specified horizontal and vertical scale (-999 - 999), mapping type, treatment of undistorted areas, and path to the distortion image map.

Method	Parameter Type	Returns	What it does (Continued)
ApplyDustAndScratches (Radius, Threshold)	Number (Long) Number (Long)		Applies the Dust & Scratches filter (Radius: 1 - 100; Threshold: 0 - 255).
ApplyGaussianBlur (Radius)	Number (Double)		Applies the Gaussian Blur filter within the specified radius (in pixels) (0.1 - 250.0).
ApplyGlassEffect (Distortion, Smoothness, Scaling [, Invert] [, Texture] [, TextureFile])	Number (Long) Number (Long) Number (Long) Boolean PsTextureType String		Applies the Glass filter (Distortion: 0 - 20; Smoothness: 1 - 15; Scaling (in percent): 50 - 200). Note: The TextureFile parameter represents the path to a texture file as a String.
ApplyHighPass (Radius)	Number (Double)		Applies the High Pass filter within the specified radius (in pixels) (0.1 - 250.0).

Method	Parameter Type	Returns	What it does (Continued)
<p>ApplyLensBlur ([Source] [, FocalDistance] [, InvertDepthMap] [, Shape] [, Radius] [, BladeCurvature] [, Rotation] [, Brightness] [, Threshold] [, Amount] [, Distribution] [, Monochromatic])</p>	<p>PsDepthMapSource Number (Long) Boolean PsGeometry Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) PsNoiseDistribution Boolean</p>		<p>Applies the Lens Blur filter.</p> <p>source: the source for the depth map. Default: 1 (psNoSource).</p> <p>focalDistance: the blur focal distance for the depth map (default: 0).</p> <p>invertDepthMask: whether the depth map is inverted (default: false).</p> <p>shape: The shape of the iris. Default: 2 (psHexagon).</p> <p>radius: The radius of the iris (default: 15).</p> <p>bladeCurvature: The blade curvature of the iris (default: 0).</p> <p>rotation: The rotation of the iris (default: 0)</p> <p>brightness: The brightness for the specular highlights (default: 0).</p> <p>threshold: The threshold for the specular highlights (default: 0).</p> <p>amount: The amount of noise (default: 0)</p> <p>distribution: The distribution value for the noise. Default: 1 (psUniformNoise).</p> <p>monochromatic: Indicates whether the noise is monochromatic (default: false).</p>
<p>ApplyLensFlare (Brightness, FlareCenter, LensType)</p>	<p>Number (Long) Array (Double) PsLensType</p>		<p>Applies the Lens Flare filter with the specified brightness (0 - 300, as a percentage), the x and y coordinates (unit value) of the flare center, and the lens type.</p>
<p>ApplyMaximum (Radius)</p>	<p>Number (Double)</p>		<p>Applies the Maximum filter within the specified radius (in pixels) (1 - 100).</p>
<p>ApplyMedianNoise (Radius)</p>	<p>Number (Double)</p>		<p>Applies the Median Noise filter within the specified radius (in pixels) (1 - 100).</p>

Method	Parameter Type	Returns	What it does (Continued)
ApplyMinimum (Radius)	Number (Double)		Applies the Minimum filter within the specified radius (in pixels) (1 - 100).
ApplyMotionBlur (Angle, Radius)	Number (Long) Number (Double)		Applies the Motion Blur filter (Angle: -360 - 360; Radius: 1 - 999).
ApplyNTSC ()			Applies the NTSC colors filter.
ApplyOceanRipple (Size, Magnitude)	Number (Long) Number (Long)		Applies the Ocean Ripple filter in the specified size (1 - 15) and magnitude (0 - 20).
ApplyOffset (Horizontal, Vertical, UndefinedAreas)	Number (Double) Number (Double) PsOffsetUndefinedAreas		Moves the layer the specified amount horizontally and vertically (min/max amounts depend on layer size), leaving an undefined area at the layer's original location.
ApplyPinch (Amount)	Number (Long)		Applies the Pinch filter in the specified amount (as a percentage) (-100 - 100).
ApplyPolarCoordinates (Conversion)	PsPolarConversionType		Applies the Polar Coordinates filter.
ApplyRadialBlur (Amount, BlurMethod, BlurQuality)	Number (Long) PsRadialBlurMethod PsRadialBlurQuality		Applies the Radial Blur filter in the specified amount (1 - 100) using either a spin or zoom effect and the specified quality.
ApplyRipple (Amount, Size)	Number (Long) PsRippleSize		Applies the Ripple filter in the specified amount (-999 to 999) throughout the image and in the specified size.
ApplySharpen ()			Applies the Sharpen filter.
ApplySharpenEdges ()			Applies the Sharpen Edges filter.
ApplySharpenMore ()			Applies the Sharpen More filter.
ApplyShear (Curve, UndefinedAreas)	Array of points (Array (Array(x, y))) PsUndefinedAreas		Applies the Shear filter (curve: 2 - 255 points). Note: You must define at least two points in the Curve parameter.

Method	Parameter Type	Returns	What it does (Continued)
ApplySmartBlur (Radius, Threshold, BlurQuality, Mode)	Number (Double) Number (Double) PsSmartBlurQuality PsSmartBlurMode		Applies the smart blur filter (Radius: 0.1 - 100.0; Threshold: 0.1 - 100.0).
ApplySpherize (Amount, Mode)	Number (Long) PsSpherizeMode		Applies the Spherize filter in the specified amount (as percentage) (-100 - 100).
ApplyStyle (StyleName)	String		Applies the specified style to the layer. Note: You must use a style from the Styles list in the Layer Style dialog.
ApplyTextureFill (TextureFile)	String		Applies the Texture Fill filter.
ApplyTwirl (Angle)	Number (Long)		Applies the Twirl filter at the specified angle (-999 - 999).
ApplyUnSharpMask (Amount, Radius, Threshold)	Number (Double) Number (Double) Number (Long)		Applies the Unsharp Mask filter (Amount: 1 - 500 as percent; Radius: 0.1 - 250.00; Threshold: 0 - 255).
ApplyWave (GeneratorNumber, MinimumWavelength, MaximumWavelength, MinimumAmplitude, MaximumAmplitude, HorizontalScale, VerticalScale, WaveType, UndefinedAreas, RandomSeed)	Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) PsWaveType PsUndefinedAreas Number (Long)		Applies the Wave filter (GeneratorNumber: 1 - 999 ; MinimumWavelength: 1 - 998 ; MaximumWavelength: 2 - MinimumWavelength + 1 ; MinimumAmplitude: 1 - 998 ; MaximumAmplitude: 2 - MinimumAmplitude + 1 ; AmountScale: 1 - 100 , as a percentage; VerticalScale: 1 - 100 , as a percentage).
ApplyZigZag (Amount, Ridges, Style)	Number (Long) Number (Long) PsZigZagType		Applies the Zigzag filter (Amount: -100 - 100; Ridges: 0 - 20).
AutoContrast ()			Adjusts the contrast of the selected channels automatically.
AutoLevels ()			Adjusts the levels of the selected channels using the auto levels option.
Clear ()			Cuts the layer without moving it to the clipboard.

Method	Parameter Type	Returns	What it does (Continued)
Copy ([Merge])	Boolean		Copies the layer to the clipboard. When the optional argument is set to <code>true</code> , a merged copy is performed (that is, all visible layers are copied to the clipboard).
Cut ()			Cuts the layer to the clipboard.
Desaturate ()			Converts a color image to a grayscale image in the current color mode by assigning equal values of each component color to each pixel.
Duplicate ([RelativeObject] [, InsertionLocation])	Object (ArtLayer or LayerSet) PsElementPlacement	ArtLayer	Creates a duplicate of the object on the screen.
Equalize ()			Redistributes the brightness values of pixels in an image to more evenly represent the entire range of brightness levels within the image.
Invert ()			Inverts the colors in the layer by converting the brightness value of each pixel in the channels to the inverse value on the 256-step color-values scale.
Link (With)	Object (ArtLayer or LayerSet)		Links the layer with the specified layer.
Merge ()		ArtLayer	Merges the layer down, removing the layer from the document; returns a reference to the art layer that this layer is merged into.

Method	Parameter Type	Returns	What it does (Continued)
MixChannels (OutputChannels [, Monochrome])	Array of Array of Number (Double) Boolean		Modifies a targeted (output) color channel using a mix of the existing color channels in the image. (OutputChannels = An array of channel specifications. For each component channel, specify a list of adjustment values (-200 - 200) followed by a 'constant' value (-200 - 200).) Note: When Monochrome = true, the maximum number of channel value specifications is 1. Note: Valid only when Document.Mode = 2 or Document.Mode = 3. Note: RGB arrays must include four doubles. CMYK arrays must include five doubles.
Move (ApplicationObject, InsertionLocation)	Object (ArtLayer or LayerSet) PsElementPlacement		Moves the layer relative to the object specified in parameters. Note: For art layers, only the constant values 3 and 4 are valid. For layer sets, only the constant values 3 and 0 are valid.
PhotoFilter ([FillColor] [, Density] [, PreserveLuminosity])	SolidColor Number (Long) Boolean		Adjust the layer's color balance and temperature as if a color filter had been applied (Density: 1 - 100, as a percentage).
Posterize (Levels)	Number (Long)		Specifies the number of tonal levels (2 - 255) for each channel and then maps pixels to the closest matching level.
Rasterize (Target)	PsRasterizeType		Converts the targeted contents in the layer into a flat, raster image.
Resize ([Horizontal] [, Vertical] [, Anchor])	Number (Double) Number (Double) PsAnchorPosition		Resizes the layer to the specified dimensions (as a percentage of its current size) and places it in the specified position.

Method	Parameter Type	Returns	What it does (Continued)
Rotate (Angle [, Anchor])	Number (Double) PsAnchorPosition		Rotates the layer around the specified anchor point.
SelectiveColor (SelectionMethod [, Reds] [, Yellows] [, Greens] [, Cyans] [, Blues] [, Magentas] [, Whites] [, Neutrals] [, Blacks])	PsAdjustmentReference Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long) Array of Number (Long)		Modifies the amount of a process color in a specified primary color without affecting the other primary colors. Note: Each color array must have four components.
ShadowHighlight ([ShadowAmount] [, ShadowWidth] [, ShadowRadius] [, HighlightAmount] [, HighlightWidth] [, HighlightRadius] [, ColorCorrection] [, MidtoneContrast] [, BlackClip] [, WhiteClip])	Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Long) Number (Double) Number (Double)		Adjusts the range of tones in the image's Shadows and highlights (ShadowAmount: 0 - 100 as percent; ShadowWidth: 0 - 100 as percent; ShadowRadius: 0 - 2500 in pixels; HighlightAmount: 0 - 100 as percent; HighlightWidth: 0 - 100 as percent; HighlightRadius: 0 - 2500 in pixels; ColorCorrection: -100 - 100; MidtoneContrast: -100 - 100; BlackClip: 0.000 - 50.000; WhiteClip: 0.000 - 50.000).
Threshold (Level)	Number (Long)		Converts grayscale or color images to high-contrast, B/W images by converting pixels lighter than the specified threshold to white and pixels darker than the threshold to black (level: 1 - 255).
Translate ([DeltaX] [, DeltaY])	Number (Double) Number (Double)		Moves the layer the specified amount (in pixels) relative to its current position.
Unlink ()			Unlinks the layer.

Sample Script

The following script closes any open documents (files), then opens each file in the Samples folder, creating an art layer for each image and using the image's file name as the layer name.

ArtLayer.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, mergedDoc
Dim fsoRef, folderRef, topLeftH, topLeftV, docH, docV, docName, selRegion
```

```
Dim x, y, layer1, layer2

Set appRef = CreateObject("Photoshop.Application")

' Save the current preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS5 to use pixels and display no dialogs
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' Close all the open documents
Do While appRef.Documents.Count
    appRef.ActiveDocument.Close()
Loop

' Create a new document to merge all the samples into
Set mergedDoc = appRef.Documents.Add(1000, 1000, 72, "Merged Samples", 2, 3, 1)
'enumerated values 2 = PsNewDocumentMode --> 2 (PsNewRGB) and
'3 = PsDocumentFill --> 3 (psTransparent)

' get all the files found in this folder
Set fsoRef = CreateObject("Scripting.FileSystemObject")
Set folderRef = fsoRef.GetFolder(appRef.Path & "Samples\" )

Randomize

' open each file
For Each f in folderRef.Files
    appRef.Open f.Path

    ' use the document name for the layer name in the merged document
    docName = appRef.ActiveDocument.Name

    ' flatten the document so we get everything and then copy
    appRef.ActiveDocument.flatten()
    appRef.ActiveDocument.Selection.SelectAll()
    appRef.ActiveDocument.Selection.Copy()

    ' don't save anything we did
    appRef.ActiveDocument.Close(2)
    'the enumerated value Close(2) = PsSaveOptions >2 (psDoNotSaveChanges)

    ' make a random selection on the document to paste into
    ' by dividing the document up in 4 quadrants and pasting
    ' into one of them by selecting that area
    topLeftH = Int(Rnd() * 2)
    topLeftV = Int(Rnd() * 2)
    ' MsgBox topLeftH & ":" & topLeftV
    docH = appRef.ActiveDocument.Width / 2
    docV = appRef.ActiveDocument.Height / 2
    selRegion = Array( Array( topLeftH * docH, topLeftV * docV), _
        Array( topLeftH * docH + docH, topLeftV * docV), _
        Array( topLeftH * docH + docH, topLeftV * docV + docV), _
        Array( topLeftH * docH, topLeftV * docV + docV), _
        Array( topLeftH * docH, topLeftV * docV) )
    appRef.ActiveDocument.Selection.Select(selRegion)
```

```
appRef.ActiveDocument.Paste()

' change the layer name and opacity
appRef.ActiveDocument.ActiveLayer.Name = docName
appRef.ActiveDocument.ActiveLayer.FillOpacity = 50
Next

' sort the layers by name
x = 0
y = 0
for x = 1 To appRef.ActiveDocument.Layers.Count
    for y = 1 To appRef.ActiveDocument.Layers.Count - 1
        Set layer1 = appRef.ActiveDocument.Layers(y)
        Set layer2 = appRef.ActiveDocument.Layers(y + 1)
        If layer1.Name > layer2.Name Then
            layer1.move layer2, 4
        End If
    Next
Next

' Reset the application preferences
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
appRef.DisplayDialogs = startDisplayDialogs
```

ArtLayers

The collection of `ArtLayer` objects in the document.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>ArtLayers</code> collection.
Parent	Object (Document)	Read-only. The object's container.
typename	String	Read-only. The class name of the referenced <code>ArtLayers</code> object.

Methods

Method	Parameter Type	Returns	What it does
Add ()		ArtLayer	Creates a new <code>ArtLayer</code> in the document.
Index (ItemPtr)	Object (ArtLayer)	Number (long)	Gets the index of the <code>ArtLayer</code> into the collection.
Item (ItemKey)	Number (Long)	ArtLayer	Gets an element from the <code>ArtLayers</code> collection.
RemoveAll ()		Nothing	Removes all elements from the <code>ArtLayers</code> collection.

BatchOptions

Options to specify when running a Batch command.

Properties

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Destination	PsBatchDestinationType	Read-write. The type of destination for the processed files. Default: 1 (psNoDestination).
DestinationFolder	String	Read-write. The folder location for the processed files. Note: Valid only when <code>Destination = 3</code> (psFolder). See Destination .
ErrorFile	String	Read-write. The file in which to log errors encountered. Note: To display errors on the screen (and stop batch processing when errors occur) leave blank.
FileNaming	Array of (PsFileNamingType options)	Read-write. A list of file naming options (maximum: 6). Note: Valid only when <code>Destination = 3</code> (psFolder). See Destination .
MacintoshCompatible	Boolean	Read-write. Indicates whether to make the final file names Macintosh compatible. Default: true. Note: Valid only when <code>Destination = 3</code> (psFolder). See Destination .
OverrideOpen	Boolean	Read-write. Indicates whether to override action open commands. Default: false.
OverrideSave	Boolean	Read-write. Indicates whether to override save as action steps with the specified destination. Default: false. Note: Valid only when <code>Destination = 3</code> (psFolder). Or <code>Destination = 2</code> (psSaveAndClose). See Destination .
StartingSerial	Number (Long)	Read-write. The starting serial number to use in naming files. Default: 1. Note: Valid only when <code>Destination = 3</code> (psFolder). See Destination .

Property	Value type	What it is (Continued)
SuppressOpen	Boolean	Read-write. Indicates whether to suppress the file open options dialogs. Default: <code>false</code> .
SuppressProfile	Boolean	Read-write. Indicates whether to suppress the color profile warnings. Default: <code>false</code> .
typename	String	Read-only. The class name of the referenced <code>BatchOptions</code> object.
UnixCompatible	Boolean	Read-write. Indicates whether to make the final file name Unix [®] compatible. Default: <code>true</code> . Note: Valid only when <code>Destination = 3</code> (<code>psFolder</code>). See Destination .
WindowsCompatible	Boolean	Read-write. Indicates whether to make the final file names Windows compatible. Default: <code>true</code> . Note: Valid only when <code>Destination = 3</code> (<code>psFolder</code>). See Destination .

BitmapConversionOptions

Options to specify when converting an image to Bitmap mode.

Note: Convert color images to grayscale before converting the image to bitmap mode. See [‘Desaturate’ on page 31](#) (in the Properties table of the `ArtLayer` object).

Properties

Property	Value Type	What it is
Angle	Number (Double)	Read-write. The angle (in degrees) at which to orient individual dots (-180 - 180). See Shape . Note: Valid only when <code>Method</code> = 4. See Method .
Application	Object (Application)	Read-only. The application that the object belongs to.
Frequency	Number (Double)	Read-write. The number of printer dots (per inch) to use (1.0 - 999.99). Note: Valid only when <code>Method</code> = 4. See Method .
Method	PsBitmapConversionType	Read-write. The conversion method to use. Default: 3.
PatternName	String	Read-write. The name of the pattern to use. Note: Valid only when <code>Method</code> = 5. See Method .
Resolution	Number (Double)	Read-write. The output resolution in pixels per inch. Default: 72.0.
Shape	PsBitmapHalfToneType	Read-write. The dot shape to use. Note: Valid only when <code>Method</code> = 1. See Method .
typename	String	Read-only. The class name of the referenced <code>BitmapConversionOptions</code> object.

BMPSaveOptions

Options that can be specified when saving a document in BMP format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Application	Object (Application)	Read-only. The application that the object belongs to.
Depth	PsBMPDepthType	Read-write. The number of bits per channel.
FlipRowOrder	Boolean	Read-write. Indicates whether to write the image from top to bottom. Default: <code>false</code> . Note: Available only when <code>OSType = 2</code> . See OSType .
OSType	PsOperatingSystem	Read-write. The target OS. Default: 2.
RLECompression	Boolean	Read-write. Indicates whether to use RLE compression. Note: Available only when <code>OSType = 2</code> . See OSType .
typename	String	Read-only. The class name of the referenced <code>BMPSaveOptions</code> object.

CameraRAWOpenOptions

Options that can be specified when opening a document in Camera Raw format.

Properties

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
BitsPerChannel	PsBitsPerChannelType	Read-write. The number of bits per channel.
BlueHue	Number (Long)	Read-write. The blue hue of the shot (-100 - 100).
BlueSaturation	Number (Long)	Read-write. The blue saturation of the shot (-100 - 100).
Brightness	Number (Long)	Read-write. The brightness of the shot (0 - 150).
ChromaticAberrationBY	Number (Long)	Read-write. The chromatic aberration B/Y of the shot (-100 - 100).
ChromaticAberrationRC	Number (Long)	Read-write. The chromatic aberration R/C of the shot (-100 - 100).
ColorNoiseReduction	Number (Long)	Read-write. The color noise reduction of the shot (0 - 100).
ColorSpace	PsColorSpaceType	Read-write. The colorspace for the image.
Contrast	Number (Long)	Read-write. The contrast of the shot (-50 - 100).
Exposure	Number (Double)	Read-write. The exposure of the shot (4.0 - 4.0).
GreenHue	Number (Long)	Read-write. The green hue of the shot (-100 - 100).
GreenSaturation	Number (Long)	Read-write. The green saturation of the shot (-100 - 100).
LuminanceSmoothing	Number (Long)	Read-write. The luminance smoothing of the shot (0 - 100).
RedHue	Number (Long)	Read-write. The red hue of the shot (-100 - 100).
RedSaturation	Number (Long)	Read-write. The red saturation of the shot (-100 - 100).
Resolution	Number (Double)	Read-write. The resolution of the document in pixels per inch (1 - 999).

Property	Value type	What it is (Continued)
Saturation	Number (Long)	Read-write. The saturation of the shot (-100 - 100).
Settings	PsCameraRAWSettingsType	Read-write. The global settings for all Camera RAW options. Default: 0 (psCameraDefault).
Shadows	Number (Long)	Read-write. The shadows of the shot (0 - 100).
ShadowTint	Number (Long)	Read-write. The shadow tint of the shot (-100 - 100).
Sharpness	Number (Long)	Read-write. The sharpness of the shot (0 - 100).
Size	PsCameraRAWSize	Read-write. The size of the new document.
Temperature	Number (Long)	Read-write. The temperature of the shot (2000 - 50000).
Tint	Number (Long)	Read-write. The tint of the shot (-150 - 150).
typename	String	Read-only. The class name of the referenced CameraRAWOpenOptions object.
VignettingAmount	Number (Long)	Read-write. The vignetting amount of the shot (-100 - 100).
VignettingMidpoint	Number (Long)	Read-write. The vignetting mid point of the shot (-100 - 100).
WhiteBalance	PsWhiteBalanceType	Read-write. The white balance options for the image.

Channel

Object that stores information about a color element in the image, analogous to a plate in the printing process that applies a single color. The document's color mode determines the number of default channels; for example, an RGB document has four default channels:

- A composite channel: RGB
- Three component channels: red, green, blue

A channel can also be an alpha channel, which stores selections as masks, or a spot channel, which stores spot colors.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Color	Object (SolidColor)	Read-write. The color of the channel. Note: Not valid when <code>Type = 1</code> .
Histogram	Array of 256 Numbers (Long)	Read-only. A histogram of the color of the channel. Note: Not valid when <code>Type = 1</code> . For component channel histogram values, use the <code>Histogram</code> property of the Document object instead. See Histogram .
Kind	PsChannelType	Read-write. The channel type.
Name	String	Read-write. The channel's name.
Opacity	Number (Double)	Read-write. The opacity to use for alpha channels or the solidity to use for spot channels (0 - 100). Note: Valid only when <code>Type = 2</code> or <code>Type = 3</code> .
Parent	Object (Document)	Read-only. The object's container.
typename	String	Read-only. The class name of the referenced <code>Channel</code> object.
Visible	Boolean	Read-write. Indicates whether the channel is visible.

Methods

Method	Parameter Type	Returns	What it does
Delete ()			Deletes the channel.
Duplicate ([TargetDocument])	Document	Channel	Duplicates the channel.
Merge ()			Merges a spot channel into the component channels.

Channels

The collection of `Channel` objects in the document. See [‘Channel’ on page 43](#).

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Count</code>	Number (Long)	Read-only. The number of elements in the <code>Channels</code> collection.
<code>Parent</code>	Object (Document)	Read-only. The object’s container.
<code>typename</code>	String	Read-only. The class name of the referenced <code>Channels</code> object.

Methods

Method	Parameter Type	Returns	What it does
<code>Add</code> ()		Channel	Creates a new <code>Channel</code> object.
<code>Index</code> (ItemPtr)	Object (Channel)	Number (Long)	Gets the index of the specified <code>Channel</code> object.
<code>Item</code> (ItemKey)	Number (Long)	Channel	Gets an element from the <code>Channels</code> collection.
<code>RemoveAll</code> ()			Removes all <code>Channel</code> objects from the <code>Channels</code> collection.

Sample Script

The following script checks for any open documents (files); if no documents are open, it opens `fish.psd` in the Samples folder.

The script then creates the histogram for each channel in the document and creates a log file named `Histogram.log` on your Desktop. The file maps out the histogram for each channel and includes the following information:

- Total pixel count
- Mean pixel count per row
- Standard deviation of pixels per row
- Median pixels per row
- Pixel count row by row, represented in rows of Xs, produces a strobe effect, as a progression of dialogs display.

Histogram.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, docRef
```

```
Dim totalCount, channelIndex, activeChannels, myChannels, secondaryIndex
Dim largestCount, histogramIndex, pixelsPerX, outputX, a, visibleChannelCount
Dim aChannelArray(), aChannelIndex, oFileSys, fileOut, hist, objWshShell

Set appRef = CreateObject("Photoshop.Application")

' Save the current preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS5 to use pixels and display no dialogs
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' if there are no documents open then try to open a sample file
If appRef.Documents.Count = 0 Then
    appRef.Open(appRef.Path + "/Samples/Fish.psd")
End If

Set docRef = appRef.ActiveDocument

' Get a shell object so we can point to the desktop
Set objWshShell = WScript.CreateObject("Wscript.Shell")

' create the output file
Set oFileSys = CreateObject("Scripting.FileSystemObject")
Set fileOut = oFileSys.CreateTextFile(objWshShell.SpecialFolders("Desktop") & _
    "\Histogram.log")

' write out a header
fileOut.Write "Histogram report for " & docRef.Name

' find out how many pixels I have
totalCount = docRef.Width * docRef.Height

' more info to the out file
fileOut.WriteLine " with a total pixel count of " & totalCount

' remember which channels are currently active
activeChannels = appRef.ActiveDocument.ActiveChannels

' document histogram only works in these modes
If docRef.Mode = 2 Or docRef.Mode = 3 Or docRef.Mode = 6 Then
    'enumerated values = PsDocumentMode --> 2 (psRGB), 3 (psCMYK), 6 (psIndexedColor)

    ' activate the main channels so we can get the document's histogram
    ' using the TurnOnDocumentHistogramChannels function
    Call TurnOnDocumentHistogramChannels(docRef)

    ' Output the documents histogram
    Call OutputHistogram(docRef.Histogram, "Luminosity", fileOut)
End If

' local reference to work from
Set myChannels = docRef.Channels

' loop through each channel and output the histogram
For channelIndex = 1 To myChannels.Count
```

```
' the channel has to be visible to get a histogram
myChannels(channelIndex).Visible = true

' turn off all the other channels
for secondaryIndex = 1 to myChannels.Count
    If Not channelIndex = secondaryIndex Then
        myChannels(secondaryIndex).Visible = false
    End If
Next

' Use the function to dump the histogram
Call OutputHistogram(myChannels(channelIndex).Histogram, _
                    myChannels(channelIndex).Name, fileOut)
Next

' close down the output file
fileOut.Close

WScript.Echo "Histogram File saved in: " & _
            objWshShell.SpecialFolders("Desktop") & "\Histogram.log"

' reset the active channels
docRef.ActiveChannels = activeChannels

' Reset the application preferences
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
appRef.DisplayDialogs = startDisplayDialogs

' Utility function that takes a histogram and name
' and dumps to the output file
Private Function OutputHistogram (inHistogram, inHistogramName, inOutFile)
    ' find out which count has the largest number
    ' I scale everything to this number for the output
    largestCount = 0

    ' a simple indexer I can reuse
    histogramIndex = 0

    ' search through all and find the largest single item
    For Each hist In inHistogram
        histogramCount = histogramCount + CLng(hist)
        If CLng(hist) > largestCount Then
            largestCount = CLng(hist)
        End If
    Next

    'These should match
    If Not histogramCount = totalCount Then
        MsgBox "Something bad is happening!"
    End If

    inOutFile.WriteLine "This histogram has a pixel count of " & histogramCount
    inOutFile.WriteLine

    'see how much each "X" is going to count as
    pixelsPerX = largestCount / 100

    'output this data to the file
```

```
inOutFile.WriteLine "One X = " & pixelsPerX & " pixels."

'output the name of this histogram
inOutFile.WriteLine inHistogramName

inOutFile.WriteLine "Mean Pixels: " & AverageHistogram(inHistogram)
inOutFile.WriteLine "Mean Pixels: " & AverageHistogram(inHistogram)
inOutFile.WriteLine "Std. Dev. Pixels: " & _
    StandardDeviationHistogram(inHistogram)
inOutFile.WriteLine "Median Pixels: " & _
    MedianHistogram(inHistogram, histogramCount)

' loop through all the items and output in the following format
' 001
' 002
' For histogramIndex = 0 To (inHistogram.Count - 1)
histogramIndex = 0
For Each hist in inHistogram
    ' I need an extra "0" for this line item to keep everything in line
    If histogramIndex < 10 Then
        inOutFile.Write "0"
    End If

    ' I need an extra "0" for this line item to keep everything in line
    If histogramIndex < 100 Then
        inOutFile.Write "0"
    End If

    ' output the index to file
    inOutFile.Write histogramIndex

    ' some spacing to make it look nice
    inOutFile.Write " "

    'figure out how many X's I need
    outputX = CDBl(hist) / largestCount * 100

    'output the X's
    For a = 0 to outputX ' (outputX - 1)
        inOutFile.Write "X"
    Next

    inOutFile.WriteLine

    histogramIndex = histogramIndex + 1

Next

inOutFile.WriteLine

End Function

' Function to active all the channels according to the document's mode
' Takes a document reference for input
Private Function TurnOnDocumentHistogramChannels (inDocument)
    ' see how many channels we need to activate
    visibleChannelCount = 0

    'based on the mode of the document
    Select Case inDocument.Mode
```

```
Case 1
    visibleChannelCount = 1
Case 5
    visibleChannelCount = 1
Case 6
    visibleChannelCount = 1
Case 8
    visibleChannelCount = 2
Case 2
    visibleChannelCount = 3
Case 4
    visibleChannelCount = 3
Case 3
    visibleChannelCount = 4
Case 8
    visibleChannelCount = 4
Case 7
    visibleChannelCount = (inDocument.Channels.Count + 1)
Case Else
    visibleChannelCount = (inDocument.Channels.Count + 1)
End Select

' now get the channels to activate into a local array
ReDim aChannelArray(visibleChannelCount)

' index for the active channels array
aChannelIndex = 1
For channelIndex = 1 to inDocument.channels.Count
    If channelIndex <= visibleChannelCount Then
        Set aChannelArray(aChannelIndex) = inDocument.Channels(channelIndex)
        aChannelIndex = aChannelIndex + 1
    End If
Next

End Function

Private Function StandardDeviationHistogram(inputArray)
    Dim numPixels, sum1, sum2, x, gray

    numPixels = 0
    sum1 = 0.0
    sum2 = 0.0

    ' Compute totals for the various statistics
    For gray = 0 To 255
        x = inputArray(gray)
        numPixels = numPixels + x
        sum1 = sum1 + x * gray
        sum2 = sum2 + x * (gray * gray)
    Next

    StandardDeviationHistogram = _
        Sqr((sum2 - (sum1 * sum1) / numPixels) / (numPixels - 1))

End Function

Private Function AverageHistogram(inputArray)
    Dim numPixels, sum1, sum2, x, gray
```



```
numPixels = 0
sum1 = 0.0
sum2 = 0.0

' Compute totals for the various statistics
For gray = 0 To 255
    x = inputArray(gray)
    numPixels = numPixels + x
    sum1 = sum1 + x * gray
    sum2 = sum2 + x * (gray * gray)
Next

AverageHistogram = sum1 / numPixels

End Function

Private Function MedianHistogram(inputArray, numPixels)
    Dim gray, total, mid

    gray = 0
    total = inputArray(0)
    mid = (numPixels + 1) / 2

    Do While (total < mid)
        gray = gray + 1
        total = total + inputArray(gray)
    Loop

    MedianHistogram = gray

End Function
```

CMYKColor

The definition of a CMYK color.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Black	Number (Double)	Read-write. The black color value (as percent) (0.0 - 100.0).
Cyan	Number (Double)	Read-write. The cyan color value (as percent) (0.0 - 100.0).
Magenta	Number (Double)	Read-write. The magenta color value (as percent) (0.0 - 100.0).
typename	String	Read-only. The class name of the referenced <code>CMYKColor</code> object.
Yellow	Number (Double)	Read-write. The yellow color value (as percent) (0.0 - 100.0).

ColorSampler

A color sampler for the document.

Note: For additional information about color samplers, see Adobe Photoshop CS5 help on the Color SamplerTool.

Properties

Property	Value type	What it is
Color	SolidColor	Read-only. The color of the color sampler.
Position	Array of Number (Double)	Read-only. The position of the color sampler in the document.
Parent	object (Document)	Read-only. The <code>ColorSampler</code> object's container.
typename	String	Read-only. The class name of the referenced <code>ColorSampler</code> object.

Methods

Method	Parameter type	Returns	What it does
Move (position)	Array of Number (Double)		Moves the color sampler to a new location in the document. The <code>position</code> parameter (x,y) represents the new horizontal and vertical locations, respectively, of the moved color sampler.
Delete ()			Deletes the <code>ColorSampler</code> object.

ColorSamplers

The collection of `ColorSampler` objects in the document. See [ColorSampler](#).

Properties

Property	Value Type	What it is
<code>Length</code>	number (Long)	Read-only. The number of elements in the <code>ColorSamplers</code> collection.
<code>Parent</code>	object (Document)	Read-only. The <code>ColorSamplers</code> object's container.
<code>typename</code>	string	Read-only. The class name of the referenced <code>ColorSamplers</code> object.

Methods

Method	Parameter Type	Returns	What it does
<code>Add</code> (<code>position</code>)	Array of Number (Double)	ColorSampler	Creates a new <code>ColorSampler</code> object. The <code>position</code> parameter (x,y) represents the horizontal and vertical locations, respectively, of the new color sampler.
<code>Index</code> (<code>ItemPtr</code>)	object (ColorSampler)	Number (Long)	Gets the index of the <code>ColorSampler</code> into the collection.
<code>Item</code> (<code>ItemKey</code>)	number	ColorSampler	Gets an element from the <code>ColorSamplers</code> collection.
<code>RemoveAll</code> ()			Removes all <code>ColorSampler</code> objects from the <code>ColorSamplers</code> collection.

ContactSheetOptions

Options that can be specified for a contact sheet.

Properties

Property	Value Type	What it is
AcrossFirst	Boolean	Read-write. Indicates whether to place the images horizontally (left to right, then top to bottom) first. Default: <code>true</code> .
Application	Object (Application)	Read-only. The application that the object belongs to.
BestFit	Boolean	Read-write. Indicates whether to rotate images for the best fit. Default: <code>false</code> .
Caption	Boolean	Read-write. Indicates whether to use the filename as a caption for the image. Default: <code>true</code> .
ColumnCount	Number (Long)	Read-write. The number of columns to include (1 - 100; default: 5).
Flatten	Boolean	Read-write. Indicates whether to flatten all layers in the final document. Default: <code>true</code> .
Font	PsGalleryFontType	Read-write. The font used for the caption. Default: 1.
FontSize	Number (Long)	Read-write. The font size to use for the caption. Default: 12.
Height	Number (Long)	Read-write. The height (in pixels) of the resulting document (100 - 2900; default: 720).
Horizontal	Number (Long)	Read-write. The horizontal spacing (in pixels) between images (0 - 29000; default: 1).
Mode	PsNewDocumentMode	Read-write. The document color mode. Default: 2 (<code>psNewRGB</code>).
Resolution	Number (Double)	Read-write. The resolution of the document in pixels per inch (35 - 1200; default: 72.0).
RowCount	Number (Long)	Read-write. The number of rows to use (1 - 100; default: 6).
typename	String	Read-only. The class name of the referenced <code>ContactSheetOptions</code> object.
UseAutoSpacing	Boolean	Read-write. Indicates whether to auto space the images. Default: <code>true</code> .

Property	Value Type	What it is (Continued)
Vertical	Number (Long)	Read-write. The vertical spacing (in pixels) between images (0 - 29000; default: 1). Note: Valid only when <code>UseAutoSpacing = false</code> .
Width	Number (Long)	Read-write. The width (in pixels) of the resulting document (100 - 2900; default: 576).

CountItem

A counted item in the document. Also see the method [AutoCount](#), defined on [Document](#).

Note: `CountItem` is available in the Extended Version only.

For additional information about count items, see Adobe Photoshop CS5 help on the Count Tool.

Properties

Property	Value type	What it is
Position	Array of Number (Double)	Read-only. The position of the count item in the document. The array (x,y) represents the horizontal and vertical location of the count item.
Parent	object (Document)	Read-only. The <code>CountItem</code> object's container.
typename	string	Read-only. The class name of the referenced <code>CountItem</code> object.

Methods

Method	Parameter type	Returns	What it does
Delete ()			Deletes the <code>CountItem</code> object.

CountItems

The collection of `CountItems` objects in the document. See [CountItem](#).

Note: `CountItems` is available in the Extended Version only.

Properties

Property	Value Type	What it is
Length	Number (Long)	Read-only. The number of elements in the <code>CountItems</code> collection.
Parent	object (Document)	Read-only. The <code>CountItems</code> object's container.
typename	String	Read-only. The class name of the referenced <code>CountItems</code> object.

Methods

Method	Parameter Type	Returns	What it does
Add (position)	Array of Number (Double)	CountItem	Creates a new <code>CountItem</code> object. Parameter <code>position (x,y)</code> represents the horizontal and vertical positions, respectively, of the new <code>CountItem</code> object.
Index (ItemPtr)	object (CountItem)	Number (Long)	Gets the index of the <code>CountItem</code> into the collection.
Item (ItemKey)	Number (Long)	Document	Gets an element from the <code>CountItem</code> collection.
RemoveAll ()			Removes all <code>CountItem</code> objects from the <code>CountItem</code> collection.

DCS1_SaveOptions

Options that can be specified when saving a CMYK document in DCS1 format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
DCS	PsDCSType	Read-write. Default: 3.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document
Encoding	PsSaveEncoding	Read-write. The type of encoding to use for document. Default: 1.
HalftoneScreen	Boolean	Read-write. Indicates whether to include halftone screen. Default: <code>false</code> .
Interpolation	Boolean	Read-write. Indicates whether to use image interpolation. Default: <code>false</code>)
Preview	PsPreviewType	Read-write. The type of preview. Default: 3.
TransferFunction	Boolean	Read-write. Indicates whether to include the Transfer functions to compensate for dot gain between the image and film. Default: <code>false</code> .
typename	String	Read-only. The class name of the referenced DCS1_SaveOptions object.
VectorData	Boolean	Read-write. Indicates whether to include vector data. Note: Valid only if the document includes vector data (un-rasterized text).

DCS2_SaveOptions

Options that can be specified when saving a CMYK document in DCS2 format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
DCS	PsDCSType	Read-write. The type of composite file to create. Default: 1.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
Encoding	PsSaveEncoding	Read-write. The type of encoding to use. Default: 1.
HalftoneScreen	Boolean	Read-write. Indicates whether to include the halftone screen. Default: <code>false</code> .
Interpolation	Boolean	Read-write. Indicates whether to use image interpolation. Default: <code>false</code> .
MultiFileDCS	Boolean	Read-write. Indicates whether to save color channels as multiple files or a single file. Default: <code>false</code> .
Preview	PsPreviewType	Read-write. The preview type. Default: 3.
SpotColors	Boolean	Read-write. Indicates whether to save spot colors.
TransferFunction	Boolean	Read-write. Indicates whether to include the Transfer functions to compensate for dot gain between the image and film. Default: <code>false</code> .
typename	String	Read-only. The class name of the referenced <code>DCS2_SaveOptions</code> object.
VectorData	Boolean	Read-write. Indicates whether to include vector data. Note: Valid only if the document includes vector data (un-rasterized text).

DICOMOpenOptions

Options that can be specified when opening a DICOM format document.

Note: `DICOMOpenOptions` is available in the Extended Version only.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Anonymize	Boolean	Read-write. Indicates whether to make the patient information anonymous.
Columns	Number (Long)	Read-write. Number of columns in n-up configuration.
Reverse	Boolean	Read-write. Indicates whether to reverse (invert) the image.
Rows	Number (Long)	Read-write. The number of rows in n-up configuration.
ShowOverlays	Boolean	Read-write. Indicates whether to show overlays.
typename	String	Read-only. The class name of the referenced <code>DICOMOpenOptions</code> object.
WindowLevel	Number (Long)	Read-write. The contrast of the image in Hounsfield units.
WindowWidth	Number (Long)	Read-write. The brightness of the image in Hounsfield units.

Document

The active containment object for layers and all most objects in the script; the basic canvas for the file.

Note: In Adobe Photoshop CS5, a document can also be referred to as an image or a canvas.

- The term *image* refers to the entire document and its contents. You can trim or crop an image. You resize an image using the `ResizeImage()` method.
- The term *canvas* refers to the space in which the document sits on the screen. You can rotate or flip the canvas. You resize the canvas using the `ResizeCanvas()` method.

Properties

Property	Value Type	What it is
<code>ActiveChannels</code>	Array (Channel objects)	Read-write. The selected channels.
<code>ActiveHistoryBrushSource</code>	Object (HistoryState)	Read-write. The history state to use with the history brush.
<code>ActiveHistoryState</code>	Object (HistoryState)	Read-write. The selected <code>HistoryState</code> object.
<code>ActiveLayer</code>	Object (ArtLayer or LayerSet)	Read-write. The selected layer.
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>ArtLayers</code>	Object (ArtLayers)	Read-only. The <code>ArtLayers</code> collection.
<code>BackgroundLayer</code>	Object (ArtLayer)	Read-only. The background layer of the document.
<code>BitsPerChannel</code>	PsBitsPerChannelType	Read-write. The number of bits per channel.
<code>Channels</code>	Object (Channels)	Read-only. The <code>Channels</code> collection.
<code>ColorProfileName</code>	String	Read-write. The name of the color profile. Note: Valid only when <code>ColorProfileType = 3</code> or <code>ColorProfileType = 2</code> . See ColorProfileType .
<code>ColorProfileType</code>	PsColorProfileType	Read-write. The type of color model that defines the document's working space.
<code>ColorSamplers</code>	ColorSamplers	Read-only. The current color samplers associated with this document.
<code>ComponentChannels</code>	Array (Channel objects)	Read-only. A list of the component color channels.

Property	Value Type	What it is (Continued)
CountItems	CountItems	Read-only. The current count items. Note: For additional information about count items, see Adobe Photoshop CS5 help on the Coun Tool.
FullName	String	Read-only. The full path name of the document.
Height	Number (Double)	Read-only. The height of the document (unit value).
Histogram	Array of 256 Numbers (Long)	Read-only. A histogram showing the number of pixels at each color intensity level for the composite channel. Note: Valid only when <code>Mode = 2; Mode = 3; or Mode = 6</code> . See Mode .
HistoryStates	Object (HistoryStates)	Read-only. The <code>HistoryStates</code> collection.
Info	Object (DocumentInfo)	Read-only. Metadata about the document.
LayerComps	Object (LayerComps)	Read-only. The <code>LayerComps</code> collection.
Layers	Object (Layers)	Read-only. The <code>Layers</code> collection.
LayerSets	Object (LayerSets)	Read-only. The <code>LayerSets</code> collection.
Managed	Boolean	Read-only. Indicates whether the document a is workgroup document.
MeasurementScale	MeasurementScale	Read-only. The measurement scale for the document. Note: This feature is available in the Extended Version only.
Mode	PsDocumentMode	Read-only. The color profile.
Name	String	Read-only. The document's name.
Parent	Object (Application)	Read-only. The <code>Document</code> object's container.
Path	String	Read-only. The path to the document.
PathItems	Object (PathItems)	Read-only. The <code>PathItems</code> collection.
PixelAspectRatio	Number (Double)	Read-write. The (custom) pixel aspect ratio to use (0.100 - 10.000).
QuickMaskMode	Boolean	Read-write. Indicates whether the document is in Quick Mask mode.

Property	Value Type	What it is (Continued)
Resolution	Number (Double)	Read-only. The document's resolution (in pixels per inch).
Saved	Boolean	Read-only. Indicates whether the document has been saved since the last change.
Selection	Object (Selection)	Read-only. The selected area of the document.
typename	String	Read-only. The class name of the Document object.
Width	Number (Double)	Read-only. The width of the document (unit value).
XMPMetadata	Object (XMPMetadata)	Read-only. XMP data for the image. Camera Raw settings are contained here.

Methods

Method	Parameter Type	Returns	What it does
AutoCount (channel, threshold)	Channel Number (Long)		Counts the number of objects in a document. Creates a CountItem object for each object counted. Note: The AutoCount feature is available in the Extended Version only. For additional information about how to set up objects to count, please see the Count Tool in the Adobe Photoshop CS5 Help
ChangeMode (DestinationMode [, Options])	PsChangeMode object (BitmapConversionOptions or IndexedConversionOptions)		Changes the color profile.
Close ([Saving])	PsSaveOptions		Closes the document. If any changes have been made, the script presents an alert with three options: save, do not save, prompt to save. The optional parameter specifies a selection in the alert box. Default: 3 (psPromptToSaveChanges).

Method	Parameter Type	Returns	What it does (Continued)
ConvertProfile (DestinationProfile, Intent [, BlackPointCompensation] [, Dither])	String PsIntent Boolean Boolean		Changes the color profile. Note: The DestinationProfile parameter must be either a string that names the color mode or Working RGB, Working CMYK, Working Gray, Lab Color (meaning one of the working color spaces or Lab color)
Crop (Bounds [, Angle] [, Width] [, Height])	Array (Double) Number (Double) Number (Double) Number (Double)		Crops the document. The first parameter is an array of four coordinates that mark the portion remaining after cropping, in the following order: left, top, right, bottom.
Duplicate ([Name] [, MergeLayersOnly])	string boolean	Document	Creates a duplicate of the Document object. The optional parameter Name provides the name for the duplicated document. The optional parameter MergeLayersOnly indicates whether to only duplicate merged layers.
ExportDocument (ExportIn [, ExportAs] [, Options])	String PsExportType ExportOptionsIllustrator or ExportOptionsSaveForWeb		Exports the document. Note: The ExportIn parameter represents the path to a file as String.
Flatten ()			Flattens all layers.
FlipCanvas (Direction)	PsDirection		Flips the image within the canvas in the specified direction.
ImportAnnotations (File)	String		Imports annotations into the document.

Method	Parameter Type	Returns	What it does (Continued)
MergeVisibleLayers ()			Flattens all visible layers in the document.
Paste ([IntoSelection])	Boolean	ArtLayer	Pastes the contents of the clipboard into the document. If the optional argument is set to <code>true</code> and a selection is active, the contents are pasted into the selection.
PrintOut ([SourceSpace] [, PrintSpace] [, Intent] [BlackPointCompensation])	PsSourceSpaceType String PsIntent Boolean		Prints the document. Note: <code>PrintSpace</code> specifies the color space for the printer. Valid values are <code>nothing</code> (that is, the same as the source); or <code>Working RGB</code> , <code>Working CMYK</code> , <code>Working Gray</code> , <code>Lab Color</code> (meaning one of the working color spaces or Lab color); or a string specifying a specific colorspace. Default: <i>nothing</i> .
RasterizeAllLayers ()			Rasterizes all layers.
RecordMeasurements ([Source] [, DataPoints])	PsMeasurementSource array of strings		Record measurements of document.
ResizeCanvas ([Width] [, Height] [, Anchor])	Number (Double) Number (Double) PsAnchorPosition		Changes the size of the canvas to display more or less of the image but does not change the image size. See ResizeImage .
ResizeImage ([Width] [, Height] [, Resolution] [, ResampleMethod])	Number (Double) Number (Double) Number (Double) PsResampleMethod		Changes the size of the image.
RevealAll ()			Expands the document to show clipped sections.

Method	Parameter Type	Returns	What it does (Continued)
RotateCanvas (Angle)	Number (Double)		Rotates the canvas (including the image) in clockwise direction.
Save ()			Saves the document.
SaveAs (SaveIn [, Options] [, AsCopy] [, ExtensionType])	String object (corresponding SaveOptions object*) Boolean PsExtensionType * Examples: BMPSaveOptions DCS2 SaveOptions JPEGSaveOptions TiffSaveOptions etc.		Saves the document with specified save options. Note: The Options parameter's value can be a value from the PsSaveDocumentType constant list, or any of the "SaveOptions" objects in the current chapter such as BMPSaveOptions , EPSSaveOptions , JPEGSaveOptions , and so on. Note: The SaveIn parameter represents the path to the file to save in as String.
SplitChannels ()		Array (Document objects)	Splits the document channels into separate images.
Trap (Width)	Number (Long)		Applies trapping to a CMYK document. Note: Valid only when Mode = 3. See Mode .
Trim ([Type] [, Top] [, Left] [, Bottom] [, Right])	PsTrimType Boolean Boolean Boolean Boolean		Trims the transparent area around the image on the specified sides of the canvas. Note: Default is true for all Boolean values.

Sample Script

The following script creates a document that contains two images (a flower and a duck) obtained from the Adobe Photoshop CS5 Samples folder and employs the following steps:

1. Determine which image is larger.
2. Resize the smaller image to match the larger image.
3. Create a merged document twice as high as either image in order to hold both images.
4. Select part of the document and paste the flower into the selection. T
5. Invert the selection and paste the duck into the lower part of the document.
6. Position the flower over the duck.

Document.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, flowerDoc
Dim duckDoc, mergedDoc, selRegion

Set appRef = CreateObject("Photoshop.Application")

' Save the current preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS2 to use pixels and display no dialogs
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' first close all the open documents
Do While appRef.Documents.Count
    appRef.ActiveDocument.Close
Loop

' Open the flower and duck files from the samples folder
Set flowerDoc = appRef.Open(appRef.Path + "/Samples/sunflower.psd")
Set duckDoc = appRef.Open(appRef.Path + "/Samples/Ducky.tif")

' Find out which document is larger
' Resize the smaller document the to the larger document's size
' The resize requires the document be the active/front document
If (flowerDoc.Width * flowerDoc.Height) > (duckDoc.Width * duckDoc.Height) Then
    appRef.ActiveDocument = duckDoc
    duckDoc.Resize flowerDoc.Width, flowerDoc.Height
Else
    appRef.ActiveDocument = flowerDoc
    flowerDoc.ResizeImage duckDoc.Width, duckDoc.Height
End If

' Create a new document twice as high as two files
Set mergedDoc = appRef.Documents.Add(duckDoc.Width, duckDoc.Height * 2, _
    duckDoc.Resolution, "flowerOverDuck")

' Copy the flower to the top; make it the active document so we can manipulate it
appRef.ActiveDocument = flowerDoc
```

```
flowerDoc.ActiveLayer.Copy

'Paste the flower to the merged document, making the merged document active
appRef.ActiveDocument = mergedDoc

' Select a square area at the top of the new document
selRegion = Array(Array(0, 0), _
                  Array(mergedDoc.Width, 0), _
                  Array(mergedDoc.Width, mergedDoc.Height / 2), _
                  Array(0, mergedDoc.Height / 2), _
                  Array(0, 0))

' Create the selection
mergedDoc.Selection.Select(selRegion)

'Paste in the flower
mergedDoc.Paste

' do the same thing for the duck
appRef.ActiveDocument = duckDoc
duckDoc.ActiveLayer.Copy
appRef.ActiveDocument = mergedDoc
mergedDoc.Selection.Select(selRegion)

' Inverting the selection so the bottom of the document is now selected
mergedDoc.Selection.Invert

' Paste the duck
mergedDoc.Paste

' get rid of our originals without modifying them
duckDoc.Close( 2) 'for PsSaveOptions --> 2 (psDoNotSaveChanges)
flowerDoc.Close( 2)

' Reset the application preferences
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
appRef.DisplayDialogs = startDisplayDialogs
```

DocumentInfo

Metadata about a `Document` object. These values can be set by choosing `File > File Info` in the Adobe Photoshop CS5 application.

Note: The `DocumentInfo` object corresponds to the `Info` property of the `Application` object. You use the property name `Info`, rather than the object name, `DocumentInfo`, in a script, as in the following sample, which sets the `Author`, `Caption`, and `Copyrighted` properties:

```
Dim docRef
docRef = Open(fileList[i])
' set the file info
docRef.Info.Author = "Mr. Adobe Programmer"
docRef.Info.Caption = "Adobe photo shoot"
docRef.Info.Copyrighted = 1
```

The following sample uses the `DocumentInfo` object incorrectly:

```
docRef.DocumentInfo.Author = "Mr. Adobe Programmer"
docRef.DocumentInfo.Caption = "Adobe photo shoot"
docRef.DocumentInfo.Copyrighted = 1
```

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>Author</code>	String	Read-write.
<code>authorPosition</code>	String	Read-write.
<code>Caption</code>	String	Read-write.
<code>CaptionWriter</code>	String	Read-write.
<code>Category</code>	String	Read-write.
<code>City</code>	String	Read-write.
<code>Copyrighted</code>	PsCopyrightedType	Read-write. The copyrighted status.
<code>CopyrightNotice</code>	String	Read-write.
<code>Country</code>	String	Read-write.
<code>CreationDate</code>	String	Read-write.
<code>Credit</code>	String	Read-write.
<code>EXIF</code>	Array of Arrays: Array(Array (tag, tag data)), ...)	Read-only. Camera data that includes camera settings used when the image was taken. Sample array values are: tag = "camera"; tag value = "Cannon".
<code>Headline</code>	String	Read-write.
<code>Instructions</code>	String	Read-write.

Property	Value Type	What it is (Continued)
JobName	String	Read-write.
Keywords	Array (Strings)	Read-write. A list of keywords that can identify the document or its contents.
OwnerUrl	String	Read-write.
Parent	Object (Document)	Read-only. The <code>Info</code> object's container.
ProvinceState	String	Read-write.
Source	String	Read-write.
SupplementalCategories	Array (Strings)	Read-write.
Title	String	Read-write.
TransmissionReference	String	Read-write.
typename	String	Read-only. The class name of the referenced <code>Info</code> object.
Urgency	PsUrgency	Read-write.

Sample Script

The following script checks to see if any documents are open. If none are open, it opens the sample file `fish.psd`.

The script then sets the following document info (metadata):

- Author: Mr. Adobe programmer
- Caption: Adobe Photo shoot
- CaptionWriter: Mr. Adobe programmer
- City: San Jose
- CopyrightNotice: Copyright (c) Adobe Programmer Photography
- Copyrighted status: Copyrighted Work
- Country: USA
- State: CA

Note: After the script finishes running, choose File > File Info to display the metadata set by the script.

DocumentInfo.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, docRef

Set appRef = CreateObject("Photoshop.Application")

' Save the current preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS5 to use pixels and display no dialogs
```

```
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' if there are no documents open then try to open a sample file
If appRef.Documents.Count = 0 Then
    appRef.Open(appRef.Path + "/Samples/Fish.psd")
End If

Set docRef = appRef.ActiveDocument

' tag all of the documents with photo shoot information
docRef.Info.Author = "Mr. Adobe Programmer"
docRef.Info.Caption = "Adobe Photo shoot"
docRef.Info.captionWriter = "Mr. Adobe Programmer"
docRef.Info.city = "San Jose"
docRef.Info.CopyrightNotice = "Copyright (c) Adobe Programmer Photography"
docRef.Info.Copyrighted = 1 'for PsCopyrightedType --> 1 (psCopyrightedWork)
docRef.Info.country = "USA"
docRef.Info.provinceState = "CA"

' Reset the application preferences
appRef.DisplayDialogs = startDisplayDialogs
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
```

Documents

The collection of open `Document` objects.

Note: See [‘Document’ on page 60](#) for information on the `Document` object.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>Documents</code> collection.
Parent	Object (Application)	Read-only. The <code>Documents</code> objects' container.
typename	String	Read-only. The class name of the referenced <code>Documents</code> object.

Methods

Method	Parameter Type	Returns	What it does
Add ([Width] [, Height] [, Resolution] [, Name] [, Mode] [, InitialFill] [, PixelAspectRatio] [, BitsPerChannel] [, ColorProfileName])	Number (Double) Number (Double) Number (Double) String PsNewDocumentMode PsDocumentFill Number (Double) PsBitsPerChannelType String	Document	Adds a <code>Document</code> Object. PixelAspectRatio: range from 0.100 - 10.00. Default 1.0 for a square aspect ratio. BitsPerChannelType has a default value of 8 (<code>psDocument8Bits</code>).
Index (ItemPtr)	object (Document)	Number (Long)	Gets the index of the <code>Document</code> into the collection.
Item (ItemKey)	Number (Long)	Document	Gets an element from the <code>Documents</code> collection.

EPSOpenOptions

Options that can be specified when opening an EPS format document.

Properties

Property	Value Type	What it is
AntiAlias	Boolean	Read-write. Indicates whether to use antialias.
Application	Object (Application)	Read-only. The application that the object belongs to.
ConstrainProportions	Boolean	Read-write. Indicates whether to constrain the proportions of the image.
Height	Number (Double)	Read-write. The height of the image (unit value).
Mode	PsOpenDocumentMode	Read-write. The color profile to use as the document mode.
Resolution	Number (Double)	Read-write. The resolution of the document in pixels per inch.
typename	String	Read-only. The class name of the referenced <code>EPSOpenOptions</code> object.
Width	Number (Double)	Read-write. The width of the image (unit value).

EPSSaveOptions

Options that can be specified when saving a document in EPS format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in this document.
Encoding	PsSaveEncoding	Read-write. The type of encoding to use. Default: 1.
HalftoneScreen	Boolean	Read-write. Indicates whether to include the halftone screen. Default: <code>false</code> .
Interpolation	Boolean	Read-write. Indicates whether to use image interpolation. Default: <code>false</code> .
Preview	PsPreviewType	Read-write. The preview type.
PsColorManagement	Boolean	Read-write. Indicates whether to use Postscript color management. Default: <code>false</code> .
TransferFunction	Boolean	Read-write. Indicates whether to include the Transfer functions to compensate for dot gain between the image and film. Default: <code>false</code> .
TransparentWhites	Boolean	Read-write. Indicates whether to display white areas as transparent. Note: Valid only when <code>Document.Mode = 5</code> . See ‘Mode’ on page 61 (in the Properties table of the <code>Document</code> object) or ‘ChangeMode’ on page 63 (in the Methods table of the <code>Document</code> object).
typename	String	Read-only. The class name of the referenced <code>EPSSaveOptions</code> object.
VectorData	Boolean	Read-write. Indicates whether to include vector data. Note: Valid only if the document includes vector data (text).

ExportOptionsIllustrator

Options that can be specified when exporting a [PathItem](#) object to an Adobe Illustrator® file.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Path	PsIllustratorPathType	Read-write. The type of path to export. Default: 1.
PathName	String	Read-write. The name of the path to export. Note: Valid only when <code>Path = 3</code> . See Path .
typename	String	Read-only. The class name of the referenced <code>ExportOptionsIllustrator</code> object.

ExportOptionsSaveForWeb

Options that can be specified when optimizing a document for the Web, or for devices.

Properties

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Blur	Number (Double)	Read-write. Applies blur to the image to reduce artifacts. Default: 0.0.
ColorReduction	PsColorReductionType	Read-write. The color reduction algorithm. Default: 1 (psSelective).
Colors	Number (Long)	Read-write. The number of colors in the palette. Default: 256.
Dither	PsDitherType	Read-write. The type of dither. Default: 2 (psDiffusion).
DitherAmount	Number (Long)	Read-write. The amount of dither. Default: 100. Note: Valid only when <code>Dither = 2</code> . See Dither .
Format	PsSaveDocumentType	Read-write. The file format to use. Default: 3 (psCompuServeGIFSave).
IncludeProfile	Boolean	Read-write. Indicates whether to include the document's embedded color profile. Default: false.
Interlaced	Boolean	Read-write. Indicates whether to download in multiple passes; progressive. Default: false.
Lossy	Number (Long)	Read-write. The amount of lossiness allowed. Default: 0.
MatteColor	RGBColor	Read-write. The colors to blend transparent pixels against.
Optimized	Boolean	Read-write. Indicates whether to create smaller but less compatible files. Default: true. Note: Valid only when <code>format = 6</code> (psJPEGSave). See Format .
PNG8	Boolean	Read-write. Indicates the number of bits; true = 8, false = 24. Default: true. Note: Valid only when <code>format = 13</code> (psPNGSave). See Format .
Quality	Number (Long)	Read-write. The quality of the produced image (0 - 100 as percentage; default: 60).

Property	Value type	What it is (Continued)
Transparency	Boolean	Read-write. Indicates transparent areas of the image should be included in the saved image. Default: <code>true</code> .
TransparencyAmount	Number (Long)	Read-write. The amount of transparency dither. Default: 100. Note: Valid only if <code>Transparency = true</code> . See Transparency .
TransparencyDither	PsDitherType	Read-write. The transparency dither algorithm. Default: 1.
typename	String	Read-only. The class name of the referenced <code>ExportOptionsSaveForWeb</code> object.
WebSnap	Number (Long)	Read-write. The tolerance amount within which to snap close colors to Web palette colors. Default: 0.

GalleryBannerOptions

Options that define the `BannerOptions` property of the `GalleryOptions` object. See ['GalleryOptions' on page 82](#).

Tip: You can preserve default values for many `GalleryBannerOptions` properties by setting the `GalleryOptions` property `PreserveAllMetadata` to `true` or by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>ContactInfo</code>	String	Read-write. The Web photo gallery contact info.
<code>Date</code>	String	Read-write. The Web photo gallery date. Default: current date.
<code>Font</code>	PsGalleryFontType	Read-write. The font setting for the banner text. Default: 1.
<code>FontSize</code>	Number (Long)	Read-write. The font size for the banner text (1 - 7; default: 3).
<code>Photographer</code>	String	Read-write. The Web photo gallery photographer.
<code>SiteName</code>	String	Read-write. The Web photo gallery site name. Default: Adobe Web Photo Gallery.
<code>typename</code>	String	Read-only. The class name of the referenced <code>GalleryBannerOptions</code> object.

GalleryCustomColorOptions

Options that define the `customColorOptions` property of the `GalleryOptions` object. See ['GalleryOptions' on page 82](#).

Tip: You can preserve default values for many `GalleryCustomColorOptions` properties by setting the `GalleryOptions` property `PreserveAllMetadata` to `true` or by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
<code>ActiveLinkColor</code>	Object (RGBColor)	Read-write. The color to use to indicate an active link.
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>BackgroundColor</code>	Object (RGBColor)	Read-write. The background color.
<code>BannerColor</code>	Object (RGBColor)	Read-write. The banner color.
<code>LinkColor</code>	Object (RGBColor)	Read-write. The color to use to indicate a link.
<code>TextColor</code>	Object (RGBColor)	Read-write. The text color.
<code>typename</code>	String	Read-only. The class name of the referenced <code>GalleryCustomColorOptions</code> object.
<code>VisitedLinkColor</code>	Object (RGBColor)	Read-write. The color to use to indicate a visited link.

GalleryImagesOptions

Options that define the `ImagesOptions` property of the `GalleryOptions` object. See ['GalleryOptions' on page 82](#).

Tip: You can preserve default values for many `GalleryImagesOptions` properties by setting the `GalleryOptions` property `PreserveAllMetadata` to `true` or by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Border</code>	Number (Long)	Read-write. The size (in pixels) of the border that separates images (0 - 99; default: 0).
<code>Caption</code>	Boolean	Read-write. Indication of whether to generate image captions. Default: <code>false</code> .
<code>Dimension</code>	Number (Long)	Read-write. The resized image dimensions in pixels. Default: 350. Note: Valid only when <code>ResizeImages = true</code> . See ResizeImages .
<code>Font</code>	PsGalleryFontType	Read-write. The font to use for image captions. Default: 1.
<code>FontSize</code>	Number (Long)	Read-write. The font size for image captions (1 - 7; default: 3). Note: Valid only when <code>Caption = true</code> . See Caption .
<code>ImageQuality</code>	Number (Long)	Read-write. The quality setting for a JPEG image (0 - 12; default: 5).
<code>IncludeCopyright</code>	Boolean	Read-write. Indication of whether to include copyright information in captions. Default: <code>false</code> . Note: Valid only when <code>Caption = true</code> . See Caption .
<code>IncludeCredits</code>	Boolean	Read-write. Indication of whether to include the credits in image captions. Default: <code>false</code> . Note: Valid only when <code>Caption = true</code> . See Caption .

Property	Value Type	What it is (Continued)
IncludeFilename	Boolean	Read-write. Indication of whether to include the file name in image captions. Default: <code>true</code> . Note: Valid only when <code>Caption = true</code> . See Caption .
IncludeTitle	Boolean	Read-write. Indication of whether to include the title in image captions. Default: <code>false</code> . Note: Valid only when <code>Caption = true</code> . See Caption .
NumericLinks	Boolean	Read-write. Indication of whether to add numeric links. Default: <code>true</code> .
ResizeConstraint	PsGalleryConstrainType	Read-write. The image dimensions to constrain in the gallery image. Default: <code>3</code> . Note: Valid only when <code>ResizeImages = true</code> . See ResizeImages .
ResizeImages	Boolean	Read-write. Indication of whether to automatically resize images for placement on the gallery pages. Default: <code>true</code> .
typename	String	Read-only. The class name of the referenced <code>GalleryImagesOptions</code> object.

GalleryOptions

Options that can be specified for a Web photo gallery.

Tip: You can preserve default values for many `GalleryOptions` properties by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
<code>AddSizeAttributes</code>	Boolean	Read-write. Indicates whether width and height attributes for images will be added. Default: <code>true</code> .
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>BannerOptions</code>	Object (GalleryBannerOptions)	Read-write. The options related to banner settings.
<code>CustomColorOptions</code>	Object (GalleryCustomColorOptions)	Read-write. The options related to custom color settings.
<code>EmailAddress</code>	String	Read-write. The email address to show on the Web page.
<code>ImagesOptions</code>	Object (GalleryImagesOptions)	Read-write. The options related to images settings.
<code>IncludeSubFolders</code>	Boolean	Read-write. Indication of whether to include all files found in sub folders of the input folder. Default: <code>true</code> .
<code>LayoutStyle</code>	String	Read-write. The style to use for laying out the Web page. Default: <code>Centered Frame 1 - Basic</code> .
<code>PreserveAllMetadata</code>	Boolean	Read-write. Indicates whether to save metadata. Default: <code>false</code> .
<code>SecurityOptions</code>	Object (GallerySecurityOptions)	Read-write. The options related to security settings.
<code>ThumbnailOptions</code>	Object (GalleryThumbnailOptions)	Read-write. The options related to thumbnail image settings.
<code>typename</code>	String	Read-only. The class name of the referenced <code>GalleryOptions</code> object.

Property	Value Type	What it is (Continued)
UseShortExtension	Boolean	Read-write. Indicates whether the short Web page extension <code>.htm</code> or Number (Long) Web page extension <code>.html</code> will be used. Default: <code>true</code> .
UseUTF8Encoding	Boolean	Read-write. Indicates whether the Web page should use UTF-8 encoding. Default: <code>false</code> .

GallerySecurityOptions

Options that define the `SecurityOptions` property of the `GalleryOptions` object. See ['GalleryOptions' on page 82](#).

Tip: You can preserve default values for many `GallerySecurityOptions` properties by setting the `GalleryOptions` property `PreserveAllMetadata` to `true` or by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Content</code>	PsGallerySecurityType	Read-write. The Web photo gallery security content. Default: 1.
<code>Font</code>	PsGalleryFontType	Read-write. The Web photo gallery security font. Default: 1.
<code>FontSize</code>	Number (Long)	Read-write. The Web photo gallery security font size (1 - 72; default: 3).
<code>Opacity</code>	Number (Long)	Read-write. The Web page security opacity as a percent. Default: 100.
<code>Text</code>	String	Read-write. The Web photo gallery security custom text.
<code>TextColor</code>	Object (RGBColor)	Read-write. The Web page security text color.
<code>TextPosition</code>	PsGallerySecurityTextPositionType	Read-write. The Web photo gallery security text position. Default: 1.
<code>TextRotate</code>	PsGallerySecurityTextRotateType	Read-write. The Web photo gallery security text orientation to use. Default: 1.
<code>typename</code>	String	Read-only. The class name of the referenced <code>GallerySecurityOptions</code> object.

GalleryThumbnailOptions

Options that define the `thumbnailOptions` property of the `GalleryOptions` object. See ['GalleryOptions' on page 82](#).

Tip: You can preserve default values for many `GalleryThumbnailOptions` properties by setting the `GalleryOptions` property `PreserveAllMetadata` to `true` or by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** on the Options area of the Web Photo Gallery dialog.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Border	Number (Long)	Read-write. The amount of border pixels you want around your thumbnail images (0 - 99; default: 0).
Caption	Boolean	Read-write. Indicates whether there is a caption. Default: <code>false</code> .
ColumnCount	Number (Long)	Read-write. The number of columns on the page. Default: 5.
Dimension	Number (Long)	Read-write. The Web photo gallery thumbnail dimension in pixels. Default: 75 .
Font	PsGalleryFontType	Read-write. The Web photo gallery font. Default: 1.
FontSize	Number (Long)	Read-write. The font size for thumbnail images text (1 - 7; default: 3).
IncludeCopyright	Boolean	Read-write. Indication of whether to include copyright information for thumbnails. Default: <code>false</code> .
IncludeCredits	Boolean	Read-write. Indication of whether to include credits for thumbnails. Default: <code>false</code> .
IncludeFilename	Boolean	Read-write. Indication of whether to include file names for thumbnails. Default: <code>false</code> .
IncludeTitle	Boolean	Read-write. Indication of whether to include titles for thumbnails. Default: <code>false</code> .
RowCount	Number (Long)	Read-write. The number of rows on the page. Default: 3.
Size	PsGalleryThumbSizeType	Read-write. The thumbnail image size. Default: 2.
typename	String	Read-only. The class name of the referenced <code>GalleryThumbnailOptions</code> object.

GIFSaveOptions

Options that can be specified when saving a document in GIF format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Colors	Number (Long)	Read-write. The number of palette colors. Note: Valid only when <code>Palette =</code> 2 (<code>psMacOSPalette</code>); 3 (<code>psWindowsPalette</code>); 4 (<code>psWebPalette</code>); 5 (<code>psUniform</code>); 6 (<code>psLocalPerceptual</code>); or 7 (<code>psLocalSelective</code>). See Palette .
Dither	PsDitherType	Read-write. The dither type.
DitherAmount	Number (Long)	Read-write. The amount of dither. (1 - 100; default: 75). Note: Valid only for when <code>Dither = 2</code> (<code>psDiffusion</code>). See Dither .
Forced	PsForcedColors	Read-write. The type of colors to force into the color Palette.
Interlaced	Boolean	Read-write. Indicates whether rows should be interlaced. Default: <code>false</code> .
Matte	PsMatteType	Read-write. The color to use to fill antialiased edges adjacent to transparent areas of the image. Default: 4 (<code>psWhiteMatte</code>). Note: When <code>Transparency = false</code> , the matte color is applied to transparent areas. See Transparency .
Palette	PsPaletteType	Read-write. The type of palette to use. Default: 7 (<code>psLocalSelective</code>).
PreserveExactColors	Boolean	Read-write. Indicates whether to protect colors in the image that contain entries in the color table from being dithered. Note: Valid only when <code>Dither = 2</code> (<code>psDiffusion</code>). See Dither .

Property	Value Type	What it is (Continued)
Transparency	Boolean	Read-write. Indicates whether to preserve transparent areas of the image during conversion to GIF format.
typename	String	Read-only. The class name of the referenced <code>GIFSaveOptions</code> object.

GrayColor

Options for defining a gray color.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Gray	Number (Double)	Read-write. The gray value (0.0 - 100.0; default: 0.0).
typename	String	Read-only. The class name of the referenced <code>grayColor</code> object.

HistoryState

A version of the document stored automatically (and added to the `HistoryStates` collection), which preserves the document's state, each time the document is saved.

Note: See ["HistoryStates" on page 90](#) for information about the `HistoryStates` collection.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Name	String	Read-only. The <code>HistoryState</code> object's name.
Parent	Object (Document)	Read-only. The <code>HistoryState</code> object's container.
Snapshot	Boolean	Read-only. Indicates whether the history state is a snapshot.
typename	String	Read-only. The class name of the referenced <code>HistoryState</code> object.

HistoryStates

The collection of `HistoryState` objects in the document.

Note: See [‘HistoryState’ on page 89](#) for more information on `HistoryState` objects.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>HistoryStates</code> collection.
Parent	Object (Document)	Read-only. The <code>HistoryStates</code> object's container.
typename	String	Read-only. The class name of the referenced <code>HistoryStates</code> object.

Methods

Method	Parameter Type	Returns	What it does
Index (ItemPtr)	Object (HistoryState)	Number (Long)	Gets the index of the <code>HistoryState</code> into the collection.
Item (ItemKey)	Number (Long)	HistoryState	Gets an element from the <code>HistoryStates</code> collection.

HSBColor

Options that can be specified for a color object using the HSB color model.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Brightness	Number (Double)	Read-write. The brightness value (0.0 - 100.0).
Hue	Number (Double)	Read-write. The hue value (0.0 - 100.0).
Saturation	Number (Double)	Read-write. The saturation value (0.0 - 100.0).
typename	String	Read-only. The class name of the referenced <code>HSBColor</code> object.

IndexedConversionOptions

Options that can be specified when converting an RGB image to an indexed color model.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Colors	Number (Long)	Read-write. The number of palette colors. Note: Valid only when <code>Palette =</code> <ul style="list-style-type: none"> 2 (<code>psMacOSPalette</code>) 3 (<code>psWindowsPalette</code>) 4 (<code>psWebPalette</code>) 5 (<code>psUniform</code>) 6 (<code>psLocalPerceptual</code>) 7 (<code>psLocalSelective</code>) 8 (<code>psLocalAdaptive</code>) See Palette .
Dither	PsDitherType	Read-write. The dither type.
DitherAmount	Number (Long)	Read-write. The amount of dither. (1 - 100). Note: Valid only when <code>Dither = 2</code> (<code>psDiffusion</code>).
Forced	PsForcedColors	Read-write. The type of colors to force into the color palette.
Matte	PsMatteType	Read-write. Read-write. The color to use to fill antialiased edges adjacent to transparent areas of the image. Default: 4 (<code>psWhiteMatte</code>). Note: When <code>Transparency = false</code> , the matte color is applied to transparent areas. See Transparency .
Palette	PsPaletteType	Read-write. The palette type. Default: 1 (<code>psExact</code>).
PreserveExactColors	Boolean	Read-write. Indicates whether to protect colors in the image that contain entries in the color table from being dithered. Note: Valid only when <code>Dither = 2</code> . (<code>psDiffusion</code>) See Dither .

Property	Value Type	What it is (Continued)
Transparency	Boolean	Read-write. Indicates whether to preserve transparent areas of the image during conversion to GIF format.
typename	String	Read-only. The class name of the referenced <code>IndexedConversionOptions</code> object.

JPEGSaveOptions

Options that can be specified when saving a document in JPEG format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
FormatOptions	PsFormatOptionsType	Read-write. The download format to use. Default: 1 (psStandardBaseline).
Matte	PsMatteType	Read-write. The color to use to fill antialiased edges adjacent to transparent areas of the image. Default: 4 (psWhiteMatte). Note: When <code>Transparency = false</code> , the matte color is applied to transparent areas. See Transparency .
Quality	Number (Long)	Read-write. The image quality setting to use (affects file size and compression) (0 - 12; default: 3).
Scans	Number (Long)	Read-write. The number of scans to make to incrementally display the image on the page (3 - 5; default: 3). Note: Valid only for when <code>FormatOptions = 3</code> (psProgressive).
typename	String	Read-only. The class name of the referenced JPEGSaveOptions object.

LabColor

Options that can be specified when defining a color object using the LAB color model.

Properties

Property	Value Type	What it is
A	Number (Double)	Read-write. The a-value (-128.0 - 127.0).
Application	Object (Application)	Read-only. The application that the object belongs to.
B	Number (Double)	Read-write. The b-value (-128.0 - 127.0).
L	Number (Double)	Read-write. The L-value (0.0 - 100.0).
typename	String	Read-only. The class name of the referenced <code>LabColor</code> object.

LayerComp

A snapshot of a state of the layers in a document (can be used to view different page layouts or compositions).

Properties

Property	Value Type	What it is
Appearance	Boolean	Read-write. Indicates whether to use layer appearance (layer styles) settings.
Application	Object (Application)	Read-only. The application that the object belongs to.
Comment	String	Read-write. A description of the layer comp.
Name	String	Read-write. The name of the layer comp.
Parent	Object (Document)	Read-write. The <code>LayerComp</code> object's container.
Position	Boolean	Read-write. Indicates whether to use layer position.
Selected	Boolean	Read-only. Indicates whether the layer comp is currently selected.
typename	String	Read-only. The class name of the referenced <code>LayerComp</code> object.
Visibility	Boolean	Read-write. Indicates whether to use layer visibility settings.

Methods

Method	Parameter Type	Returns	What it does
Apply ()			Applies the layer comp to the document.
Delete ()			Deletes the <code>LayerComp</code> object.
Recapture ()			Recaptures the current layer state(s) for this layer comp.
ResetfromComp ()			Resets the layer comp state to the document state.

LayerComps

The collection of `LayerComp` objects in the document.

Note: See [“LayerComp” on page 96](#) for information on `LayerComp` objects.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>LayerComps</code> collection.
Parent	Object (Document)	Read-only. The <code>LayerComps</code> object's container.
typename	String	Read-only. The class name of the referenced <code>LayerComps</code> object.

Methods

Method	Parameter Type	Returns	What it does
Add (Name, Comment, Appearance, Position, Visibility)	String String Boolean Boolean Boolean	LayerComp	Adds a layer comp.
Index (ItemPtr)	Object (LayerComp)	Number (Long)	Gets the index of the <code>LayerComp</code> into the collection.
Item (ItemKey)	Number (Long)	LayerComp	Gets an element from the <code>LayerComps</code> collection.
RemoveAll ()			Removes all <code>LayerComp</code> objects from the <code>LayerComps</code> collection.

Layers

The collection of layer objects, including `ArtLayer` and `LayerSet` objects, in the document.

Note: See [“ArtLayer” on page 24](#) for information on `ArtLayer` objects. See [“LayerSet” on page 99](#) for information on `LayerSet` objects.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>Layers</code> collection.
Parent	Object (Document or LayerSet)	Read-only. The <code>Layers</code> object's container.
typename	String	Read-only. The class name of the referenced <code>Layers</code> object.

Methods

Method	Parameter Type	Returns	What it does
Index (ItemPtr)	Object (ArtLayer or LayerSet)	Number (Long)	Gets the index of the <code>ArtLayer</code> or <code>LayerSet</code> into the collection.
Item (ItemKey)	Number (Long)	Object (ArtLayer or LayerSet)	Gets an element from the collection.
RemoveAll ()			Removes all layers from the collection.

LayerSet

A group of layer objects, which can include `ArtLayer` objects and other (nested) `LayerSet` objects. A single command or set of commands manipulates all layers in a `LayerSet` object.

Properties

Property	Value Type	What it is
AllLocked	Boolean	Read-write. Indicates whether the contents in the layers contained in the <code>LayerSet</code> object are editable.
Application	Object (Application)	Read-only. The application that the object belongs to.
ArtLayers	Object (ArtLayers)	Read-only. The <code>ArtLayers</code> in this <code>LayerSet</code> .
BlendMode	PsBlendMode	Read-write. The blend mode to use for the layer set.
Bounds	Array (Double)	Read-only. The bounding rectangle of the layer set.
EnabledChannels	Array (Channel objects)	Read-write. The channels enabled for the layer set; must be a list of component channels. Note: See <code>Kind</code> in the Properties table for the <code>Channel</code> Object ('Channel' on page 43).
Layers	Object (Layers)	Read-only. The layers in this <code>LayerSet</code> object.
LayerSets	Object (LayerSets)	Read-only. The top level <code>LayerSets</code> in this document.
LinkedLayers	Array (ArtLayer and/or LayerSet)	Read-only. The layers linked to this <code>LayerSet</code> object.
Name	String	Read-write. The name of the <code>LayerSet</code> object.
Opacity	Number (Double)	Read-write. The master opacity of the <code>LayerSet</code> Object (0.0 - 100.0).
Parent	Object (Document or LayerSet)	Read-only. The <code>LayerSet</code> object's container.
typename	String	Read-only. The class name of the referenced <code>LayerSet</code> object.
Visible	Boolean	Read-write. Indicates whether the <code>LayerSet</code> object is visible.

Methods

Method	Parameter Type	Returns	What it does
Delete ()			Deletes the <code>LayerSet</code> object.
Duplicate ([RelativeObject] [, InsertionLocation])	object (ArtLayer or LayerSet) PsElementPlacement	Object (LayerSet)	Creates a duplicate of the <code>LayerSet</code> object.
Link (With)	Object (ArtLayer or LayerSet)		Links the layer set with another layer.
Merge ()		<code>ArtLayer</code>	Merges the layerset; returns a reference to the art layer created by this method.
Move (RelativeObject, InsertionLocation)	Object (Application) PsElementPlacement		Moves the <code>LayerSet</code> object.
Resize ([Horizontal] [, Vertical] [, Anchor])	Number (Double) Number (Double) PsAnchorPosition		Resizes all layers in the layer set to the specified dimensions (as a percentage of its current size) and places the layer set in the specified position.
Rotate (Angle [, Anchor])	Number (Double) PsAnchorPosition		Rotates all layers in the layer set around the specified anchor point.
Translate ([DeltaX] [, DeltaY])	Number (Double) Number (Double)		Moves the position relative to its current position.
Unlink ()			Unlinks the layer set.

LayerSets

The collection of `LayerSet` objects in the document.

Note: See [“LayerSet” on page 99](#) for information on `LayerSet` objects.

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Count</code>	Number (Long)	Read-only. The number of elements in the <code>LayerSets</code> collection.
<code>Parent</code>	Object (Document or LayerSet)	Read-only. The <code>LayerSets</code> object's container.
<code>typename</code>	String	Read-only. The class name of the referenced <code>LayerSets</code> object.

Methods

Method	Parameter Type	Returns	What it does
<code>Add</code> ()		LayerSet	Creates a new <code>LayerSet</code> object.
<code>Index</code> (ItemPtr)	Object (LayerSet)	Number (Long)	Gets the index of the <code>LayerSet</code> into the collection.
<code>Item</code> (ItemKey)	Number (Long)	LayerSet	Gets an element from the <code>LayerSets</code> collection.
<code>RemoveAll</code> ()			Removes the layer set, and any layers or layer sets it contains, from the document.

Sample Script

The following script creates three layer sets, then nests a second layer set in each layer set, and then creates a text layer in each nested set that displays the text “Layer in *n* Set Inside *n* Set”, where *n* represents the ordinal number of the set (first, second, or third).

LayerSets.vbs

```
Dim appRef, docRef, myLayerSets(3,3), textArray, i, myLayers(3)

Set appRef = CreateObject("Photoshop.Application")

'close all open documents
Do While appRef.Documents.Count
    appRef.ActiveDocument.Close
Loop

' create a working document
```

```
Set docRef = appRef.Documents.Add

' Create an array to hold the text
textArray = Array("First", "Second", "Third")

'Create an indexer variable
i = 0

' Create three layer sets at the top level
for i = 0 to 2
    Set myLayerSets(i,0) = docRef.LayerSets.Add
Next

' Rearrange the layer sets with the first one on top, second next, etc.
myLayerSets(1,0).moveAfter(myLayerSets(0,0))
myLayerSets(2,0).moveAfter(myLayerSets(1,0))

' Create a layer set inside each layer set
for i = 0 to 2
    myLayerSets(i,0).Name = textArray(i) + " Set"
    Set myLayerSets(i,1) = myLayerSets(i,0).LayerSets.Add
    myLayerSets(i,1).Name = "Inside " + textArray(i) + " Set"
Next

' Create a text layer with a description inside each layer set
for i = 0 to 2
    Set myLayers(i) = myLayerSets(i,1).ArtLayers.Add
    myLayers(i).Kind = 2 ' PsLayerKind.psTextLayer
    myLayers(i).textItem.Contents = "Layer in " & textArray(i) & " Set Inside " _
        & textArray(i) & " Set"
    myLayers(i).textItem.position = Array(appRef.ActiveDocument.Width * i * 0.33, _
        appRef.ActiveDocument.Height * (i + 1) * 0.25)
    myLayers(i).textItem.Size = 12
Next
```

MeasurementLog

The measurement log for the application. See [MeasurementLog](#) (in the Properties table for the [Application](#) object.)

Note: The MeasurementLog feature is available in the Extended Version only.

Because the MeasurementLog class is a property of the Application object, you use the property name, measurementLog, rather than the class name, MeasurementLog, in your code.

Methods

Method	Parameter type	Returns	What it does
ExportMeasurements ([File] [, Range] [, DataPoints])	String PsMeasurementRange array of strings		Export some measurement(s).
DeleteMeasurements ([Range])	PsMeasurementRange		Delete a measurement.

MeasurementScale

The measurement scale for the document. See [MeasurementScale](#) (in the Properties table for the [Document](#) object.)

Note: The MeasurementScale feature is available in the Extended Version only.

Properties

Property	Value Type	What it is
<code>PixelLength</code>	number (Long)	Read-write. The length in pixels this scale equates to.
<code>LogicalLength</code>	number (Double)	Read-write. The logical length this scale equates to.
<code>LogicalUnits</code>	String	Read-write. The logical units for this scale.

NoColor

An object that represents a missing color.

Properties

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
typename	String	Read-only. The class name of the referenced <code>noColor</code> object.

Notifier

An event-handler object that tells the script to execute specified code when a specified event occurs.

Properties

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Event	String	Read-only. The event ID in four characters or a unique String that the notifier is associated with. Note: For a list of four-character codes, see Appendix A: Event ID Codes .
EventClass	String	Read-only. The class ID of the event associated with the <code>Notifier</code> object, four characters or a unique string. Note: When an event applies to multiple types of objects, you use this property to distinguish which object this <code>Notifier</code> applies to. For example, the <code>Make</code> event ("Mk ") applies to documents ("Dcmn"), channels ("Chnl") and other objects..
EventFile	File	Read-only. The path to the file to execute when the event occurs/activates the notifier.
Parent	Object (Application)	Read-only. The <code>Notifier</code> object's container.
typename	String	Read-only. The class name of the referenced <code>Notifier</code> object.

Methods

Method	Parameter type	Returns	What it does
Remove ()			Deletes the <code>Notifier</code> object. Note: You can remove a <code>Notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from in the Photoshop preferences folder. See Adobe Photoshop CS5 help for more information.

Notifiers

The collection of `Notifier` objects in the document; the `Notifiers` property of the `Application` object.

Note: See 'Notifier' on page 106 for information on `Notifier` objects. See [Notifiers](#) (in the Properties table of the [Application](#) object).

Properties

Property	Value type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Count</code>	Number (Long)	Read-only. The number of elements in the <code>Notifiers</code> collection.
<code>EventClass</code>	String	Read-only. The class ID of the event.
<code>Parent</code>	Object (Application)	Read-only. The <code>Notifiers</code> object's container
<code>typename</code>	String	Read-only. The class name of the referenced <code>Notifiers</code> object.

Methods

Method	Parameter type	Returns	What it does
Add (Event, EventFile [, EventClass])	String String String	Notifier	<p>Creates a <code>Notifier</code> object.</p> <p>Note: <code>EventClass</code> defines the class ID of the event: four characters or a unique string . For a list of four-character codes, see Appendix A: Event ID Codes.</p> <p>Tip: Remember to omit the single quotes when including a four-character ID in your code.</p> <p>Note: <code>EventFile</code> defines the script file that executes when the event occurs.</p> <p>Note: An <code>eventClass</code> value corresponds to the class of object the event is applied to: four characters or a unique string.</p> <p>When an <code>event</code> applies to multiple types of objects, you use the <code>EventClass</code> parameter to distinguish which object this <code>Notifier</code> applies to. For example, the Make event ("Mk ") applies to documents ("Dcmn"), channels ("Chnl") and other objects.</p>
Index (ItemPtr)	Object (Notifier)	Number (Long)	Gets the index of the <code>Notifier</code> into the collection.
Item (ItemKey)	Number (Long)	Notifier	Gets an element from the <code>Notifiers</code> collection.
RemoveAll ()			Removes all <code>Notifier</code> objects from the <code>Notifiers</code> collection. <p>Note: You can remove a <code>notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from in the Photoshop preferences folder. See Adobe Photoshop CS5 help for more information.</p>

PathItem

A path or drawing object, such as the outline of a shape or a straight or curved line, which contains sub paths that comprise its geometry.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Kind	PsPathKind	Read-write. The PathItem object's type.
Name	String	Read-write. The PathItem object's name.
Parent	Object (Document)	Read-only. The PathItem object's container.
SubPathItems	Object (SubPathItems)	Read-only. The sub path objects for this PathItem object.
typename	String	Read-only. The class name of the referenced PathItem object.

Methods

Method	Parameter Type	Returns	What it does
Delete ()			Deletes this PathItem object.
Deselect ()			Deselects this PathItem object.
Duplicate (Name)	String		Duplicates this PathItem object with the new name specified in the argument.
FillPath ([FillColor] [, Mode] [, Opacity] [, PreserveTransparency] [, Feather] [, WholePath] [, AntiAlias])	Object (SolidColor , ArtLayer , HistoryState); or String PsColorBlendMode Number (Double) Boolean Number (Double) Boolean Boolean		Fills the area enclosed by the path (Opacity: 0 - 100 as percent; Feather: 0.0 - 250.0 in pixels).
MakeClippingPath ([Flatness])	Number (Double)		Makes this PathItem object the clipping path for this document; the optional parameter tells the PostScript printer how to approximate curves in the path (0.2 - 100).

Method	Parameter Type	Returns	What it does (Continued)
MakeSelection ([Feather] [, AntiAlias] [, Operation])	Number (Double) Boolean PsSelectionType		Makes a Selection object, whose border is the path, from this PathItem Object (Feather: 0.0 - 250.0 in pixels). Note: See 'Selection' on page 136 .
Select ()			Makes this PathItem object the active or selected PathItem object.
StrokePath ([Tool] [, SimulatePressure])	PsToolType Boolean		Strokes the path with the specified information.

Sample Script

The following creates a path in three segments: two diagonal lines that form a V, and a curved line above the V that makes it look like a 2D ice cream cone.

Paths.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, docRef
Dim lineArray(1), lineArray2(1), lineArray3(2), lineSubPathArray(2), myPathItem

Set appRef = CreateObject("Photoshop.Application")

' Save the current preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS5 to use pixels and display no dialogs
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' first close all the open documents
Do While appRef.Documents.Count
    appRef.ActiveDocument.Close
Loop

' create a document to work with
Set docRef = appRef.Documents.Add(5000, 7000, 72, "Simple Line")

'line #1--it's a straight line so the coordinates for anchor, left, and
'right for each point have the same coordinates
Set lineArray(0) = CreateObject("Photoshop.PathPointInfo")
lineArray(0).Kind = 2 ' for PsPointKind --> 2 (psCornerPoint)
lineArray(0).Anchor = Array(100, 100)
lineArray(0).LeftDirection = lineArray(0).Anchor
lineArray(0).RightDirection = lineArray(0).Anchor
```

```
Set lineArray(1) = CreateObject("Photoshop.PathPointInfo")
lineArray(1).Kind = 2
lineArray(1).Anchor = Array(150, 200)
lineArray(1).LeftDirection = lineArray(1).Anchor
lineArray(1).RightDirection = lineArray(1).Anchor

Set lineSubPathArray(0) = CreateObject("Photoshop.SubPathInfo")
lineSubPathArray(0).operation = 2 'for PsShapeOperation --> 2 (psShapeXOR)
lineSubPathArray(0).Closed = false
lineSubPathArray(0).entireSubPath = lineArray

'line#2
Set lineArray2(0) = CreateObject("Photoshop.PathPointInfo")
lineArray2(0).Kind = 2
lineArray2(0).Anchor = Array(150, 200)
lineArray2(0).LeftDirection = lineArray2(0).Anchor
lineArray2(0).RightDirection = lineArray2(0).Anchor

Set lineArray2(1) = CreateObject("Photoshop.PathPointInfo")
lineArray2(1).Kind = 2
lineArray2(1).Anchor = Array(200, 100)
lineArray2(1).LeftDirection = lineArray2(1).Anchor
lineArray2(1).RightDirection = lineArray2(1).Anchor

Set lineSubPathArray(1) = CreateObject("Photoshop.SubPathInfo")
lineSubPathArray(1).operation = 2
lineSubPathArray(1).Closed = false
lineSubPathArray(1).entireSubPath = lineArray2
'draw the "ice cream" curve above the two lines already on the screen
'it's a curved line, so there are 3 points, not 2 and the
'coordinates for the middle point (lineArray3(1)) are different.
'The left direction is positioned "above" the anchor on the screen.
'The right direction is positioned "below" the anchor
'You can change the coordinates for these points to see
'how the curve works...
Set lineArray3(0) = CreateObject("Photoshop.PathPointInfo")
lineArray3(0).Kind = 2
lineArray3(0).Anchor = Array(200, 100)
lineArray3(0).LeftDirection = lineArray3(0).Anchor
lineArray3(0).RightDirection = lineArray3(0).Anchor

Set lineArray3(1) = CreateObject("Photoshop.PathPointInfo")
lineArray3(1).Kind = 2
lineArray3(1).Anchor = Array(150, 50)
lineArray3(1).LeftDirection = Array(100, 50)
lineArray3(1).RightDirection = Array(200, 50)

Set lineArray3(2) = CreateObject("Photoshop.PathPointInfo")
lineArray3(2).Kind = 2
lineArray3(2).Anchor = Array(100, 100)
lineArray3(2).LeftDirection = lineArray3(2).Anchor
lineArray3(2).RightDirection = lineArray3(2).Anchor

Set lineSubPathArray(2) = CreateObject("Photoshop.SubPathInfo")
lineSubPathArray(2).operation = 2
lineSubPathArray(2).Closed = false
lineSubPathArray(2).entireSubPath = lineArray3

'create the path item
Set myPathItem = docRef.PathItems.Add("A Line", lineSubPathArray)
```

```
' stroke it so we can see something
myPathItem.StrokePath(2) 'for PsToolType --> 2 (psBrush)

' Reset the application preferences
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
appRef.DisplayDialogs = startDisplayDialogs
```


PathItems

The collection of `PathItem` objects in the document.

Note: See '[PathItem](#)' on page 109 for information on `PathItem` objects.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of <code>PathItem</code> objects in the <code>PathItems</code> collection.
Parent	Object (Document)	Read-only. The <code>PathItems</code> object's container.
typename	String	Read-only. The class name of the referenced <code>PathItems</code> object.

Methods

Method	Parameter Type	Returns	What it does
Add (Name, EntirePath)	String Array (SubPathInfo objects)	PathItem	Creates a new <code>PathItem</code> object from the sub paths defined in the array provided in the <code>EntirePath</code> parameter. A new SubPathItem object is created for each <code>SubPathInfo</code> object provided in <code>entirePath</code> , and those <code>SubPathItem</code> objects are added to the SubPathItems collection of the returned <code>PathItem</code> .
Index (ItemPtr)	Object (PathItem)	Number (Long)	Gets the index of the <code>PathItem</code> into the collection.
Item (ItemKey)	Number (Long)	PathItem	Gets a <code>PathItem</code> object from the <code>PathItems</code> collection.
RemoveAll ()			Removes all <code>PathItem</code> objects from the <code>PathItems</code> collection.

PathPoint

Information about an array of `PathPointInfo` objects.

Note: You do not use the `PathPoint` object to create points that make up a path. Rather, you use the `PathPoint` object to retrieve information about the points that describe path segments. To create path points, use the `PathPointInfo` objects. See ['PathPointInfo' on page 115](#).

Properties

Property	Value Type	What it is
<code>Anchor</code>	Array (Double)	Read-only. The point on the curve (<code>LeftDirection</code> / <code>RightDirection</code> are points representing the control handle end points).
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>Kind</code>	PsPointKind	Read-only. The <code>PathPoint</code> object's type.
<code>LeftDirection</code>	Array (Double)	Read-only. The x and y coordinates that define the left handle.
<code>Parent</code>	Object (SubPathItem)	Read-only. The <code>PathPoint</code> object's container.
<code>RightDirection</code>	Array (Double)	Read-only. The x and y coordinates that define the right handle.
<code>typename</code>	String	Read-only. The class name of the referenced <code>PathPoint</code> object.

PathPointInfo

A point on a path, expressed as an array of three coordinate arrays: the anchor point, left direction point, and right direction point. For paths that are straight segments (not curved), the coordinates of all three points are the same. For curved segments, the coordinates are different. The difference between the anchor point and the left or right direction points determines the arc of the curve. You use the left direction point to bend the curve “outward” or make it convex; you use the right direction point to bend the curve “inward” or make it concave.

Properties

Property	Value Type	What it is
Anchor	Array	Read-write. The x and y coordinates of one end point of the path segment.
Application	Object (Application)	Read-only. The application that the object belongs to.
Kind	PsPointKind	Read-write. The <code>PathPointInfo</code> object's kind.
LeftDirection	Array (Double)	Read-write. The location of the left direction point ('in' position).
RightDirection	Array (Double)	Read-write. The location of the right handle ('out' position).
typename	String	Read-only. The class name of the referenced <code>PathPointInfo</code> object.

PathPoints

A collection of `PathPoint` objects that comprises the `PathPoints` property of the `SubPathItem` object.

Note: See [‘SubPathItem’ on page 144](#) for more information.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>PathPoints</code> collection.
Parent	Object (SubPathItem)	Read-only. The <code>PathPoints</code> object's container.
typename	String	Read-only. The class name of the referenced <code>PathPoints</code> object.

Method	Parameter type	Returns	What it does
Index (ItemPtr)	Object (PathPoint)	Number (Long)	Gets the index of the <code>PathPoint</code> into the collection.
Item (ItemKey)	Number (Long)	PathPoint	Gets an element from the <code>PathPoints</code> collection.

PDFOpenOptions

Options that can be specified when opening a document in generic PDF format.

Properties

Property	Value Type	What it is
AntiAlias	Boolean	Read-write. Indicates whether to use antialias.
Application	Object (Application)	Read-only. The application that the object belongs to.
BitsPerChannel	PsBitsPerChannelType	Read-write. The number of bits per channel.
ConstrainProportions	Boolean	Deprecated for Adobe Photoshop CS5.
CropPage	PsCropToType	Read-write. The method of cropping to use.
Height	Double	Deprecated for Adobe Photoshop CS5.
Mode	PsOpenDocumentMode	Read-write. The color model to use.
Name	String	Read-write. The name of the document.
Page	Number (Long)	Read-write. The page to which to open the document.
Resolution	Number (Double)	Read-write. The resolution of the document (in pixels per inch).
SuppressWarnings	Boolean	Read-write. Indicates whether to suppress warnings when opening the document.
typename	String	Read-only. The class name of the referenced <code>PDFOpenOptions</code> object.
UsePageNumber	Boolean	Read-write. Indicates whether the value specified in the <code>page</code> property will refer to an image number when <code>usePageNumber = false</code> . See Page .
Width	Double	Deprecated for Adobe Photoshop CS5.

PDFSaveOptions

Options that can be specified when saving a document in PDF format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels with the file.
Annotations	Boolean	Read-write. Indicates whether to save comments with the file.
Application	Object (Application)	Read-only. The application that the object belongs to.
ColorConversion	Boolean	Read-write. Indicates whether to convert the color profile to a destination profile.
ConvertToEightBit	Boolean	Read-write. Indicates whether to convert a 16-bit image to 8-bit for better compatibility with other applications.
Descripton	String	Read-write. Description of the save options to use.
DestinationProfile	String	Read-write. Description of the final RGB or CMYK output device, such as a monitor or a press standard.
DowngradeColorProfile	Boolean	Deprecated for Adobe Photoshop CS5.
DownSample	PsPDFResampleType	Read-write. The down sample method to use.
DownSampleSize	Number (Double)	Read-write. The size to downsample images if they exceed the limit in pixels per inch.
DownSampleSizeLimit	Number (Double)	Read-write. Limits downsampling or subsampling to images that exceed this value in pixels per inch.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
EmbedFonts	Boolean	Deprecated for Adobe Photoshop CS5.
EmbedThumbnail	Boolean	Read-write. Indicates whether to include a small preview image in Adobe PDF files.
Encoding	PsPDFEncoding	Read-write. The encoding method to use. Default: 1 (psPDFZIP).
Interpolation	Boolean	Deprecated for Adobe Photoshop CS5.

Property	Value Type	What it is (Continued)
JPEGQuality	Number (Long)	Read-write. The quality of the produced image (0 - 12), which is inversely proportionate to the compression amount. Note: Valid only when Encoding = 2 (psPDFJPEG).
Layers	Boolean	Read-write. Indicates whether to save the document's layers.
OptimizeForWeb	Boolean	Read-write. Indicates whether to improve performance of PDF files on Web servers.
OutputCondition	String	Read-write. An optional comment field for inserting descriptions of the output condition. The text is stored in the PDF/X file.
OutputConditionID	String	Read-write. Identifier for the output condition.
PDFCompatibility	PsPDFCompatibilityType	Read-write. The PDF version to make the document compatible with.
PDFStandard	PsPDFStandardType	Read-write. The PDF standard to make the document compatible with.
PreserveEditing	Boolean	Read-write. Indicates whether to reopen the PDF in Adobe Photoshop CS5 with native Photoshop data intact.
PresetFile	String	Read-write. The preset file to use for settings. Note: This option overrides other settings.
ProfileInclusionPolicy	Boolean	Read-write. Indicates whether to show which profiles to include.
RegistryName	String	Read-write. URL where the output condition is registered.
SpotColors	Boolean	Read-write. Indicates whether to save spot colors.
TileSize	Number (Long)	Read-write. Compression option. Note: Valid only when encoding = PDFEncoding.JPEG2000.
Transparency	Boolean	Deprecated for Adobe Photoshop CS5.
typename	String	Read-only. The class name of the referenced PDFSaveOptions object.
UseOutlines	Boolean	Deprecated for Adobe Photoshop CS5.

Property	Value Type	What it is (Continued)
VectorData	Boolean	Deprecated for Adobe Photoshop CS5.
View	Boolean	Read-write. Indicates whether to open the saved PDF in Adobe Acrobat.

PhotoCDOpenOptions

DEPRECATED in Adobe Photoshop CS5. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.

Options to be specified when opening a Kodak Photo CD (PCD) files, including high-resolution files from Pro Photo CD discs.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
ColorProfileName	String	Read-write. The profile to use when reading the image.
ColorSpace	PsPhotoCDCColorSpace	Read-write. The colorspace for the image.
Orientation	PsOrientation	Read-write. The image orientation.
PixelSize	PsPhotoCDSize	Read-write. The image dimensions.
Resolution	Number (Double)	Read-write. The image resolution (in pixels per inch).
typename	String	Read-only. The class name of the referenced <code>PhotoCDOpenOptions</code> object.

PhotoshopSaveOptions

Options that can be specified when saving a document in PSD format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Annotations	Boolean	Read-write. Indicates whether to save the annotations.
Application	Object (Application)	Read-only. The application that the object belongs to.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
Layers	Boolean	Read-write. Indicates whether to preserve the layers.
SpotColors	Boolean	Read-write. Indicates whether to save the spot colors.
typename	String	Read-only. The class name of the referenced PhotoshopSaveOptions object.

PICTFileSaveOptions

Options that can be specified when saving a document in PICT format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Application	Object (Application)	Read-only. The application that the object belongs to.
Compression	PsPICTCompression	Read-write. Default: 1)
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
Resolution	PsPICTBitsPerPixels	Read-write. The number of bits per pixel.
typename	String	Read-only. The class name of the referenced PICTFileSaveOptions object.

PicturePackageOptions

Options that can be specified for a Picture Package.

Property	Value type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Content	PsPicturePackageTextType	Read-write. The content information. Default: 0 (psNoText).
Flatten	Boolean	Read-write. Indicates whether all layers in the final document are flattened. Default: true.
Font	PsGalleryFontType	Read-write. The font used for security text. Default: 1 (psArial).
FontSize	Number (Long)	Read-write. The font size used for security text. Default: 12.
Layout	String	Read-write. The layout to use to generate the picture package. Default: "(2) 5x7".
Mode	PsNewDocumentMode	Read-write. Read-write. The color profile to use as the document mode. Default: 2 (psNewRGB).
Opacity	Number (Long)	Read-write. The Web page security opacity as a percent. Default: 100.
Resolution	Number (Double)	Read-write. The resolution of the document in pixels per inch. Default: 72.0.
Text	String	Read-write. The picture package custom text. Note: Valid only when Content = 2 (psUserText). See Content .
TextColor	RGBColor	Read-write. The color to use for security text.
TextPosition	PsGallerySecurityTextPositionType	Read-write. The security text position. Default: 1 (psCentered).
TextRotate	PsGallerySecurityTextRotateType	Read-write. The orientation to use for security text. Default: 1 (psZero).
typename	String	Read-only. The class name of the referenced PicturePackageOptions object.

PixarSaveOptions

Options that can be specified when saving a document in Pixar format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Application	Object (Application)	Read-only. The application that the object belongs to.
typename	String	Read-only. The class name of the referenced <code>PixarSaveOptions</code> object.

PNGSaveOptions

Options that can be specified when saving a document in PNG format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Interlaced	Boolean	Read-write. Indicates whether the should rows be interlaced. Default: <i>false</i> .
typename	String	Read-only. The class name of the referenced <code>PNGSaveOptions</code> object.

Preferences

Options to define for the `Preferences` property of the `Application` object. See ['Preferences' on page 17](#) (in the Properties table for the `Application` object).

Note: Defining the `Preferences` properties is basically equivalent to selecting `Edit > Preferences` (Windows) or `Photoshop > Preferences` in the Adobe Photoshop CS5 application. For explanations of individual settings, please refer to Adobe Photoshop CS5 Help.

Properties

Property	Value Type	What it is
AdditionalPluginFolder	String	Read-write. The path to an additional plug-in folder. Note: Valid only when <code>UseAdditionalPluginFolder = true</code> . See UseAdditionalPluginFolder .
Application	Object (Application)	Read-only. The application that the object belongs to.
AskBeforeSavingLayeredTIFF	Boolean	Read-write. Indicates whether to ask the user to verify layer preservation options when saving a file in TIFF format.
AutoUpdateOpenDocuments	Boolean	Read-write. Indicates whether to automatically update open documents.
BeepWhenDone	Boolean	Read-write. Indicates whether to beep when a process finishes.
ColorChannelsInColor	Boolean	Read-write. Indicates whether to display component channels in the Channels palette in color.
ColorPicker	PsColorPicker	Read-write.
ColumnGutter	Number (Double)	Read-write. The width of the column gutters (in points). (0.1 - 600.0).
ColumnWidth	Number (Double)	Read-write. Column width (in points) (0.1 - 600.0).
CreateFirstSnapshot	Boolean	Read-write. Indicates whether to automatically make the first snapshot when a new document is created.
DynamicColorSliders	Boolean	Read-write. Indicates whether dynamic color sliders appear in the Color palette.
EditLogItems	PsEditLogItemsType	Read-write. The options for editing history log items. Note: Valid only when <code>UseHistoryLog = true</code> . See UseHistoryLog .

Property	Value Type	What it is (Continued)
ExportClipboard	Boolean	Read-write. Indicates whether to retain Adobe Photoshop CS5 contents on the clipboard after you exit the application.
FontPreviewSize	psFontPreviewType	Read-write. Indicates whether to show font previews in the type tool font menus.
GamutWarningOpacity	Number (Double)	Read-write. (0 - 100 as percent).
GridSize	PsGridSize	Read-write. The size to use for squares in the grid.
GridStyle	PsGridLineStyle	Read-write. The formatting style for non-printing grid lines.
GridSubDivisions	Number (Long)	Read-write. (1 - 100)
GuideStyle	PsGuideLineStyle	Read-write. The formatting style for non-printing guide lines.
ImageCacheLevels	Number (Long)	Read-write. The number of images to hold in the cache (1 - 8).
ImagePreviews	PsSaveBehavior	Read-write. The behavior mode to use when saving files.
Interpolation	PsResampleMethod	Read-write. The method to use to assign color values to any new pixels created when an image is resampled or resized.
KeyboardZoomResizesWindows	Boolean	Read-write. Indicates whether to automatically resize the window when zooming in or out using keyboard shortcuts.
MaximizeCompatibility	PsQueryStateType	Read-write. The behavior to use to check whether to maximize compatibility when opening Adobe Photoshop CS5 (PSD) files.
MaxRAMuse	Number (Long)	Read-write. The maximum percentage of available RAM used by Adobe Photoshop CS5 (5 - 100).
NonLinearHistory	Boolean	Read-write. Indicates whether to allow non-linear history.
NumberOfHistoryStates	Number (Long)	Read-write. The number of history states to preserve (1 - 100).
OtherCursors	PsOtherPaintingCursors	Read-write. The type of pointer to use.

Property	Value Type	What it is (Continued)
PaintingCursors	PsPaintingCursors	Read-write. The type of pointer to use.
Parent	Object (Application)	Read-write. The <code>Preferences</code> object's container.
PixelDoubling	Boolean	Read-write. Indicates whether to halve the resolution or (double the size of pixels) to make previews display more quickly.
PointSize	PsPointType	Read-write. The point/pica size.
RecentFileListLength	Number (Long)	Read-write. The number of items in the recent file list (0 - 30).
RulerUnits	PsUnits	Read-write. The unit the scripting system will use when receiving and returning values.
SaveLogItems	PsSaveLogItemsType	Read-write. The options for saving the history items.
SaveLogItemsFile	String	Read-write. The path to the history log file.
SavePaletteLocations	Boolean	Read-write. Indicates whether to make new palette locations the default location.
ShowAsianTextOptions	Boolean	Read-write. Indicates whether to display Asian text options in the Paragraph palette.
ShowEnglishFontNames	Boolean	Read-write. Indicates whether to list Asian font names in English.
ShowSliceNumber	Boolean	Read-write. Indicates whether to display slice numbers in the document window when using the Slice tool.
ShowToolTips	Boolean	Read-write. Indicates whether to show pop up definitions on mouse over.
SmartQuotes	Boolean	Read-write. Indicates whether to use curly or straight quote marks.
typename	String	Read-only. The class name of the referenced <code>Preferences</code> object.
TypeUnits	PsTypeUnits	Read-write. The unit type-size that the numeric inputs are assumed to represent.

Property	Value Type	What it is (Continued)
UseAdditionalPluginFolder	Boolean	Read-write. Indicates whether to use an additional folder for compatible plug-ins stored with a different application.
UseHistoryLog	Boolean	Read-write. Indicates whether to create a log file for history states.
UseLowerCaseExtension	Boolean	Read-write. Indicates whether the file extension should be lowercase.
UseShiftKeyForToolSwitch	Boolean	Read-write. Indicates whether to enable cycling through a set of hidden tools.
UseVideoAlpha	Boolean	Read-write. Indicates whether to enable Adobe Photoshop CS5 to send transparency information to your computer's video board. (Requires hardware support.)

PresentationOptions

Options that can be specified for PDF presentations.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
AutoAdvance	Boolean	Read-write. Indicates whether to auto advance images when viewing the presentation. Default: true. Note: Valid only when <code>Presentation = true</code> . See Presentation .
IncludeFilename	Boolean	Read-write. Indicates whether to include the file name for the image (default: false).
Interval	Number (Long)	Read-write. The time in seconds before the view is auto advanced (1 - 60; default: 5). Note: Valid only when <code>AutoAdvance = true</code> . See AutoAdvance .
Loop	Boolean	Read-write. Indicates whether to begin the presentation again after the last page. Default: false. Note: Valid only when <code>AutoAdvance = true</code> . See AutoAdvance .
Magnification	PsMagnificationType	Read-write. The magnification type to use when viewing the image.
PDFFileOptions	PDFSaveOptions	Read-write. Options to use when creating the PDF file.
Presentation	Boolean	Read-write. Indicates whether the output will be a presentation. Default: false); when false, the output is a Multi-Page document.
Transition	PsTransitionType	Read-write. The transition from one image to the next. Default: 9 (psNoTransition). Note: Valid only when <code>AutoAdvance = true</code> . See AutoAdvance .
typename	String	Read-only. The class name of the referenced <code>PDFPresentationOptions</code> object.

RawFormatOpenOptions

Options that can be specified when opening a document in RAW format.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
BitsPerChannel	Number (Long)	Read-write. The number of bits for each channel. Note: The only valid values are <code>BitsPerChannel = 8</code> or <code>BitsPerChannel = 16</code> .
ByteOrder	PsByteOrder	Read-write. The order in which bytes will be read. Note: Valid only when <code>BitsPerChannel = 16</code> . See BitsPerChannel .
ChannelNumber	Number (Long)	Read-write. The number of channels in the image (1 - 56). Note: The value of <code>ChannelNumber</code> cannot exceed the number of channels in the image. When <code>BitsPerChannel = 16</code> , only the following values are valid: 1, 3, or 4. See BitsPerChannel .
HeaderSize	Number (Long)	Read-write. The number of bytes of information that will appear in the file before actual image information begins; that is, the number of zeroes inserted at the beginning of the file as placeholders (0 - 1919999).
Height	Number (Long)	Read-write. The height of the image (in pixels).
InterleaveChannels	Boolean	Read-write. Indicates whether to store color values sequentially.
RetainHeader	Boolean	Read-write. Indicates whether to retain the header when saving. Note: Valid only when HeaderSize is 1 or greater.
typename	String	Read-only. The class name of the referenced <code>RawFormatOpenOptions</code> object.
Width	Number (Long)	Read-write. The image width in pixels.

RawSaveOptions

Options that can be specified when saving a document in RAW format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether alpha channels should be saved.
Application	Object (Application)	Read-only. The application that the object belongs to.
SpotColors	Boolean	Read-write. Indicates whether the spot colors should be saved.
typename	String	Read-only. The class name of the referenced <code>RawSaveOptions</code> object.

RGBColor

The definition of a color in RGB color mode.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Blue	Number (Double)	Read-write. The blue color value (0.0 - 255.0; default: 255.0).
Green	Number (Double)	Read-write. The green color value (0.0 - 255.0; default: 255.0).
HexValue	String	Read-write. The hex representation of the color.
Red	Number (Double)	Read-write. The red color value (0.0 - 255.0; default: 255.0).
typename	String	Read-only. The class name of the referenced <code>RGBColor</code> object.

Selection

The selected area of a document or layer.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Bounds	Array of Number (Double)	Read-only. The bounding rectangle of the entire selection.
Parent	Object (Document)	Read-only. The object's container.
Solid	Boolean	Read-only. Indicates if the bounding rectangle is a solid.
typename	String	Read-only. The class name of the referenced <code>Selection</code> object.

Methods

Method	Parameter Type	Returns	What it does
Clear ()			Clears the selection and does not copy it to the clipboard.
Contract (By)	Number (Double)		Contracts the selection by the specified amount.
Copy ([Merge])	Boolean		Copies the selection to the clipboard. When the optional argument is used and set to <code>true</code> , a merged copy is performed (all visible layers in the selection are copied).
Cut ()			Clears the current selection and copies it to the clipboard.
Deselect ()			Deselects the current selection.
Expand (By)	Number (Double)		Expands the selection by the specified amount.
Feather (By)	Number (Double)		Feathers the edges of the selection by the specified amount.

Method	Parameter Type	Returns	What it does (Continued)
Fill (FillType [, Mode] [, Opacity] [, PreserveTransparency])	Object (SolidColor , or HistoryState) PsColorBlendMode Number (Long) Boolean		Fills the selection (Opacity: 1 - 100 as percent).
Grow (Tolerance, AntiAlias)	Number (Long) Boolean		Grows the selection to include all adjacent pixels falling within the specified tolerance range.
Invert ()			Inverts the selection (deselects the selection and selects the rest of the layer or document). Note: To flip the selection shape, see Rotate .
Load (From [, Combination] [, Inverting])	Channel PsSelectionType Boolean		Loads the selection from the specified channel.
MakeWorkPath ([Tolerance])	Number (Double)		Makes this selection item the work path for this document.
Resize ([Horizontal] [, Vertical] [, Anchor])	Number (Double) Number (Double) PsAnchorPosition		Resizes the selected area to the specified dimensions and anchor position.
ResizeBoundary ([Horizontal] [, Vertical] [, Anchor])	Number (Double) Number (Double) PsAnchorPosition		Changes the size of the selection to the specified dimensions around the specified anchor.
Rotate (Angle [, Anchor])	Number (Double) PsAnchorPosition		Rotates the selection by the specified amount around the specified anchor point.
RotateBoundary (Angle [, Anchor])	Number (Double) PsAnchorPosition		Rotates the boundary of the selection around the specified anchor.
Select (Region [, Type] [, Feather] [, AntiAlias])	Array (Points: Array (Array (x,y),...) PsSelectionType Number (Double) Boolean		Selects the specified region.
SelectAll ()			Selects the entire layer.

Method	Parameter Type	Returns	What it does (Continued)
SelectBorder (Width)	Number (Double)		Selects the selection border only (in the specified width); subsequent actions do not affect the selected area within the borders.
Similar (Tolerance, AntiAlias)	Number (Long) Boolean		Grows the selection to include pixels throughout the image falling within the tolerance range.
Smooth (Radius)	Number (Long)		Cleans up stray pixels left inside or outside a color-based selection (within the radius specified in pixels).
Store (Into [, Combination])	Channel PsSelectionType		Saves the selection as a channel.
Stroke (StrokeColor, Width [, Location] [, Mode] [, Opacity] [, PreserveTransparency])	Object (SolidColor) Number (Long) PsStrokeLocation PsColorBlendMode Number (Long) Boolean		Strokes the selection border (Opacity: 1 - 100 as percent).
Translate ([DeltaX] [, DeltaY])	Number (Double) Number (Double)		Moves the entire selection relative to its current position.
TranslateBoundary ([DeltaX] [, DeltaY])	Number (Double) Number (Double)		Moves the selection relative to its current position.

Sample Script

► **The following script creates a checkerboard using the following steps:**

1. Create an 800 x 800 pixel document.
2. Divide the entire document into 100 x 100 pixel squares.
3. Select every other square in the first row, then shift the selection criteria to select the alternate squares in the following row. Repeat until every other square in the document is selected.
4. Fill the selected squares with the foreground color from the palette.
5. Invert the selection and fill the newly selected squares with the background color from the palette.
6. Deselect the squares to remove the selection outlines (the "marching ants").

Selection.vbs

```
Dim appRef, startRulerUnits, startTypeUnits, startDisplayDialogs, docSize
```

```
Dim cells, cellSize, checkersDoc, shiftIt, h, v, eventWait, enumRedrawComplete
Dim typeState, keyState, desc

Set appRef = CreateObject("Photoshop.Application")

' Save the current Preferences
startRulerUnits = appRef.Preferences.RulerUnits
startTypeUnits = appRef.Preferences.TypeUnits
startDisplayDialogs = appRef.DisplayDialogs

' Set Photoshop CS5 to use pixels and display no dialogs
appRef.Preferences.RulerUnits = 1 'for PsUnits --> 1 (psPixels)
appRef.Preferences.TypeUnits = 1 'for PsTypeUnits --> 1 (psPixels)
appRef.DisplayDialogs = 3 'for PsDialogModes --> 3 (psDisplayNoDialogs)

' Close all the open documents
Do While appRef.Documents.Count
    appRef.ActiveDocument.Close
Loop

' Create variables for the 800 pixel board divided in even 100 x 100 squares
docSize = 800
cells = 8
cellSize = docSize / cells

' create a new document
Set checkersDoc = appRef.Documents.Add(docSize, docSize, 72, "Checkers")

' Create a variable to use for selecting the checker board
' That allows me to shift the selection one square to the right
' on every other row, and then shift back for the rows in between.
shiftIt = true

' loop through vertically to create the first row
v = 0
For v = 0 To (docSize - 1) Step cellSize
    ' Switch the shift For a new row
    shiftIt = Not shiftIt

    ' loop through horizontally
    h = 0
    For h = 0 To (docSize - 1) Step (cellSize * 2)
        ' push over the cellSize to start with only
        If shiftIt And h = 0 Then
            h = h + cellSize
        End If
        ' Select a square
        selRegion = Array(Array(h, v), _
            Array(h + cellSize, v), _
            Array(h + cellSize, v + cellSize), _
            Array(h, v + cellSize), _
            Array(h, v))

        If h = 0 And v = 0 Then
            checkersDoc.Selection.Select selRegion
        Else
            checkersDoc.Selection.Select selRegion, 2
            ' value 2 is for PsSelectionType --> 2 (psExtendSelection)
        End If
    Next h
Next v
```

```
        ' turn this off for faster execution
        ' turn this on for debugging
        WaitForRedraw
    Next
Next

' Fill the current selection with the Foreground color
checkersDoc.Selection.Fill(appRef.ForegroundColor)

' Invert the selection
checkersDoc.Selection.Invert()

' Fill the new selection with the background color
checkersDoc.Selection.Fill(appRef.BackgroundColor)

' Clear the selection to get rid of the non-printing borders
checkersDoc.Selection.Deselect()

' Reset the application preferences
appRef.Preferences.RulerUnits = startRulerUnits
appRef.Preferences.TypeUnits = startTypeUnits
appRef.DisplayDialogs = startDisplayDialogs

' -----
' A helper function for debugging
' It also helps the user see what is going on
' if you turn it off for this example you
' get a flashing cursor for a Number (Long) time
' Save a bit of time by creating the variables only once
Private Sub WaitForRedraw
    If VarType(eventWait) = vbEmpty Then
        eventWait = appRef.charIDToTypeID("Wait")
    End If
    If VarType(enumRedrawComplete) = vbEmpty Then
        enumRedrawComplete = appRef.charIDToTypeID("RdCm")
    End If
    If VarType(typeState) = vbEmpty Then
        typeState = appRef.charIDToTypeID("Stte")
    End If
    If VarType(keyState) = vbEmpty Then
        keyState = appRef.charIDToTypeID("Stte")
    End If
    If VarType(desc) = vbEmpty Then
        Set desc = CreateObject("Photoshop.ActionDescriptor")
        desc.putEnumerated KeyState, typeState, enumRedrawComplete
    End If
    appRef.executeAction eventWait, desc, 3 _
    'value of 3 for PsDialogModes --> 3 (psDisplayNoDialogs)
End Sub
```

SGIRGBSaveOptions

Options that can be specified when saving a document in SGIRGB format.

Note: The SGIRGB format is not installed automatically with Adobe Photoshop CS5.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Application	Object (Application)	Read-only. The application that the object belongs to.
SpotColors	Boolean	Read-write. Indicates whether to save the spot colors.
typename	String	Read-only. The class name of the referenced <code>SGIRGBSaveOptions</code> object.

SolidColor

A color definition used in the document.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
CMYK	Object (CMYKColor)	Read-write. The CMYK color mode.
Gray	Object (GrayColor)	Read-write. The Grayscale color mode.
HSB	Object (HSBColor)	Read-write. The HSB color mode.
Lab	Object (LabColor)	Read-write. The LAB color mode.
Model	PsColorModel	Read-write. The color model.
NearestWebColor	Object (RGBColor)	Read-only. The nearest Web color to the current color.
RGB	Object (RGBColor)	Read-write. The RGB color mode.
typename	String	Read-only. The class name of the referenced <code>SolidColor</code> object.

Methods

Method	Parameter Type	Returns	What it does
IsEqual (Color)	SolidColor	Boolean	Indicates whether the <code>SolidColor</code> object is visually equal to the specified color.

SubPathInfo

An array of `PathPointInfo` objects that describes a straight or curved segment of a path.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Closed	Boolean	Read-write. Indicates whether the path describes an enclosed area.
EntireSubPath	Array (PathPoint objects)	Read-write.
Operation	PsShapeOperation	Read-write. The sub path's operation on other sub paths.
typename	String	Read-only. The class name of the referenced <code>SubPathInfo</code> object.

SubPathItem

Information about a path.

Note: You do not use the `SubPathItem` object to create a path. Rather, you create path segments using the [SubPathInfo](#) object. Use the `SubPathItem` object to retrieve information about a path. (Note that all of the `SubPathItem` object's properties are *Read-only*.)

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Closed	Boolean	Read-only. Indicates whether the path is closed.
Operation	PsShapeOperation	Read-only. The sub path operation on other sub paths.
Parent	Object (PathItem)	Read-only. The object's container.
PathPoints	Object (PathPoints)	Read-only. The <code>PathPoints</code> collection.
typename	String	Read-only. The class name of the referenced <code>SubPathItem</code> object.

SubPathItems

A collection of `SubPathItem` objects. See [SubPathItem](#).

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the collection belongs to.
Count	Number (Long)	Read-only. The number of elements in the <code>SubPathItems</code> collection.
Parent	Object (PathItem)	Read-only. The <code>SubPathItems</code> object's container.
typename	String	Read-only. The class name of the referenced <code>SubPathItems</code> object.

Methods

Method	Parameter type	Returns	What it does
Index (ItemPtr)	Object (SubPathItem)	Number (Long)	Gets the index of the <code>SubPathItem</code> into the collection.
Item (ItemKey)	Number (Long)	SubPathItem	Gets an element from the <code>SubPathItems</code> collection.

TargaSaveOptions

Options that can be set when saving a document in TGA (Targa) format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Application	Object (Application)	Read-only. The application that the object belongs to.
Resolution	PsTargaBitsPerPixels	Read-write. The number of bits per pixel. Default: 24.
RLECompression	Boolean	Read-write. Indicates whether RLE compression should be used. Default: <code>true</code> .
typename	String	Read-only. The class name of the referenced <code>TargaSaveOptions</code> object.

TextFont

Details about a font in the `TextFonts` collection.

Note: See [TextFonts](#) for more information on the `TextFonts` collection.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Family	String	Read-only. The font family.
Name	String	Read-only. The name of the font.
Parent	Object (Application)	Read-only. The object's container.
PostScriptName	String	Read-only. The PostScript name of the font.
Style	String	Read-only. The font style.
typename	String	Read-only. The class name of the referenced <code>TextFont</code> object.

TextFonts

The collection of fonts available on your computer.

Note: The `TextFonts` object corresponds to the `Fonts` property of the `Application` object. In a script, you use `Fonts` to refer to a `TextFonts` object. The following sample demonstrates how to use the `Count` property of the `TextFonts` object to display a dialog that indicates the number of fonts installed on the machine.

- **Correct:**
`Alert appRef.Fonts.Count`
- **Incorrect:**
`Alert appRef.TextFonts.Count`

See ['Application' on page 16](#), specifically the `Fonts` property, for more information.

Properties

Property	Value Type	What it is
<code>Application</code>	Object (Application)	Read-only. The application that the collection belongs to.
<code>Count</code>	Number (Long)	Read-only. The number of elements in the <code>TextFonts</code> collection.
<code>Parent</code>	Object (Application)	Read-only. The object's container.
<code>typename</code>	String	Read-only. The class name of the referenced <code>TextFonts</code> object.

Methods

Method	Parameter Type	Returns	What it does
<code>Index</code> (<code>ItemPtr</code>)	Object (TextFont)	Number (Long)	Gets the index of the <code>TextFont</code> into the collection.
<code>Item</code> (<code>ItemKey</code>)	Number (Long)	TextFont	Gets an element from the <code>TextFonts</code> collection.

TextItem

The text in an `ArtLayer` object whose `Kind` property's value is 2.

Note: See [ArtLayer](#), specifically the `Kind` property, for more information.

Properties

Property	Value Type	What it is
<code>AlternateLigatures</code>	Boolean	Read-write. Indicates whether to use alternate ligatures. Note: Alternate ligatures are the same as Discretionary Ligatures. Please refer to Adobe Photoshop CS5 Help for more information.
<code>AntiAliasMethod</code>	PsAntiAlias	Read-write. The method of anti aliasing to use.
<code>Application</code>	Object (Application)	Read-only. The application that the object belongs to.
<code>AutoKerning</code>	PsAutoKernType	Read-write. The auto kerning option to use.
<code>AutoLeadingAmount</code>	Number (Double)	Read-write. The percentage to use for auto. Default leading (0.01 - 5000.00 in points). Note: Valid only when <code>UseAutoLeading = true</code> . See UseAutoLeading .
<code>BaselineShift</code>	Number (Double)	Read-write. The unit value to use in the baseline offset of text.
<code>Capitalization</code>	PsCase	Read-write. The text case.
<code>Color</code>	Object (SolidColor)	Read-write. The text color.
<code>Contents</code>	String	Read-write. The actual text in the layer.
<code>DesiredGlyphScaling</code>	Number (Double)	Read-write. The desired amount (percentage) to scale the horizontal size of the text letters (50 - 200; at 100, the width of characters is not scaled). Note: Valid only when <code>Justification =</code> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); OR 7 (<code>psFullyJustified</code>). See Justification . The following values are also required: MinimumGlyphScaling and MaximumGlyphScaling .

Property	Value Type	What it is (Continued)
DesiredLetterScaling Note: 'Letter Scaling' is basically equivalent to 'Letter Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).	Number (Double)	Read-write. The amount of space between letters (100 - 500; at 0, no space is added between letters). Note: Valid only when <code>Justification =</code> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). See Justification . The following values are also required: MinimumLetterScaling and MaximumLetterScaling .
DesiredWordScaling Note: 'Word Scaling' is basically equivalent to 'Word Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).	Number (Double)	Read-write. The amount (percentage) of space between words (0 -1000; at 100, no additional space is added between words). Note: Valid only when <code>Justification =</code> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). See Justification . The following values are also required: MinimumWordScaling and MaximumWordScaling .
Direction	PsDirection	Read-write. The text orientation.
FauxBold	Boolean	Read-write. Indicates whether to use faux bold. Default: <code>false</code> . Note: Using <code>FauxBold.true</code> is equivalent to selecting text and clicking the Faux Bold button in the Character palette.
FauxItalic	Boolean	Read-write. Indicates whether to use faux italic. Default: <code>false</code> . Note: Using <code>FauxItalic.true</code> is equivalent to selecting text and clicking the Faux Italic button in the Character palette.
FirstLineIndent	Number (Double)	Read-write. The amount (unit value) to indent the first line of paragraphs (-1296 - 1296).
Font	String	Read-write. The text face of the character.
HangingPunctuation	Boolean	Read-write. Indicates whether to use roman Hanging Punctuation.
Height	Number (Double)	Read-write. The height of the bounding box (unit value) for paragraph text. Note: Valid only when <code>Kind =</code> 2 (<code>psParagraphText</code>). See Kind .

Property	Value Type	What it is (Continued)
HorizontalScale	Number (Long)	Read-write. Character scaling (horizontal) in proportion to vertical scale (0 - 1000 in percent). See VerticalScale .
HyphenateAfterFirst	Number (Long)	Read-write. The number of letters after which hyphenation in word wrap is allowed (1 - 15).
HyphenateBeforeLast	Number (Long)	Read-write. The number of letters before which hyphenation in word wrap is allowed (1 - 15).
HyphenateCapitalWords	Boolean	Read-write. Indicates whether to allow hyphenation in word wrap of capitalized words.
HyphenateWordsLongerThan	Number (Long)	Read-write. The minimum number of letters a word must have in order for hyphenation in word wrap to be allowed (2 - 25).
Hyphenation	Boolean	Read-write. Indicates whether to use hyphenation in word wrap.
HyphenationZone	Number (Double)	Read-write. The distance at the end of a line that will cause a word to break in unjustified type (0 - 720 pica).
HyphenLimit	Number (Long)	Read-write. The maximum number of consecutive lines that can end with a hyphenated word.
Justification	PsJustification	Read-write. The paragraph justification.
Kind	PsTextType	Read-write. The text-wrap type.
Language	PsLanguage	Read-write. The language to use.
Leading	Number (Double)	Read-write. The leading amount (unit value).
LeftIndent	Number (Double)	Read-write. The amount (unit value) of space to indent text from the left (-1296 - 1296).
Ligatures	Boolean	Read-write. Indicates whether to use ligatures.
MaximumGlyphScaling	Number (Double)	<p>Read-write. The maximum amount (percentage) to scale the horizontal size of the text letters (50 - 200; at 100, the width of characters is not scaled).</p> <p>Note: Valid only when <code>Justification =</code></p> <ul style="list-style-type: none"> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). <p>See Justification. The following values are also required: MinimumGlyphScaling and DesiredGlyphScaling.</p>

Property	Value Type	What it is (Continued)
<p>MaximumLetterScaling</p> <p>Note: 'Letter Scaling' is basically equivalent to 'Letter Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).</p>	<p>Number (Double)</p>	<p>Read-write. The maximum amount of space to allow between letters (100 - 500; at 0, no space is added between letters).</p> <p>Note: Valid only when <code>Justification =</code></p> <ul style="list-style-type: none"> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). <p>See Justification. The following values are also required: MaximumLetterScaling and DesiredLetterScaling.</p>
<p>MaximumWordScaling</p> <p>Note: 'Word Scaling' is basically equivalent to 'Word Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).</p>	<p>Number (Double)</p>	<p>Read-write. The maximum amount (percentage) of space to allow between words (0 - 1000; at 100, no additional space is added between words).</p> <p>Note: Valid only when <code>Justification =</code></p> <ul style="list-style-type: none"> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). <p>See Justification. The following values are also required: MaximumWordScaling and DesiredWordScaling.</p>
<p>MinimumGlyphScaling</p>	<p>Number (Double)</p>	<p>Read-write. The minimum amount (percentage) to scale the horizontal size of the text letters (50 - 200; at 100, the width of characters is not scaled).</p> <p>Note: Valid only when <code>Justification =</code></p> <ul style="list-style-type: none"> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). <p>See Justification. The following values are also required: MaximumGlyphScaling and DesiredGlyphScaling.</p>
<p>MinimumLetterScaling</p> <p>Note: 'Letter Scaling' is basically equivalent to 'Letter Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).</p>	<p>Number (Double)</p>	<p>Read-write. The minimum amount (percentage) of space between letters (100 - 500; at 0, no space is removed between letters).</p> <p>Note: Valid only when <code>Justification =</code></p> <ul style="list-style-type: none"> 4 (<code>psLeftJustified</code>); 5 (<code>psCenterJustified</code>); 6 (<code>psRightJustified</code>); or 7 (<code>psFullyJustified</code>). <p>See Justification. The following values are also required: MaximumLetterScaling and DesiredLetterScaling.</p>

Property	Value Type	What it is (Continued)
MinimumWordScaling Note: 'Word Scaling' is basically equivalent to 'Word Spacing' in the Adobe Photoshop CS5 application Justification dialog (Select Justification on the Paragraphs palette menu).	Number (Double)	Read-write. The minimum amount (percentage) of space between words (0 -1000; at 100, no space is removed between words). Note: Valid only when <code>Justification = 4 (psLeftJustified); 5 (psCenterJustified); 6 (psRightJustified); or 7 (psFullyJustified)</code> . See Justification . The following values are also required: MaximumWordScaling and DesiredWordScaling .
NoBreak	Boolean	Read-write. Indicates whether to allow words to break at the end of a line. Tip: When enacted on large amounts of consecutive characters, <code>noBreak = true</code> can prevent word wrap and thus may prevent some text from appearing on the screen.
OldStyle	Boolean	Read-write. Indicates whether to use old style type.
Parent	Object (ArtLayer)	Read-write. The <code>TextItem</code> object's container.
Position	Array of Number (Double)	Read-write. The position of origin for the text. The array must contain two values (unit value). Tip: Setting the <code>Position</code> property is basically equivalent to clicking the text tool at a point in the document to create the point of origin for text.
RightIndent	Number (Double)	Read-write. The amount of space (unit value) to indent text from the right (-1296 - 1296).
Size	Number (Double)	Read-write. The font size (unit value).
SpaceAfter	Number (Double)	Read-write. The amount of space (unit value) to use after each paragraph (-1296 - 1296).
SpaceBefore	Number (Double)	Read-write. The amount of space (unit value) to use before each paragraph (-1296 - 1296).
StrikeThru	PsStrikeThruType	Read-write. The text strike through option to use.
TextComposer	PsTextComposer	Read-write. The composition method to use to evaluate line breaks and optimize the specified hyphenation and Justification options. Note: Valid only when <code>Kind = 2 (psParagraphText)</code> . See Kind .

Property	Value Type	What it is (Continued)
Tracking	Number (Double)	Read-write. The amount of uniform spacing between multiple characters (-1000 - 10000). Note: Tracking units are 1/1000 of an em space. The width of an em space is relative to the current type size. In a 1-point font, 1 em equals 1 point; in a 10-point font, 1 em equals 10 points. So, for example, 100 units in a 10-point font are equivalent to 1 point.
typename	String	Read-only. The class name of the referenced <code>TextItem</code> object.
Underline	PsUnderlineType	Read-write. The text underlining options.
UseAutoLeading	Boolean	Read-write. Indicates whether to use a font's built-in leading information.
VerticalScale	Number (Long)	Read-write. Character scaling (vertical) in proportion to horizontal scale (0 - 1000 in percent). See HorizontalScale .
WarpBend	Number (Double)	Read-write. The warp bend percentage (-100 - 100).
WarpDirection	PsDirection	Read-write. The warp direction.
WarpHorizontalDistortion	Number (Double)	Read-write. The horizontal distortion (as percentage) of the warp (-100 - 100).
WarpStyle	PsWarpStyle	Read-write. The style of warp to use.
WarpVerticalDistortion	Number (Double)	Read-write. The vertical distortion (as percentage) of the warp (-100 - 100).
Width	Number (Double)	Read-write. The width of the bounding box (unit value) for paragraph text. Note: Valid only when <code>Kind = 2</code> (<code>psParagraphText</code>). See Kind .

Methods

Method	Parameter Type	Returns	What it does
ConvertToShape ()			Converts the text item and its containing layer to a fill layer with the text changed to a clipping path.
CreatePath ()			Creates a clipping path from the outlines of the actual text items (such as letters or words).

TiffSaveOptions

Options that can be specified when saving a document in TIFF format.

Properties

Property	Value Type	What it is
AlphaChannels	Boolean	Read-write. Indicates whether to save the alpha channels.
Annotations	Boolean	Read-write. Indicates whether to save the annotations.
Application	Object (Application)	Read-only. The application that the object belongs to.
ByteOrder	PsByteOrder	Read-write. The order in which the document's bytes will be read. The default is 2 (<code>psMacOSByteOrder</code>) when running on Mac OS and 1 (<code>psIBMByteOrder</code>) when running on a PC.
EmbedColorProfile	Boolean	Read-write. Indicates whether to embed the color profile in the document.
ImageCompression	PsTIFFEncodingType	Read-write. The compression type. Default: 1 (<code>psNoTIFFCompression</code>).
InterleaveChannels	Boolean	Read-write. Indicates whether the channels in the image will be interleaved.
JPEGQuality	Number (Long)	Read-write. The quality of the produced image (0-12), which is inversely proportionate to the amount of JPEG compression. Note: Valid only when <code>ImageCompression = 3</code> (<code>psTiffJPEG</code>).
LayerCompression	PsLayerCompressionType	Read-write. The method of compression to use when saving layers (as opposed to saving composite data). Note: Valid only when <code>Layers = true</code> . See Layers
Layers	Boolean	Read-write. Indicates whether to save the layers.
SaveImagePyramid	Boolean	Read-write. Indicates whether to preserve multiresolution information. Default: <code>false</code> .
SpotColors	Boolean	Read-write. Indicates whether to save the spot colors.

Property	Value Type	What it is (Continued)
Transparency	Boolean	Read-write. Indicates whether to save the transparency as an additional alpha channel when the file is opened in another application.
typename	String	Read-only. The class name of the referenced <code>TIFFSaveOptions</code> object.

XMPMetadata

Camera raw image file settings stored in an XMP file in the same folder as the raw file with the same base name and an XMP extension.

Properties

Property	Value Type	What it is
Application	Object (Application)	Read-only. The application that the object belongs to.
Parent	Object (Document)	Read-only. The object's container.
RawData	String	Read-write. The raw XML form of file information.
typename	String	Read-only. The class name of the referenced XMPMetadata object.

3

Scripting Constants

This section lists and describes the enumerations defined for use with Adobe Photoshop CS5 VBScript properties and methods.

Constant type	Values	What it means
PsAdjustmentReference	1 (psRelative) 2 (psAbsolute)	Method to use for interpreting selective color adjustment specifications: 1 = % of the existing color amount; 2 = % of the whole.
PsAnchorPosition	1 (psTopLeft) 2 (psTopCenter) 3 (psTopRight) 4 (psMiddleLeft) 5 (psMiddleCenter) 6 (psMiddleRight) 7 (psBottomLeft) 8 (psBottomCenter) 9 (psBottomRight)	The point on the object that does not move when the object is rotated or resized.
PsAntiAlias	1 (psNoAntialias) 2 (psSharp) 3 (psCrisp) 4 (psStrong) 5 (psSmooth)	Method to use to smooth edges by softening the color transition between edge pixels and background pixels.
PsAutoKernType	1 (psManual) 2 (psMetrics) 3 (psOptical)	The type of kerning to use for characters.
PsBatchDestinationType	1 (psNoDestination) 2 (psSaveAndClose) 3 (psFolder)	The destination, if any, for batch-processed files: 1: Leave all files open; 2: Save changes and close the files; 3: Save modified versions of the files to a new location (leaving the originals unchanged).
PsBitmapConversionType	1 (psHalfThreshold) 2 (psPatternDither) 3 (psDiffusionDither) 4 (psHalftoneScreen) 5 (psCustomPattern)	Specifies the quality of an image you are converting to bitmap mode.
PsBitmapHalftoneType	1 (psHalftoneRound) 2 (psHalftoneDiamond) 3 (psHalftoneEllipse) 4 (psHalftoneLine) 5 (psHalftoneSquare) 6 (psHalftoneCross)	Specifies the shape of the dots (ink deposits) in the halftone screen.
PsBitsPerChannelType	1 (psDocument1Bit) 8 (psDocument8Bits) 16 (psDocument16Bits) 32 (psDocument32Bits)	The number of bits per color channel.

Constant type	Values	What it means
PsBlendMode	1 (psPassThrough) 2 (psNormalBlend) 3 (psDissolve) 4 (psDarken) 5 (psMultiply) 6 (psColorBurn) 7 (psLinearBurn) 8 (psLighten) 9 (psScreen) 10 (psColorDodge) 11 (psLinearDodge) 12 (psOverlay) 13 (psSoftLight) 14 (psHardLight) 15 (psVividLight) 16 (psLinearLight) 17 (psPinLight) 18 (psDifference) 19 (psExclusion) 20 (psHue) 21 (psSaturationBlend) 22 (psColorBlend) 23 (psLuminosity) 26 (psHardMix) 27 (psLighterColor) 28 (psDarkerColor) 29 (psSubtract) 30 (psDivide)	Controls how pixels in the image are blended.
PsBMPDepthType	1 (psBMP1Bit) 4 (psBMP4Bits) 8 (psBMP8Bits) 16 (psBMP16Bits) 24 (psBMP24Bits) 32 (psBMP32Bits) 60 (psBMP_X1R5G5B5) 61 (psBMP_A1R5G5B5) 62 (psBMP_R5G6B5) 63 (psBMP_X4R4G4B4) 64 (psBMP_A4R4G4B4) 65 (psBMP_R8G8B8) 66 (psBMP_X8R8G8B8) 67 (psBMP_A8R8G8B8)	The number of bits per channel (also called pixel depth or color depth). The number selected indicates the exponent of 2. For example, a pixel with a bit-depth of 8 has 2 ⁸ , or 256, possible color values.
PsByteOrder	1 (psIBMByteOrder) 2 (psMacOSByteOrder)	The order in which bytes will be read.
PsCameraRAWSettingsType	0 (psCameraDefault) 1 (psSelectedImage) 2 (psCustomSettings)	The default CameraRAW settings to use: the camera settings, custom settings, or the settings of the selected image.
PsCameraRAWSize	0 (psMinimumCameraRAW) 1 (psSmallCameraRAW) 2 (psMediumCameraRAW) 3 (psLargeCameraRAW) 4 (psExtraLargeCameraRAW) 5 (psMaximumCameraRAW)	The camera RAW size type options: 0 = 1536 x 1024 1 = 2048 x 1365 2 = 3072 x 2048 3 = 4096 x 2731 4 = 5120 x 4096 5 = 6144 x 4096

Constant type	Values	What it means
PsCase	1 (psNormalCase) 2 (psAllCaps) 3 (psSmallCaps)	The case usage for type.
PsChangeMode	1 (psConvertToGrayscale) 2 (psConvertToRGB) 3 (psConvertToCMYK) 4 (psConvertToLab) 5 (psConvertToBitmap) 6 (psConvertToIndexedColor) 7 (psConvertToMultiChannel)	The type of color mode to use. Note: Color images must be changed to grayscale (1) mode before you can change them to bitmap (5) mode.
PsChannelType	1 (psComponentChannel) 2 (psMaskedAreaAlphaChannel) 3 (psSelectedAreaAlphaChannel) 4 (psSpotColorChannel)	The type of channel: 1: related to document color mode; 2: Alpha channel where color indicates masked area; 3: Alpha channel where color indicates selected area; 4: channel that contains spot colors.
PsColorBlendMode	2 (psNormalBlendColor) 3 (psDissolveBlend) 4 (psDarkenBlend) 5 (psMultiplyBlend) 6 (psColorBurnBlend) 7 (psLinearBurnBlend) 8 (psLightenBlend) 9 (psScreenBlend) 10 (psColorDodgeBlend) 11 (psLinearDodgeBlend) 12 (psOverlayBlend) 13 (psSoftLightBlend) 14 (psHardLightBlend) 15 (psVividLightBlend) 16 (psLinearLightBlend) 17 (psPinLightBlend) 18 (psDifferenceBlend) 19 (psExclusionBlend) 20 (psHueBlend) 21 (psSaturationBlendColor) 22 (psColorBlendMode) 23 (psLuminosityBlend) 24 (psBehindBlend) 25 (psClearBlend) 26 (psHardMixBlend) 27 (psSubtract) 28 (psDivide)	Controls how pixels in the image are blended.
PsColorModel	1 (psGrayscaleModel) 2 (psRGBModel) 3 (psCMYKModel) 4 (psLabModel) 5 (psHSBModel) 50 (psNoModel)	The color model to use.
PsColorPicker	1 (psAdobeColorPicker) 2 (psAppleColorPicker) 3 (psWindowsColorPicker) 4 (psPlugInColorPicker)	The color picker to use.
PsColorProfileType	1 (psNo) 2 (psWorking) 3 (psCustom)	The color profile type to use to manage this document.

Constant type	Values	What it means
PsColorReductionType	0 (psPerceptualReduction) 1 (psSelective) 2 (psAdaptive) 3 (psRestrictive) 4 (psCustomReduction) 5 (psBlackWhiteReduction) 6 (psSFWGrayscale) 7 (psMacintoshColors) 8 (psWindowsColors)	The color reduction algorithm option to use.
PsColorSpaceType	0 (psAdobeRGB) 1 (psColorMatchRGB) 2 (psProPhotoRGB) 3 (psSRGB)	The type of color space to use.
PsCopyrightedType	1 (psCopyrightedWork) 2 (psPublicDomain) 3 (psUnmarked)	The copyright status of the document.
PsCreateFields	1 (psDuplication) 2 (psInterpolation)	The method to use for creating fields.
PsCropToType	0 (psBoundingBox) 1 (psMediaBox) 2 (psCropBox) 3 (psBleedBox) 4 (psTrimBox) 5 (psArtBox)	The style to use when cropping a page.
PsDCSType	1 (psNoComposite) 2 (psGrayscaleComposite) 3 (psColorComposite)	The DCS format to use: 1: Does not create a composite file; 2: Creates a grayscale composite file in addition to DCS files; 3: Creates a color composite file in addition to DCS files.
PsDepthMapSource	1 (psNoSource) 2 (psTransparencyChannel) 3 (psLayerMask) 4 (psImageHighlight)	What to use for the depth map.
PsDescValueType	1 (psIntegerType) 2 (psDoubleType) 3 (psUnitDoubleType) 4 (psStringType) 5 (psBooleanType) 6 (psListType) 7 (psObjectType) 8 (psEnumeratedType) 9 (psReferenceType) 10 (psClassType) 11 (psAliasType) 12 (psRawType)	The value type of an object.
PsDialogModes	1 (psDisplayAllDialogs) 2 (psDisplayErrorDialogs) 3 (psDisplayNoDialogs)	Controls the type (mode) of dialogs Photoshop displays when running scripts.
PsDirection	1 (psHorizontal) 2 (psVertical)	The orientation of the object.

Constant type	Values	What it means
PsDisplacementMapType	1 (psStretchToFit) 2 (psTile)	Describes how the displacement map fits the image if the image is not the same size as the map.
PsDitherType	1 (psNoDither) 2 (psDiffusion) 3 (psPattern) 4 (psNoise)	The default type of dithering to use.
PsDocumentFill	1 (psWhite) 2 (psBackgroundColor) 3 (psTransparent)	The fill of the document.
PsDocumentMode	1 (psGrayscale) 2 (psRGB) 3 (psCMYK) 4 (psLab) 5 (psBitmap) 6 (psIndexedColor) 7 (psMultiChannel) 8 (psDuotone)	The color mode of the open document.
PsEditLogItemsType	1 (psSessionOnly) 2 (psConcise) 3 (psDetailed)	The history log edit options: 1: Save history log only for the session; 2: Save a concise history log; 3: Save a detailed history log.
PsElementPlacement	0 (psPlaceInside) 1 (psPlaceAtBeginning) 2 (psPlaceAtEnd) 3 (psPlaceBefore) 4 (psPlaceAfter)	The object's position in the Layers palette. Note: Not all values are valid for all object types. Please refer to the object property definition in VBScript Interface to make sure you are using a valid value.
PsEliminateFields	1 (psOddFields) 2 (psEvenFields)	The type of fields to eliminate.
PsExportType	1 (psIllustratorPaths) 2 (psSaveForWeb)	The export options to use.
PsExtensionType	2 (psLowercase) 3 (psUppercase)	The formatting of the extension in the filename.

Constant type	Values	What it means
PsFileNamingType	1 (psDocumentNameMixed) 2 (psDocumentNameLower) 3 (psDocumentNameUpper) 4 (psSerialNumber1) 5 (psSerialNumber2) 6 (psSerialNumber3) 7 (psSerialNumber4) 8 (psSerialLetterLower) 9 (psSerialLetterUpper) 10 (psMmddy) 11 (psMmdd) 12 (psYyyymmdd) 13 (psYymmdd) 14 (psYyddmm) 15 (psDdmmyy) 16 (psDdmm) 17 (psExtensionLower) 18 (psExtensionUpper)	File naming options for the batch command.
psFontPreviewType	0 (psFontPreviewNone) 1 (psFontPreviewSmall) 2 (psFontPreviewMedium) 3 (psFontPreviewLarge)	The type size to use for font previews in the type tool font menus.
PsForcedColors	1 (psNoForced) 2 (psBlackWhite) 3 (psPrimaries) 4 (psWeb)	The type of colors to be forced (included) into the color table: 2: Pure black and pure white; 3: Red, green, blue, cyan, magenta, yellow, black, and white; 4: the 216 web-safe colors.
PsFormatOptionsType	1 (psStandardBaseline) 2 (psOptimizedBaseline) 3 (psProgressive)	The option with which to save a JPEG file: 1: Format recognized by most web browsers; 2: Optimized color and a slightly reduced file size; 3: Displays a series of increasingly detailed scans as the image downloads.
PsGalleryConstrainType	1 (psConstrainWidth) 2 (psConstrainHeight) 3 (psConstrainBoth)	The type of proportions to constrain for images.
PsGalleryFontType	1 (psArial) 2 (psCourierNew) 3 (psHelvetica) 4 (psTimesNewRoman)	The fonts to use for the Web photo gallery captions and other text.
PsGallerySecurityTextPositionType	1 (psCentered) 2 (psUpperLeft) 3 (psLowerLeft) 4 (psUpperRight) 5 (psLowerRight)	The position of the text displayed over gallery images as an antitheft deterrent.
PsGallerySecurityTextRotateType	1 (psZero) 2 (psClockwise45) 3 (psClockwise90) 4 (psCounterClockwise45) 5 (psCounterClockwise90)	The orientation of the text displayed over gallery images as an antitheft deterrent.

Constant type	Values	What it means
PsGallerySecurityType	1 (psNoSecurity) 2 (psCustomSecurityText) 3 (psFilename) 4 (psCopyright) 5 (psCaption) 6 (psCredit) 7 (psTitle)	The content to use for text displayed over gallery images as an antitheft deterrent. Note: All types draw from the image's file information except 2.
PsGalleryThumbSizeType	1 (psSmall) 2 (psMedium) 3 (psLarge) 4 (psCustomThumbnail)	The size of thumbnail images in the web photo gallery.
PsGeometry	0 (psTriangle) 1 (psPentagon) 2 (psHexagon) 3 (psSquareGeometry) 4 (psHeptagon) 5 (psOctagon)	Geometric options for shapes, such as the iris shape in the Lens Blur Filter.
PsGridLineStyle	1 (psGridSolidLine) 2 (psGridDashedLine) 3 (psGridDottedLine)	The line style for the nonprinting grid displayed over images.
PsGridSize	1 (psNoGrid) 2 (psSmallGrid) 3 (psMediumGrid) 4 (psLargeGrid)	The value of grid line spacing.
PsGuideLineStyle	1 (psGuideSolidLine) 2 (psGuideDashedLine)	The line style for nonprinting guides displayed over images.
PsIllustratorPathType	1 (psDocumentBounds) 2 (psAllPaths) 3 (psNamedPath)	The paths to export.
PsIntent	1 (psPerceptual) 2 (psSaturation) 3 (psRelativeColorimetric) 4 (psAbsoluteColorimetric)	The rendering intent to use when converting from one color space to another.
PsJavaScriptExecutionMode	1 (psNeverShowDebugger) 2 (psDebuggerOnError) 3 (psBeforeRunning)	The debugging behavior to use when executing a JavaScript.
PsJustification	1 (psLeft) 2 (psCenter) 3 (psRight) 4 (psLeftJustified) 5 (psCenterJustified) 6 (psRightJustified) 7 (psFullyJustified)	The placement of paragraph text within the bounding box.

Constant type	Values	What it means
PsLanguage	1 (psEnglishUSA) 2 (psEnglishUK) 3 (psFrench) 4 (psCanadianFrench) 5 (psFinnish) 6 (psGerman) 7 (psOldGerman) 8 (psSwissGerman) 9 (psItalian) 10 (psNorwegian) 11 (psNynorskNorwegian) 12 (psPortuguese) 13 (psBrazilianPortuguese) 14 (psSpanish) 15 (psSwedish) 16 (psDutch) 17 (psDanish)	The language to use.
PsLayerCompressionType	1 (psRLELayerCompression) 2 (psZIPLayerCompression)	Compression methods for data for pixels in layers.
PsLayerKind	1 (psNormalLayer) 2 (psTextLayer) 3 (psSolidFillLayer) 4 (psGradientFillLayer) 5 (psPatternfillLayer) 6 (psLevelsLayer) 7 (psCurvesLayer) 8 (psColorBalanceLayer) 9 (psBrightnessContrastLayer) 10 (psHueSaturationLayer) 11 (psSelectiveColorLayer) 12 (psChannelMixerLayer) 13 (psGradientMapLayer) 14 (psInversionLayer) 15 (psThresholdLayer) 16 (psPosterizeLayer) 17 (psSmartObjectLayer) 18 (psPhotoFilterLayer) 19 (psExposureLayer) 20 (psLayer3D) 21 (psVideoLayer) 22 (psBlackAndWhiteLayer) 23 (psVibrance)	The kind of ArtLayer object.
PsLayerType	1 (psArtLayer) 2 (psLayerSet)	The kind of layer object.
PsLensType	1 (psZoomLens) 2 (psPrime35) 3 (psPrime105) 5 (psMoviePrime)	The type of lens to use.
PsMagnificationType	0 (psActualSize) 1 (psFitPage)	The type of magnification to use when viewing an image.

Constant type	Values	What it means
PsMatteType	1 (psNoMatte) 2 (psForegroundColorMatte) 3 (psBackgroundColorMatte) 4 (psWhiteMatte) 5 (psBlackMatte) 6 (psSemiGray) 7 (psNetscapeGrayMatte)	The color to use for matting.
PsMeasurementRange	1 (psAllMeasurements) 2 (psActiveMeasurements)	The measurement to take action upon
PsMeasurementSource	1 (psMeasureSelection) 2 (psMeasureCountTool) 3 (psMeasureRulerTool)	The source for recording measurements
PsNewDocumentMode	1 (psNewGray) 2 (psNewRGB) 3 (psNewCMYK) 4 (psNewLab) 5 (psNewBitmap)	The color profile to use for the document.
PsNoiseDistribution	1 (psUniformNoise) 2 (psGaussianNoise)	Distribution method to use when applying an Add Noise filter.
PsOffsetUndefinedAreas	1 (psOffsetSetToLayerFill) 2 (psOffsetWraparound) 3 (psOffsetRepeatEdgePixels)	Method to use to fill the empty space left by offsetting a an image or selection.
PsOpenDocumentMode	1 (psOpenGray) 2 (psOpenRGB) 3 (psOpenCMYK) 4 (psOpenLab)	The color profile to use.

Constant type	Values	What it means
PsOpenDocumentType	1 (psPhotoshopOpen) 2 (psBMPOpen) 3 (psCompuServeGIFOpen) 4 (psPhotoshopEPSOpen) 5 (psFilmstripOpen) 6 (psJPEGOpen) 7 (psPCXOpen) 8 (psPhotoshopPDFOpen) 9 (psPhotoCDOpen) 10 (psPICTFileFormatOpen) 11 (psPICTResourceFormatOpen) 12 (psPixarOpen) 13 (psPNGOpen) 14 (psRawOpen) 15 (psScitexCTOpen) 16 (psTargaOpen) 17 (psTIFFOpen) 18 (psPhotoshopDCS_1Open) 19 (psPhotoshopDCS_2Open) 21 (psPDFOpen) 22 (psEPSOpen) 23 (psEPSPICTPreviewOpen) 24 (psEPSTIFFPreviewOpen) 25 (psAliasPIXOpen) 26 (psElectricImageOpen) 27 (psPortableBitmapOpen) 28 (psWavefrontRLAOpen) 29 (psSGIRGBOpen) 30 (psSoftImageOpen) 31 (psWirelessBitmapOpen) 32 (psCameraRAWOpen) 33 (psDICOMOpen)	The format in which to open a document. Note: psPhotoCDOpen (8) is deprecated. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD. Note: The psDICOMOpen (33) option is for the Extended version only.
PsOperatingSystem	1 (psOS2) 2 (psWindows)	The operating system.
PsOrientation	1 (psLandscape) 2 (psPortrait)	The page orientation.
PsOtherPaintingCursors	1 (psStandardOther) 2 (psPreciseOther)	The pointer for the following tools: Eraser, Pencil, Paintbrush, Healing Brush, Rubber Stamp, Pattern Stamp, Smudge, Blur, Sharpen, Dodge, Burn, Sponge.
PsPaintingCursors	1 (psStandard) 2 (psPrecise) 3 (psBrushsize)	The pointer for the following tools: Marquee, Lasso, Polygonal Lasso, Magic Wand, Crop, Slice, Patch Eyedropper, Pen, Gradient, Line, Paint Bucket, Magnetic Lasso, Magnetic Pen, Freeform Pen, Measure, Color Sampler.

Constant type	Values	What it means
PsPaletteType	1 (psExact) 2 (psMacOSPalette) 3 (psWindowsPalette) 4 (psWebPalette) 5 (psUniform) 6 (psLocalPerceptual) 7 (psLocalSelective) 8 (psLocalAdaptive) 9 (psMasterPerceptual) 10 (psMasterSelective) 11 (psMasterAdaptive) 12 (psPreviousPalette)	The palette type to use.
PsPathKind	1 (psNormalPath) 2 (psClippingPath) 3 (psWorkPath) 4 (psVectorMask) 5 (psTextMask)	The type of path.
PsPDFCompatibilityType	1 (psPDF13) 2 (psPDF14) 3 (psPDF15) 4 (psPDF16)	The PDF version to make the document compatible with.
PsPDFEncoding	0 (psPDFNone) 1 (psPDFZip) 2 (psPDFJPEG) 3 (psPDFPDFZip4Bit) 4 (psPDFJPEGHIGH) 5 (psPDFJPEGMEDHIGH) 6 (psPDFJPEGMED) 7 (psPDFJPEGMEDLOW) 8 (psPDFJPEGLow) 9 (psPDFJPEG2000High) 10 (psPDFJPEG2000MEDHIGH) 11 (psPDFJPEG2000MED) 12 (psPDFJPEG2000MEDLOW) 13 (psPDFJPEG2000LOW) 14 (psPDFJPEG2000LOSSLESS)	Encoding and compression options to use when saving a document in PDF format.
PsPDFResampleType	0 (psNoResample) 1 (psPDFAverage) 2 (psPDFSubSample) 3 (psPDFBicubic)	The down sample method to use.
PsPDFStandardType	0 (psNoStandard) 1 (psPDFX1A2001) 2 (psPDFX1A2003) 3 (psPDFX32002) 4 (psPDFX32003)	The PDF standard to make the document compatible with.
PsPhotoCDCColorSpace	1 (psRGB8) 2 (psRGB16) 3 (psLab8) 4 (psLab16)	The color space to use when creating a Photo CD. Note: Deprecated for Adobe Photoshop CS5. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.

Constant type	Values	What it means
PsPhotoCDSize	1 (psMinimumPhotoCD) 2 (psSmallPhotoCD) 3 (psMediumPhotoCD) 4 (psLargePhotoCD) 5 (psExtralargePhotoCD) 6 (psMaximumPhotoCD)	The pixel dimensions of the image. psMinimumPhotoCD = 64x96 psSmallPhotoCD = 128x192 psMediumPhotoCD = 256x384 psLargePhotoCD = 512x768 psExtralargePhotoCD = 1024x1536 psMaximumPhotoCD = 2048x3072 Note: Deprecated for Adobe Photoshop CS5. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.
PsPICTBitsPerPixels	2 (psPICTTwoBits) 4 (psPICTFourBits) 8 (psPICTEightBits) 16 (psPICTSixteenBits) 32 (psPICTThirtyTwoBits)	The number of bits per pixel to use when compression a PICT file. Note: Use 16 or 32 for RGB images; use 2, 4, or 8 for bitmap and grayscale images.
PsPICTCompression	1 (psNoPICTCompression) 2 (psJPEGLowPICT) 4 (psJPEGMediumPICT) 5 (psJPEGHighPICT) 6 (psJPEGMaximumPICT)	The type of compression to use when saving an image as a PICT file.
PsPicturePackageTextType	1 (psNoText) 2 (psUserText) 3 (psFilenameText) 4 (psCopyrightText) 5 (psCaptionText) 6 (psCreditText) 7 (psOriginText)	The function or meaning of text in a Picture Package.
PsPointKind	1 (psSmoothPoint) 2 (psCornerPoint)	The role a PathPoint plays in a PathItem .
PsPointType	1 (psPostScriptPoints) 2 (psTraditionalPoints)	The kind of measurement to use for type points: 1 = 72 points/inch; 2 = 72.27 points/inch.
PsPolarConversionType	1 (psRectangularToPolar) 2 (psPolarToRectangular)	The method of polar distortion to use.
PsPreviewType	1 (psNoPreview) 2 (psMonochromeTIFF) 3 (psEightbitTIFF)	The type of image to use as a low-resolution preview in the destination application.
PsPurgeTarget	1 (psUndoCaches) 2 (psHistoryCaches) 3 (psClipboardCache) 4 (psAllCaches)	Cache to be targeted in a purge operation.
PsQueryStateType	1 (psAlways) 2 (psAsk) 3 (psNever)	Permission state for queries.

Constant type	Values	What it means
PsRadialBlurMethod	1 (psSpin) 2 (psZoom)	The blur method to use.
PsRadialBlurQuality	1 (psRadialBlurDraft) 2 (psRadialBlurGood) 3 (psRadialBlurBest)	The smoothness or graininess of the blurred image.
PsRasterizeType	1 (psTextContents) 2 (psShape) 3 (psFillContent) 4 (psLayerClippingPath) 5 (psEntireLayer) 6 (psLinkedLayers)	The layer element to rasterize.
PsReferenceFormType	1 (psReferenceNameType) 2 (psReferenceIndexType) 3 (psReferenceIdentifierType) 4 (psReferenceOffsetType) 5 (psReferenceEnumeratedType) 6 (psReferencePropertyType) 7 (psReferenceClassType)	The type of an ActionReference object.
PsResampleMethod	1 (psNoResampling) 2 (psNearestNeighbor) 3 (psBilinear) 4 (psBicubic) 5 (psBicubicSharper) 6 (psBicubicSmoother)	The method to use for image interpolation.
PsRippleSize	1 (psSmallRipple) 2 (psMediumRipple) 3 (psLargeRipple)	The undulation size to use.
PsSaveBehavior	1 (psNeverSave) 2 (psAlwaysSave) 3 (psAskWhenSaving)	The application's behavior when a Save method is called.
PsSaveDocumentType	1 (psPhotoshopSave) 2 (psBMPSave) 3 (psCompuServeGIFSave) 4 (psPhotoshopEPSSave) 6 (psJPEGSave) 7 (psPCXSave) 8 (psPhotoshopPDFSave) 10 (psPICTFileFormatSave) 12 (psPixarSave) 13 (psPNGSave) 14 (psRawSave) 15 (psScitexCTSave) 16 (psTargaSave) 17 (psTIFFSave) 18 (psPhotoshopDCS_1Save) 19 (psPhotoshopDCS_2Save) 25 (psAliasPIXSave) 26 (psElectricImageSave) 27 (psPortableBitmapSave) 28 (psWavefrontRLASave) 29 (psSGIRGBSave) 30 (psSoftImageSave) 31 (psWirelessBitmapSave) 1	The format in which to save a document.

Constant type	Values	What it means
PsSaveEncoding	1 (psBinary) 2 (psJPEGLow) 3 (psAscii) 4 (psJPEGMedium) 5 (psJPEGHigh) 6 (psJPEGMaximum)	The type of encoding to use when saving a file.
PsSaveLogItemsType	1 (psMetadata) 2 (psLogFile) 3 (psLogFileAndMetadata)	The location of history log data.
PsSaveOptions	1 (psSaveChanges) 2 (psDoNotSaveChanges) 3 (psPromptToSaveChanges)	The save options to use when the <code>Close</code> method is called to close a document.
PsSelectionType	1 (psReplaceSelection) 2 (psExtendSelection) 3 (psDiminishSelection) 4 (psIntersectSelection)	The selection behavior when a selection already exists: 1: Replace the selected area; 2: Add the selection to an already selected area; 3: Remove the selection from the already selected area; 4: Make the selection only the area where the new selection intersects the already selected area.
PsShapeOperation	1 (psShapeAdd) 2 (psShapeXOR) 3 (psShapeIntersect) 4 (psShapeSubtract)	A <code>subPathItem</code> object's behavior when it intersects another <code>subPathItem</code> object.
PsSmartBlurMode	1 (psSmartBlurNormal) 2 (psSmartBlurEdgeOnly) 3 (psSmartBlurOverlayEdge)	The method to use for smart blurring: 1 : Apply blur to entire image; 2, 3 : Apply blur only to edges of color transitions.
PsSmartBlurQuality	1 (psSmartBlurLow) 2 (psSmartBlurMedium) 3 (psSmartBlurHigh)	The blur quality to use.
PsSourceSpaceType	1 (psDocumentSpace) 2 (psProofSpace)	The color space for source when printing.
PsSpherizeMode	1 (psNormalSpherize) 2 (psHorizontalSpherize) 3 (psVerticalSpherize)	The curve (or stretch shape) to use for the distortion.
PsStrikeThruType	1 (psStrikeOff) 2 (psStrikeHeight) 3 (psStrikeBox)	The style of strikethrough to use.
PsStrokeLocation	1 (psInsideStroke) 2 (psCenterStroke) 3 (psOutsideStroke)	The placement of path or selection boundary strokes.
PsTargaBitsPerPixels	16 (psTarga16Bits) 24 (psTarga24Bits) 32 (psTarga32Bits)	The resolution to use when saving an image in Targa format.

Constant type	Values	What it means
PsTextComposer	1 (psAdobeSingleLine) 2 (psAdobeEveryLine)	The composition method to use to optimize the specified hyphenation and justification options.
PsTextType	1 (psPointText) 2 (psParagraphText)	The type of text: 1: Text that does not wrap; 2: Text that wraps within a bounding box.
PsTextureType	1 (psBlocksTexture) 2 (psCanvasTexture) 3 (psFrostedTexture) 4 (psTinyLensTexture) 5 (psTextureFile)	The type of texture or glass surface image to load for a texturizer or glass filter.
PsTIFFEncodingType	1 (psNoTIFFCompression) 2 (psTiffLZW) 3 (psTiffJPEG) 4 (psTiffZIP)	The encoding to use for TIFF files.
PsToolType	1 (psPencil) 2 (psBrush) 3 (psEraser) 4 (psBackgroundEraser) 5 (psCloneStamp) 6 (psPatternStamp) 7 (psHealingBrush) 8 (psHistoryBrush) 9 (psArtHistoryBrush) 10 (psSmudge) 11 (psBlur) 12 (psSharpen) 13 (psDodge) 14 (psBurn) 15 (psSponge) 16 (psColorReplacementTool)	The tool selection.
PsTransitionType	1 (psBlindsHorizontal) 2 (psBlindsVertical) 3 (psDissolveTransition) 4 (psBoxIn) 5 (psBoxOut) 6 (psGlitterDown) 7 (psGlitterRight) 8 (psGlitterRightDown) 9 (psNoTransition) 10 (psRandom) 11 (psSplitHorizontalIn) 12 (psSplitHorizontalOut) 13 (psSplitVerticalIn) 14 (psSplitVerticalOut) 15 (psWipeDown) 16 (psWipeLeft) 17 (psWipeRight) 18 (psWipeUp)	The method to use to transition from one image to the next in a PDF presentation.
PsTrimType	0 (psTransparentPixels) 1 (psTopLeftPixel) 9 (psBottomRightPixel)	Type of pixels to trim around an image: 9 = bottom right pixel color; 1 = top left pixel color.
PsTypeUnits	1 (psTypePixels) 4 (psTypeMM) 5 (psTypePoints)	The unit to use for measuring text characters.

Constant type	Values	What it means
PsUndefinedAreas	1 (psWrapAround) 2 (psRepeatEdgePixels)	The method to use to treat undistorted areas or areas left blank in an image to which the a filter in the Distort category has been applied.
PsUnderlineType	1 (psUnderlineOff) 2 (psUnderlineRight) 3 (psUnderlineLeft)	The placement of text underlining. Note: 3 and 2 are valid only when PsDirection = 2.
PsUnits	1 (psPixels) 2 (psInches) 3 (psCM) 4 (psMM) 5 (psPoints) 6 (psPicas) 7 (psPercent)	The measurement unit for type and ruler increments.
PsUrgency	0 (psNone) 1 (psLow) 2 (psTwo) 3 (psThree) 4 (psFour) 5 (psNormal) 6 (psSix) 7 (psSeven) 8 (psHigh)	The editorial urgency of the artwork.
PsWarpStyle	1 (psNone) 2 (psArc) 3 (psArcLower) 4 (psArcUpper) 5 (psArch) 6 (psBulge) 7 (psShellLower) 8 (psShellUpper) 9 (psFlag) 10 (psWave) 11 (psFish) 12 (psRise) 13 (psFishEye) 14 (psInflate) 15 (psSqueeze) 16 (psTwist)	The warp style to use.
PsWaveType	1 (psSine) 2 (psTriangular) 3 (psSquare)	The type of wave to use.
PsWhiteBalanceType	0 (psAsShot) 1 (psAuto) 2 (psDaylight) 3 (psCloudy) 4 (psShade) 5 (psTungsten) 6 (psFluorescent) 7 (psFlash) 8 (psCustomCameraSettings)	The lighting conditions to use (affects color balance).
PsZigZagType	1 (psAroundCenter) 2 (psOutFromCenter) 3 (psPondRipples)	The method of zigzagging to use.

Appendix A: Event ID Codes

The following table lists events and their four-character ID codes or string identifiers for use with the `Notifier` object.

Note: Do not include single quotes (') with four-character IDs in your code. The single quotes are used in this table to illustrate the placement of required spaces in codes that do not contain four letters. However, string identifiers, which are longer than four characters, require double quotes in the code.

Tip: If you can't find the event you want to use for notification in this table, you can use `ScriptListener` to determine the event ID code. See the `ScriptListener` documentation in the Action Manager chapter of the *Photoshop CS5 Scripting Guide*.

Event	4-char ID or String
3DTransform	'TdT '
Average	'Avrg'
ApplyStyle	'ASty'
Assert	'Asrt '
AccentedEdges	'AccE'
Add	'Add '
AddNoise	'AdNs '
AddTo	'AddT'
Align	'Algn'
All	'All '
AngledStrokes	'AngS'
ApplyImage	'AppI'
BasRelief	'BsRl '
Batch	'Btch'
BatchFromDroplet	'BtcF'
Blur	'Blr '
BlurMore	'BlrM'
Border	'Brdr'
Brightness	'BrgC'
CanvasSize	'CnvS'
ChalkCharcoal	'ChlC'
ChannelMixer	'ChnM'

Event	4-char ID or String
Charcoal	'Chrc'
Chrome	'Chrm'
Clear	'Cler'
Close	'Cls '
Clouds	'Clds'
ColorBalance	'ClrB'
ColorHalftone	'ClrH'
ColorRange	'ClrR'
ColoredPencil	'ClrP'
ContactSheet	"0B71D221-F8CE-11d2-B21B-0008C75B322C"
ConteCrayon	'CntC'
Contract	'Cntc'
ConvertMode	'CnvM'
Copy	'copy'
CopyEffects	'CpFX'
CopyMerged	'CpyM'
CopyToLayer	'CpTL'
Craquelure	'Crql'
CreateDroplet	'CrtD'
Crop	'Crop'
Crosshatch	'Crsh'
Crystallize	'Crst'
Curves	'Crvs'
Custom	'Cstm'
Cut	'cut '
CutToLayer	'CtTL'
Cutout	'Ct '
DarkStrokes	'DrkS'
DeInterlace	'Dntr'
DefinePattern	'DfnP'
Defringe	'Dfrg'
Delete	'Dlt '
Desaturate	'Dstt'

Event	4-char ID or String
Deselect	'Dslc'
Despeckle	'Dspc'
DifferenceClouds	'DfrC'
Diffuse	'Dfs '
DiffuseGlow	'DfsG'
DisableLayerFX	'dlfx'
Displace	'Dspl'
Distribute	'Dstr'
Draw	'Draw'
DryBrush	'DryB'
Duplicate	'Dplc'
DustAndScratches	'DstS'
Emboss	'Embs'
Equalize	'Eqlz'
Exchange	'Exch'
Expand	'Expn'
Export	'Expr'
JumpTo	'Jpto'
ExportTransparentImage	"02879e00-cb66-11d1-bc43-0060b0a13dc4"
Extrude	'Extr'
Facet	'Fct '
Fade	'Fade'
Feather	'Fthr'
Fibers	'Fbrs'
Fill	'Fl '
FilmGrain	'FlmG'
Filter	'Fltr'
FindEdges	'FndE'
FitImage	"3caa3434-cb67-11d1-bc43-0060b0a13dc4"
FlattenImage	'FltI'
Flip	'Flip'
Fragment	'Frgm'

Event	4-char ID or String
Fresco	'Frsc'
GaussianBlur	'GsnB'
Get	'getd'
Glass	'Gls '
GlowingEdges	'GlwE'
Gradient	'Grdn'
GradientMap	'GrMp'
Grain	'Grn '
GraphicPen	'GraP'
Group	'GrpL'
Grow	'Grow'
HalftoneScreen	'Hlfs'
Hide	'Hd '
HighPass	'HghP'
HSBHSL	'HsbP'
HueSaturation	'HStr'
ImageSize	'ImgS'
Import	'Impr'
InkOutlines	'InkO'
Intersect	'Intr'
IntersectWith	'IntW'
Inverse	'Invs'
Invert	'Invr'
LensFlare	'LnsF'
Levels	'Lvls'
LightingEffects	'LghE'
Link	'Lnk '
Make	'Mk '
Maximum	'Mxm '
Median	'Mdn '
MergeLayers	'Mrg2'
MergeLayersOld	'MrgL'
MergeSpotChannel	'MSpt'

Event	4-char ID or String
MergeVisible	'MrgV'
Mezzotint	'Mztn'
Minimum	'Mnm '
ModeChange	"8cba8cd6-cb66-11d1-bc43-0060b0a13dc4"
Mosaic	'Msc '
Mosaic_PLUGIN	'MscT'
MotionBlur	'MtnB'
Move	'move'
NTSCColors	'NTSC'
NeonGlow	'NGLw'
Next	'Nxt '
NotePaper	'NtPr'
Notify	'Ntfy'
Null	typeNull
OceanRipple	'OcnR'
Offset	'Ofst'
Open	'Opn '
Paint	'Pnt '
PaintDaubs	'PntD'
PaletteKnife	'PltK'
Paste	'past'
PasteEffects	'PaFX'
PasteInto	'PstI'
PasteOutside	'PstO'
Patchwork	'Ptch'
Photocopy	'Phtc'
PicturePackage	"4C1ABF40-DD82-11d2-B20F-0008C75B322C"
Pinch	'Pnch'
Place	'Plc '
Plaster	'Plst'
PlasticWrap	'PlsW'
Play	'Ply '

Event	4-char ID or String
Pointillize	'Pntl'
Polar	'Plr '
PosterEdges	'PstE'
Posterize	'Pstr'
Previous	'Prvs'
Print	'Prnt'
ProfileToProfile	'PrfT'
Purge	'Prge'
Quit	'quit'
RadialBlur	'RdlB'
Rasterize	'Rstr'
RasterizeTypeSheet	'RstT'
RemoveBlackMatte	'RmvB'
RemoveLayerMask	'RmvL'
RemoveWhiteMatte	'RmvW'
Rename	'Rnm '
ReplaceColor	'RplC'
Reset	'Rset'
ResizeImage	"1333cf0c-cb67-11d1-bc43-0060b0a13dc4"
Reticulation	'Rtcl'
Revert	'Rvrt'
Ripple	'Rple'
Rotate	'Rtte'
RoughPastels	'RghP'
Save	'save'
Select	'slct'
SelectiveColor	'SlcC'
Set	'setd'
SharpenEdges	'ShrE'
Sharpen	'Shrp'
SharpenMore	'ShrM'
Shear	'Shr '
Show	'Shw '

Event	4-char ID or String
Similar	'Smlr'
SmartBlur	'SmrB'
Smooth	'Smth'
SmudgeStick	'SmdS'
Solarize	'Slrz'
Spatter	'Spt '
Spherize	'Sphr'
SplitChannels	'Sp1C'
Sponge	'Spng'
SprayedStrokes	'SprS'
StainedGlass	'StnG'
Stamp	'Stmp'
Stop	'Stop'
Stroke	'Strk'
Subtract	'Sbtr'
SubtractFrom	'SbtF'
Sumie	'Smie'
TakeMergedSnapshot	'TkMr'
TakeSnapshot	'TkSn'
TextureFill	'TxtF'
Texturizer	'Tztz'
Threshold	'Thrs'
Tiles	'Tls '
TornEdges	'TrnE'
TraceContour	'TrcC'
Transform	'Trnf'
Trap	'Trap'
Twirl	'Twrl'
Underpainting	'Undr'
Undo	'undo'
Ungroup	'Ungr'
Unlink	'Unlk'
UnsharpMask	'UnsM'

Event	4-char ID or String
Variations	'Vrtn'
Wait	'Wait'
WaterPaper	'WtrP'
Watercolor	'Wtrc'
Wave	'Wave'
Wind	'Wnd '
ZigZag	'ZgZg'
BackLight	'BacL'
FillFlash	'File'
ColorCast	'ColE'

Index

A

- Action Manager
 - scripting objects 8
- actions
 - executing 18
- active links 79
- Add Noise filter 26
- adjust
 - contrast 30
- AdjustBrightnessContrast 25
- adjusting
 - brightness 25
 - color balance 25
 - colors 158
 - component channels 32
 - curves 25
 - highlights 33
 - layers color balance 32
 - levels 26, 30
 - shadows 33
 - temperature 32
- Adobe Photoshop CS 2
 - activating 17
 - new features 5
 - version 17
- alpha channels
 - defined 43
- anchor points
 - path point info 115
 - path points 114
- anchor position
 - types 158
- annotations 64
- anti alias
 - text 149
 - types 158
- application
 - activating 17
 - checking if feature enabled 19
 - code sample 21
 - location 16
 - preferences 128
 - version 17
- art layers, *See* layers
- Asian text 130
- Average filter 26

B

- background color
 - application 16
 - galleries 79
- background layer
 - designating 24

- finding 60
- Batch command
 - destination folder 37
- batch command
 - destination types 158
 - input folder 18
- beep 128
- bitmap documents
 - converting to 39
 - opening 167
 - saving 40
- bitmap images
 - See* bitmap documents 39
- BitmapConversionOptions 39
- black and white images 33
- blend modes 159
- Blur filter 26
- blur filters
 - Average 26
 - Blur 26
 - Blur More 26
 - Gaussian Blur 27
 - Lens Blur 28
 - Motion Blur 29
 - Radial Blur 29
 - Smart Blur 30
- Blur More filter 26
- BMP documents
 - opening 167
 - saving 40
- brightness
 - adjusting 25
 - camera shots 41
 - equalizing 31

C

- caches
 - histograms 129
 - images 129
 - purging 20
- camera raw documents
 - opening 41, 167
- canvases
 - resizing 65
 - rotating 64
- captions
 - contact sheets 53
 - galleries 80
- channels
 - activating 60
 - adding 44, 56
 - alpha *See* alpha channels
 - code sample 44

- component *See* component channels 25
 - composite *See* composite channels
 - creating 56
 - deleting 43
 - displaying in color 128
 - making visible 43
 - merging (spot) 43
 - mixing 32
 - splitting 66
 - spot *See* spot channels
 - types of 160
 - clipping paths
 - creating 109
 - from text 154
 - Clouds filter 26
 - CMYK color 50
 - color picker 128, 160
 - color samplers
 - adding 52
 - creating 52
 - deleting 51
 - moving 51
 - colors
 - adjusting 25
 - blend modes 159
 - CMYK 50
 - comparing 142
 - forced 86, 163
 - gray 88
 - HSB 91
 - Lab 95
 - links 79
 - none 105
 - RGB 135
 - selective 33
 - solid color objects 142
 - component channels
 - color balance adjustments 25
 - defined 43
 - displaying in color 128
 - enabling 99
 - listing 60
 - merging with spot channels 43
 - mixing 32
 - composite channel
 - defined 43
 - Compuserve GIF documents
 - opening 167
 - saving 86
 - contact sheets
 - captions 53
 - dimensions 54
 - formatting 53
 - making 19
 - contrast
 - adjusting 25
 - adjusting automatically 30
 - copyrights 69, 161
 - curors 129
 - curves
 - adjusting 25
 - defining 29
 - Custom filter 26
- D**
- DCS1 documents
 - opening 167
 - saving 57
 - DCS2 documents
 - opening 167
 - saving 58
 - default units 130
 - De-Interlace filter 26
 - Deprecated 19
 - Despeckle filter 26
 - dialogs
 - displaying 16
 - modes 161
 - DICOM format documents
 - opening 59
 - Difference Clouds filter 26
 - Diffuse Glow filter 26
 - Displace filter 26
 - distort filters
 - Diffuse Glow 26
 - Displace 26
 - Glass Effect 27
 - Ocean Ripple 29
 - Pinch 29
 - Polar Coordinates 29
 - Ripple 29
 - Shear 29
 - Spherize 30
 - Twirl 30
 - Wave 30
 - Zigzag 30
 - documents
 - activating 16
 - adding 72
 - closing 63
 - color samplers 60
 - colors 60
 - counting items 61
 - counting objects 63
 - creating 72
 - cropping 64
 - exporting 64
 - loading 19
 - managed 61
 - measurement scale 61
 - metadata 25, 62, 69
 - open with Photoshop dialog 20
 - opening 20
 - printing 65
 - sample code 67
 - saving 66
 - size 61
 - specifying author 69
 - title 70

- trapping (CMYK) 66
- trimming 66

Dust & Scratches filter 27

E

- edit log 128
- EPS documents
 - opening 73, 167
 - saving 74
- equalizing, brightness values 31
- event IDs
 - using ScriptListener to find 175
- events, associating with actions 108
- EXIF 69
- exporting
 - documents 64
 - paths 75
 - to Illustrator 75
 - to the web 75
 - type of 162

F

- file extensions, case of 162
- file types
 - Macintosh 16
 - naming 163
 - Windows 17
- files
 - extensions 131
 - merging 19
 - naming types 163
- Filmstrips, opening 167
- filters
 - See individual filter names
- fonts
 - contact sheets 53
 - family 147
 - finding 16
 - gallery banners 78
 - gallery type 164
 - picture packages 124
 - PostScript names 147
- foreground color 16

G

- galleries
 - banners 78
 - constrain types 163
 - font type 164
 - image options 80
 - making 19
 - photographer 78
 - security options 84
 - security type 164
 - thumbnails 85
- Gaussian Blur filter 27
- GIF documents
 - opening 167

- saving 86

Glass Effect filter 27

GrayColor 88

grid options 129

guide options 129

H

- High Pass filter 27
- highlights 25, 33
- histograms
 - caches 129
 - channels 43
 - code sample 44
 - documents 61
- history states
 - activating 60
 - number of 129
 - snapshot 89
- HSBColor 91

I

- IDs
 - string to type 20
 - type to char 20
 - type to string 20
- images
 - black and white 33
 - cache level 129
 - gallery 80
 - previews 129
 - resizing 65
- indexed color model 92

J

- JavaScript
 - executing from VBScript 18
- JPEG documents
 - opening 167
 - saving 94
- justification 151, 164

K

- kerning
 - types of 158
- keyboard options 129
- keywords 70

L

- Lab color 95
- layer comps
 - adding 97
 - applying 96
 - using visibility in 96
- layer sets
 - adding 101
 - finding layers in 99
 - linking 100

- making visible 99
- moving 100
- nesting 99
- opacity 99
- sample code 101
- unlinking 100
- layer styles 30
- layers
 - activating 60
 - adding 36
 - adjusting 25–26
 - applying filters 26–30
 - applying styles to 30
 - background 24
 - clipboard commands 30–32
 - counting 98
 - flattening 65
 - grouping 24
 - kind 24
 - linking 31
 - locking contents 24–25
 - making visible 25
 - merging 31
 - rasterizing 32, 65
 - sample code 33
 - types 165
- left direction points 114
 - path point info 115
- Lens Blur filter
 - applying 28
- Lens Flare filter 28
- levels
 - adjusting 26
 - adjusting automatically 30
- link colors
 - active 79
 - visited 79
- linking layers 31

M

- Macintosh
 - compatibility in Batch command 37
 - file types 16
- Maximum filter 28
- Median Noise filter 28
- memory, available 16
- merging
 - channels 43
 - files 19
 - layer sets 100
 - layers 31
 - layers (in copy command) 136
 - visible layers 65
- metadata 157
- midtones 25
- Minimum filter 29
- Motion Blur filter 29

N

- nearest web color, finding 142
- new features 5
- noise filters
 - Add Noise 26
 - Despeckle 26
 - Dust & Scratches 27
 - Median Noise 28
- notifiers
 - adding 108
 - associating with actions 108
 - event IDs 175
 - removing 106
- NTSC filter 29

O

- Ocean Ripple filter 29
- Offset filter 29
- opacity
 - channels 43
 - layer sets 99
 - layers 24
 - picture packages 124
- open options
 - Camera RAW format 41
 - DICOM format 59
 - EPS format 73
 - PDF format 117
 - Photo CD format 121
 - raw format 133
- optimizing 75, 76
- other filters
 - Custom 26
 - High Pass 27
 - Maximum 28
 - Minimum 29
 - Offset 29

P

- palette locations 130
- paragraph text 172
- path items
 - adding 113
 - clipping path 109
 - filling 109
 - from selections 137
 - making selection 110
 - path segments 143
 - sample code 110
 - selecting 109
 - stroking 110
- path point info
 - anchor points 115
 - left/right direction points 115
 - subpath info items 143
- path points
 - anchor points 114
 - defined 116
 - left/right direction points 114

- paths
 - See path items
- PCX documents
 - opening 167
- PDF documents
 - opening 117, 167
 - saving 118
- PDF presentations
 - auto advance 132
 - code sample 23
 - making 19
 - transition type 132, 172
- photo galleries
 - See galleries
- Photo Merge 19
- PhotoCD documents, opening 121, 167
- Photoshop CS 2, See Adobe Photoshop CS 2
- Photoshop documents
 - opening 167
 - saving 122
- Photoshop PDF documents, opening 167
- PICT files
 - opening 167
 - saving 123
- PICT resources
 - opening 167
- picture packages
 - flattening layers in 124
 - making 20
 - specifying options 124
- Pinch filter 29
- Pixar documents
 - opening 167
 - saving 125
- plug-in
 - folders 131
- PNG documents
 - opening 167
 - saving 104, 126
- point text 172
- points
 - corner 169
 - PostScript 169
 - size 130
 - smooth 169
- Polar Coordinates filter 29
- PostScript font names 147
- preferences 128
- printing 65
- Pro Photo CD discs, opening files from 121
- property
 - measurementLog 16
- PSD documents
 - opening 167
 - saving 122
- psVideoLayer 165
- purging, caches 20

Q

- Quick Mask mode 61

R

- Radial Blur filter 29
- rasterizing 32
- raw documents
 - opening 133, 167
 - saving 134
- RecordMeasurements 65
- render filters
 - Clouds 26
 - Difference Clouds 26
 - Lens Flare 28
- RGBColor 135
- right direction points
 - defining 114
 - path point info 115
- Ripple filter 29
- ruler units 130, 173

S

- save as 66
- saving
 - See individual document formats
 - CompuServe GIF documents 86
 - ESP documents 74
 - GIF documents 86
 - JPEG documents 94
 - PDF documents 118
 - Photoshop documents 122
 - PICT files 123
 - Pixar documents 125
 - PNG documents 126
 - PSD documents 122
 - raw documents 134
 - SGIRGB documents 141
 - TIFF documents 155
- scripting build date 17
- scripting interface, new features 5
- ScriptingVersion 17
- Scripts Events Manager 16
- security, galleries 84
- selections
 - clearing 136
 - creating paths from 137
 - filling 136
 - from paths 110
 - inverting 137
 - resizing 137
 - sample code 138
- selective color 33
- SGIRGB documents
 - opening 167
 - saving 141, 158
- shadows 25, 33
- Sharpen Edges filter 29
- Sharpen filter 29
- sharpen filters

- Sharpen 29
 - Sharpen Edges 29
 - Sharpen More 29
 - Unsharp Mask 30
- Sharpen More filter 29
- Shear filter 29
- Smart Blur filter 30
- smart quotes 130
- Spherize filter 30
- spot channels
 - defined 43
 - merging 43
- styles, applying 30
- SystemInformation 17

T

- Targa documents
 - opening 167
 - saving 146
- text
 - Asian 130
 - creating paths from 154
 - creating selections from 154
 - fonts 150
 - formatting 149
 - gallery security 84
 - hyphenation 151
 - justification 151
 - paragraph 172
 - picture packages 124
 - point 172
 - warping 154
- text layers
 - contents 25, 149
 - creating 24, 165
 - sample code 101
- Texture Fill filter 30
- threshold 33
- thumbnails 85
 - sizes 164
 - specifications 85
- TIFF documents
 - opening 167
 - saving 155
- tool tips, displaying 130

- trapping 66
- Twirl filter 30
- type units 130, 172

U

- units
 - defaults 130
 - ruler 130, 173
 - type 130, 172
- Unix, compatibility in Batch commands 38
- Unsharp Mask filter 30
- urgency 70
- UTF8 encoding 83

V

- video filters
 - De-Interlace 26
 - NTSC 29
- visibility
 - application 17
 - channels 43
 - layer sets 99
 - layers 25
- visited links 79

W

- warp 154
- Wave filter
 - applying 30
 - type 173
- web snap 77
- white balance 42, 173
- Windows
 - color settings 17
 - compatibility in Batch commands 38
 - file types 17

X

- xml 157
- xmp metadata 157

Z

- Zigzag filter 30